




Aluminium-U-Profil


Güte: EN AW 6060 T66, AlMgSi 0,5 F22
Normen: EN 573-3 / EN 755-1 / -2 / -9
Eloxalqualität
Länge: 6 Meter



Abmessung H x B x S mm	Gewicht kg/mtr.	Abmessung H x B x S mm	Gewicht kg/mtr.	Abmessung H x B x S mm	Gewicht kg/mtr.	Abmessung H x B x S mm	Gewicht kg/mtr.
10 x 10 x 2	0,140	35 x 20 x 2	0,383	50 x 40 x 3	1,004	80 x 50 x 3	1,409
10 x 20 x 2	0,248	35 x 25 x 2	0,437	50 x 40 x 4	1,318	80 x 50 x 5	2,295
12 x 12 x 2	0,173	35 x 35 x 2	0,545	50 x 50 x 2	0,788	80 x 60 x 5	2,565
14 x 16 x 2	0,227	35 x 35 x 3	0,802	50 x 50 x 3	1,166	80 x 80 x 4	2,506
15 x 15 x 2	0,221	40 x 15 x 2	0,356	50 x 50 x 4	1,534	90 x 20 x 2,5	0,844
15 x 20 x 2	0,275	40 x 20 x 2	0,410	50 x 50 x 5	1,890	90 x 40 x 3	1,328
20 x 10 x 2	0,194	40 x 20 x 2,5	0,506	60 x 20 x 2	0,518	90 x 50 x 3	1,490
20 x 15 x 2	0,248	40 x 20 x 3	0,599	60 x 30 x 3	0,923	90 x 50 x 5	2,430
20 x 20 x 2	0,302	40 x 25 x 2	0,464	60 x 40 x 3	1,085	100 x 20 x 2	0,734
20 x 20 x 3	0,437	40 x 25 x 3	0,680	60 x 40 x 4	1,426	100 x 40 x 3	1,409
20 x 25 x 2	0,356	40 x 25 x 4	0,886	60 x 40 x 5	1,755	100 x 50 x 3	1,571
20 x 30 x 2	0,410	40 x 30 x 2	0,518	60 x 50 x 2	0,842	100 x 50 x 5	2,565
20 x 40 x 2	0,518	40 x 30 x 3	0,761	60 x 50 x 3	1,247	100 x 50 x 10	4,860
20 x 40 x 2,5	0,641	40 x 40 x 2	0,626	60 x 60 x 3	1,409	110 x 40 x 3	1,490
25 x 15 x 2	0,275	40 x 40 x 3	0,923	60 x 60 x 4	1,858	120 x 20 x 2,5	1,046
25 x 20 x 2	0,329	40 x 40 x 4	1,210	60 x 60 x 5	2,295	120 x 40 x 3	1,571
25 x 25 x 2	0,383	40 x 40 x 5	1,485	65 x 25 x 2,5	0,743	140 x 40 x 3	1,733
25 x 25 x 3	0,559	40 x 50 x 2	0,734	65 x 55 x 2,5	1,148	140 x 40 x 6	3,370
30 x 15 x 2	0,302	40 x 60 x 4	1,642	70 x 35 x 3	1,850	140 x 60 x 6	4,018
30 x 15 x 3	0,437	45 x 25 x 3	0,721	70 x 40 x 3	1,166	150 x 30 x 4	2,182
30 x 20 x 2	0,356	50 x 15 x 2	0,410	70 x 40 x 4	1,534	150 x 37 x 3	1,766
30 x 20 x 3	0,518	50 x 20 x 2	0,464	80 x 20 x 2	0,626	160 x 80 x 8	6,566
30 x 30 x 2	0,464	50 x 20 x 3	0,680	80 x 30 x 3	1,085	200 x 40 x 3	2,219
30 x 30 x 3	0,680	50 x 25 x 2	0,518	80 x 40 x 3	1,247	220 x 20 x 4	2,722
30 x 40 x 3	0,842	50 x 30 x 2	0,572	80 x 40 x 4	1,642	260 x 38 x 3	2,673
30 x 50 x 3	1,004	50 x 30 x 3	0,842	80 x 40 x 5	2,025		
30 x 60 x 2	0,788	50 x 30 x 4	1,102	80 x 40 x 6	2,398		

Aluminium-Rundstange


Güte: EN AW 6060 T66, AlMgSi 0,5 F22
Normen: EN 573-3 / EN 755-1 / -2 / -3
Eloxalqualität
Länge: 6 Meter



Abmessung mm	Gewicht kg/mtr.
6	0,080
8	0,140
10	0,212
12	0,350
15	0,480
18	0,680
20	0,850
25	1,320
30	1,910
35	2,610
40	3,390
45	4,300
50	5,300
60	7,630
70	10,390
80	13,800
100	21,220

Aluminium-Vierkantstange

Güte: EN AW 6060 T66 , AlMgSi 0,5, F 22
Normen: 373-3 / EN 755-1 / -2 / -4
Eloxalqualität
Länge: 6 Meter



Abmessung mm	Gewicht kg/mtr.
6	0,097
8	0,175
10	0,270
12	0,390
15	0,610
20	1,080
25	1,690
30	2,430
35	3,300
40	4,320
50	6,750
60	9,720
80	17,280
100	27,000

Weitere Abmessungen und Werkstoffe kurzfristig lieferbar!