

# Micador For Artists Fixative

## 1. Product Identifier & Identity for the Chemical

<b>Product Code &amp; Name</b>	<b>PCA045, PCA048</b> Micador For Artists Fixative 450g 175g
<b>Other names</b>	\
<b>Recommended use</b>	Art and Craft
<b>Restrictions on use</b>	Adult product – Not a Toy. Always test spray on samples product prior to using on final work.
<b>Date issued</b>	<b>28<sup>th</sup> September 2021</b>
<b>Company name</b>	Micador Australia Pty Ltd, Micador International Pty Ltd
<b>ABN</b>	98 004 509 880, 90 004 624 800
<b>Address</b>	3 Park Rd, Cheltenham Victoria 3192 Australia PO Box 4218, Black Rock, Victoria, 3193, Australia
<b>Emergency phone</b>	+61 3 8788 1800 (Monday – Friday from 8.30am – 5.00pm)
<b>Phone</b>	+61 3 8788 1800
<b>Email</b>	<a href="mailto:safety@micador.com.au">safety@micador.com.au</a>

### Poisons Information Centre

<b>AUSTRALIA</b>	13 11 26
<b>NEW ZEALAND</b>	0800 764 766 or 0800 POISON
<b>OTHER</b>	Contact your local country poison centre

## 2. Hazard Identification

**Hazard Classification** This product is classified as hazardous under Australian WHS Regulations. This product is classified as a Dangerous Good by the Australian Dangerous Goods Code.

Flammable Aerosols, Cat 1  
Compressed Gas  
Skin Corrosion, Cat 2  
Serious Eye Damage, Cat 2B  
Specific Target Organ  
Single Exposure Cat 3  
Carcinogenicity, Cat 2

**Hazard Statement(s)** Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.  
H222 Extremely flammable aerosol.  
H280 Contain gas under pressure; may explode if heated.  
H315 Causes skin irritation  
H320 Causes eye irritation  
H335 May cause respiratory irritation  
H336 May cause drowsiness or dizziness  
H351 Suspected of causing cancer

**Signal** Danger

## 3. Composition/Information on Ingredients

### Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P260 Do not breathe dust/fumes/gas/mist/vapours/spray.  
P271 Use only in a well-ventilated area.  
P312 Call a POISON CENTER/ doctor if you feel unwell.  
P305 IF IN EYES: wash out immediately with water.  
P302 IF ON SKIN: remove contaminated clothing and wash thoroughly.  
P301 + P331 IF SWALLOWED: rinse mouth with water. Do NOT induce vomiting.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

For further health and safety information please refer to the full SDS.

Note: This product should not be used in any purpose or manner contrary to recommended use unless authorised.

## 4. First Aid Measures

Chemical Name	CAS Number	Proportion
Dichloromethane	75-09-2	10-30%
Ethanol	64-17-5	30-60%
Hydrocarbon propellant		30-60%
- Propane	74-98-6	
- Butane	106-97-8	
Other ingredients		to 100%

## 5. Fire Fighting Measures

For advice, contact a Poisons Information Centre 131126 or a doctor. Ensure medical personnel are aware of the identity and nature (hydrocarbon propelled aerosol) involved.

**Inhalation:** Remove victim to fresh air to prevent further exposure. Propane is an asphyxiant. If breathing difficulties are experienced, seek immediate medical care. Do not use direct mouth to mouth method of resuscitation, use alternative respiratory method.

**Skin Contact:** Remove contaminated clothing and shoes and wash well skin with warm soapy water. If irritation persists, contact a doctor

**Eye Contact:** Flush out immediately with running water for at least 15 minutes. If symptoms persist, seek medical attention.

**Ingestion:** Due to high volatility of product, this is not likely to occur. If sprayed in mouth, rinse mouth with plenty of water. If swallowed, do NOT induce vomiting. Seek medical attention.

Beware- heat greater than 50 C / 122 °F may cause these extremely flammable, pressurised dispensers to rupture, and violently rocket in various directions. These rockets will release flammable and potentially toxic gasses, which will increase the risk of fire spreading. In extinguishing any fire beware of any residual unburnt gas that could reignite.

<b>Suitable Extinguishing Media</b>	Small fire: Use water spray/fog/foam, dry chemical or carbon dioxide (CO2). Large fire: Use water spray/fog/foam.
<b>Hazards</b>	Aerosols may rupture and rocket (become projectiles) when exposed to excessive heat. Released gases can form extremely flammable, invisible, odourless explosive mixtures with air. Released gases can be heavier than air and travel to source of ignition causing flashback. Hazardous concentrations can accumulate in a confined space (pits, low laying areas). Fire can produce irritating, poisonous and corrosive gases. High concentration of gas could cause dizziness or asphyxiation without warning
<b>Precautions / PPE</b>	For large quantities, consider initial evacuation for at least 100m in all directions. Fight fire from protected position or use unmanned hose holders or monitor nozzles. Use spark-proof tools and explosion-proof equipment. Wear SCBA and protective gloves. Structural firefighter's uniform provides limited protection. If large amounts are involved, wear SCBA and chemical splash suit. If impossible to safely extinguish fire, protect surroundings, withdraw from area and allow fire to burn.
<b>Hazchem Code (for Placarding and transport only)</b>	If safe to do so, move undamaged aerosols from fire area but do not approach hot aerosols. Cool aerosols with water before handling. 2YE Class 2 flammable Gas



## 6. Accidental Release Measures

<b>Personal Precautions, PPE and Emergency Procedures</b>	<p>Spill is flammable (until LPG dissipates). Eliminate all sources of ignition including static discharge. Wear protective gloves and safety glasses to prevent contamination of skin and eyes.</p> <p>Minor spills: Keep area well ventilated and wipe up.</p> <p>Major spills:</p> <p>Isolate spill or leak area for at least 8 m in all directions. Eliminate all sources of ignition within at least 15 m.</p> <p>Keep upwind and to higher ground (propellant gas is heavier than air and will seek low points, pay special attention to drains and pits- these will likely be explosive environments).</p> <p>Major fire:</p>
<b>Environmental Precautions</b>	<p>Consider initial evacuation for at least 100 m in all directions</p> <p>Notify police and fire brigade of the location, material, UN Number, quantity and emergency contact as well as condition and damage observed.</p> <p>Keep leaking containers away from drains, surface and ground water.</p> <p>Ensure leakage does not enter streams, sewers or drinking water supply.</p>
<b>Containment / Clean up Procedures</b>	<p>Eliminate all ignition sources, including static within at least 15 m. All equipment used when handling the product must be earthed.</p> <p>If water is available, spray leaking containers to reduce ignition hazard and disperse gas. Isolate area until gas has dispersed. Ventilate area. Avoid release to the environment. Do not empty into drains or natural waterways.</p> <p>Absorb spill with inert absorbent material (e.g. dry sand or earth) for disposal using an approved method or following local regulations.</p>

## 7. Handling and Storage

<b>Precautions for Safe Handling</b>	<p>Ensure spray nozzle is always directed away from user. Do not pierce or burn can after use. Extremely flammable- Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Do not breathe concentrated, vapour, mist or spray. Local exhaust ventilation may be necessary to minimise excessive vapour concentration (as long as they do not introduce risk of ignition), if levels are likely to be high or in a confined space.</p>
<b>Conditions for Safe Storage</b>	<p>Keep out of reach of children. Store in a well-ventilated area, away from damp or corrosive conditions. Protect from sunlight and do not expose to temperatures exceeding 50 °C / 122 °F. Store in accordance with Dangerous Goods Regulations and transport in accordance with the ADG Code for Dangerous Goods Class 2.1</p>

## 8. Exposure Controls/Personal Protection

<b>National Exposure Standards</b>	<p>There is no established TLV (Threshold Limit Value) for this product.</p> <p>Avoid exposure – obtain special instructions before use.</p> <p>Butane - TWA (Time-Weighted Average) is 800ppm / 1900mg/m<sup>3</sup></p> <p>Propane is an asphyxiant</p>
------------------------------------	---

# SAFETY DATA SHEET (SDS)

<b>Biological Limit Values</b>	Not available.
<b>Engineering Controls</b>	No smoking. No flames or sources of ignition. Local exhaust ventilation may be necessary to minimise excessive vapour concentration, if levels are likely to be high or in a confined space.
<b>Personal Protective Equipment (PPE)</b>	Personal Protective Equipment is not required under normal conditions of use. When handling bulk quantities, wear protective gloves and safety glasses. Do not exceed exposure limits. .

## 9. Physical and Chemical Properties

<b>Appearance</b>	Aerosol, Fine clear spray
<b>Odour</b>	Solvent like
<b>pH</b>	Not available
<b>Vapour Pressure</b>	Not available
<b>Vapour Density</b>	Not available
<b>Boiling point (propellant)</b>	-42 to 0°C
<b>Solubility in Water</b>	Immiscible
<b>Specific Gravity (propellant)</b>	0.58 approx.
<b>Flash Point (propellant)</b>	-104 to -60°C
<b>Flammable limits (propellant)</b>	1.5% to 9.6% in air (v/v)
<b>Ignition Temperature (propellant)</b>	494°C to 600°C

## 10. Stability and reactivity

<b>Chemical Stability</b>	Stable under normal ambient conditions of storage and use. Avoid heat sources. Aerosol cans may explode/burst violently when subject to extremes of heat or pressure and may become projectiles.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid static charge and discharge with high concentrations and in confined space. Avoid damp or corrosive conditions.
<b>Incompatible Materials / Hazardous Reactions</b>	Can react violently with oxidising agents – chlorine, pool chlorine or nitric acid.
<b>Hazardous Decomposition Products</b>	Products may include oxides of carbon and nitrogen.

## 11. Toxicological information

<b>Potential adverse health effects and symptoms associated with exposure to the material</b>	<p>Vapours may cause light-headedness, drowsiness and dizziness.</p> <p><b>Ingestion:</b> Unlikely due to high volatility of product, but maybe harmful if swallowed.</p> <p><b>Eyes:</b> Liquid may cause damage. Vapour may cause irritation.</p> <p><b>Skin:</b> May cause cold burn. Irritating to skin.</p> <p><b>Inhalation:</b> Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. May cause light-headedness, dizziness and drowsiness. Excessive exposure may cause unconsciousness or even death, due to asphyxiation.</p>
---	---

## 12. Ecological information

The information provided is based on data available for the material and the components of the material.

<b>Ecotoxicity / Persistence / Degradability / Mobility</b>	Propellant will vaporise rapidly when released to atmosphere. Propellant consists of hydrocarbons that photo chemically decompose under atmospheric conditions.
---	--

## 13. Disposal considerations

Disposal of material must comply with local laws and regulations at time of disposal.

<b>Consumer Instructions</b>	Do not pierce or burn can. Containers can be disposed of in the normal household waste stream. Recycle empty can.
<b>Bulk quantities</b>	Dispose of according to Local, State and National regulations.

## 14. Transport information

Transport in accordance with the requirements of ADG Code.

<b>UN Number</b>	1950
<b>Proper Shipping Name (ADG 7, IMDG)</b>	AEROSOLS
<b>Proper Shipping name (IATA)</b>	AEROSOLS, FLAMMABLE
<b>EMS Code</b>	F-D, S-U
<b>Emergency Procedure Guide</b>	2D1
<b>Class and subsidiary risk(s)</b>	2.1
<b>Packaging Group</b>	None allocated
<b>Hazchem Code</b>	2YE
<b>Special Precautions for Users</b>	Keep out of reach of children. Spray in well-ventilated area. Keep away from sources of ignition – No smoking. Extremely flammable - Do not spray on a naked flame or any incandescent material.

## 15. Regulatory information

<b>Poisons Schedule</b>	Not applicable
<b>Additional information</b>	Not applicable

