## Nordtrack™ CT85 & CT100 Heavy-duty tracked mobile stacking conveyors

#### Made to give you dependable, heavy-duty performance

Nordtrack<sup>™</sup> CT85 and CT100 tracked stacking conveyors deliver heavy-duty reliability combined with convenient mobility. They include remote controlled crawler tracks as standard for easy on-site positioning. They also give you the capacity you need to replace wheel loaders.

Heavy-duty construction and easy servicing for continuous performance

Different hopper options for higher volumes

Agile and easy to move on-site Remote controlled hydraulically driven crawler tracks

> Nordtrack™ CT100 pictured Available only in North America



More cost-effective than wheel loaders



Mobile and easy to move on-site



Reduces traffic on-site for improved health and safety



Reliable, heavy-duty performance

### Technical details Nordtrack™ CT85 & CT100

# Metso





Nordtrack™ CT85 mobile stacking conveyor

Belt length 24.4 m (80') Belt width

900 mm (36")

Hopper capacity 1.5 m<sup>3</sup> (2.0 yd<sup>3</sup>) Stockpile height 10.0 m (32' 10")

Capacity

Stockpile capacity 1,848 m<sup>3</sup> (2418 yd<sup>3</sup>)

#### Nordtrack™ CT100 mobile stacking conveyor

Belt length 30.5 m (100') Belt width

900 mm (36")

Hopper capacity 1.5 m<sup>3</sup> (2.0 yd<sup>3</sup>) Stockpile height 12.4 m (40' 7") Stockpile capacity 3,490 m<sup>3</sup> (4565 yd<sup>3</sup>) Drive options



Diesel engine Tier 4F: CAT C2.2 37 kW (49 hp) Tier 4F - power upgrade: CAT C2.8 55 kW (74 hp)

Diesel engine Tier 4F: CAT C2.8 55 kW (74 hp) Tier 4F - power upgrade: CAT C3.4 75 kW (100 hp) Transport dimensions



Weight 11.4 † (25,000 lbs) Width 2.5 m (8' 2") Height 3.5 m (11' 3") Length 15.8 m (51' 8")

Weight 12.7 t (28,000 lbs) Width 2.6 m (8' 5") Height 3.5 m (11' 4") Length 21.3 m (69' 9")

