

Nordtrack™ S2.11 mobile scalping screen

Heavy duty high capacity screening

Made to deliver versatile, all around screening

The Nordtrack™ S2.11 mobile scalping screen handles massive volumes of feed material with precision. It gives you the flexibility to screen a wide variety of feed materials in different recycling, demolition and aggregate applications, and is able to reach over 800 tph screening potential depending on application.

High capacity feeder with durable structure

- Belt feeder
- Apron feeder*
- Highly resistant wear plates
- Remote controller for feeder speed and on/off

High volumes and precision

Wide fines conveyor

High capacity versatile screening

- Massive screenbox
- Extensive screening media choice

Areas of application:



Concrete waste screening



Sand and gravel



Agricultural materials screening



Aggregate screening

Efficient dust suppression

Water spraying system with pump*

Fuel efficient drive system

Dual Power upgrade kit to drive the hydraulics with external electric power*

Possibility for two-way split*



High capacity screening



Wide range of media options
for different applications



Easy to control and move on-site



Durable and reliable design

* Optional, not included in standard delivery

Screen



Top deck
6,100 x 1,800 m (20' x 6')

Bottom deck
5,500 x 1,800 m (18' x 6')

Options for screening media

- Punch plate
- Plate grizzly / bofor bar
- Heavy duty fingers
- Woven screen mesh

Stroke

10 mm

Feeder



Belt feeder as standard, apron feeder as option

Hopper capacity
11.5 m³ (15.0 yd³)

Conveyors



Fines conveyor
1,050 mm (42")

Mid-fraction conveyor
900 mm (36")

Oversize conveyor
1,600 mm (64")

Engine options



Tier 3 (Stage III A):
CAT C7.1 209 kW (281 hp)

Tier 4F:
CAT C7.1 168 kW 225 (hp)

Stage V:
CAT C7.1 168 kW (225 hp)

Transport dimensions



Weight
37.2 t (82,000 lbs)

Width
3.0 m (9' 10")

Height
3.5 m (11' 6")

Length
17.0 m (55' 8")

