

FUTURE-PROOF COMMUNICATORS FOR THE ALARM BUSINESS



MN02-LTE-M



FUTURE-PROOF TECHNOLOGY LTE-M on AT&T and Verizon networks (model specific)

REMOTE PANEL PROGRAMMING Upload/Download via RING/TIP to selected panels



\$

×

INTERACTIVE FEATURES Smartphone App for end users and Admin App for installers

IMPROVED RECURRING REVENUE Flat-rate low monthly fees for improved profitability



www.m2mservices.com





EV MAIN FEATURES

UNIVERSAL PANEL COMPATIBILITY – Dial Capture Interface supporting Contact ID, SIA and Pulse 4+2 UPLOAD/DOWNLOAD for selected panels: DSC, Honeywell and NX series REMOTE ARM/ DISARM/ STAY ARM of multiple partitions via keybus for selected panels EXCEPTIONAL REDUNDANCY – Dual-SIM, supporting AT&T and Verizon (model specific) SUPERVISED CONNECTIVITY – 10 minute polling of the connection ADMIN PORTAL – Online 24/7 device management & real-time status monitoring of all accounts

Remote Upload/Download







The UDL software you are familiar with – DLS, Compass, DL900

MN02-LTE-M and MN01-RNGR connected to alarm panel

MN02-LTE-M supports remote UDL via add-on MN01-RNGR module connected to the RING/TIP terminals for selected panels (DSC, Honeywell and GE NX series)

🗟 MN02-LTE-M SPECIFICATIONS

- Multi-band LTE-M 700/850/1700/1900/2100 MHz
- 1 input & 1 output (programmable)
- Supply voltage: +12 to +15 VDC
- Consumption: Standby 15mA, Peak 200mA
- Dimensions: 1.6" x 1.95" x 0.8"
- Weight: 1oz without antenna

CERTIFICATIONS

985 • Household Fire Warning Systems 1023 • Household Burglar Alarm Systems

1610 • Central-Station Burglar-Alarm Units

SMARTPHONE APPs FOR END USERS & INSTALLERS

- RControl and RControl Admin for Android / iPhone
- Remote ARM / DISARM
- Real-time push and email notifications
- Multiple end users and devices per account
- 12 months of event history
- Configuration and diagnostics





www.m2mservices.com