

**M2M**  
SERVICES

SIMPLICITY.  
APPLIED.

# UNIVERSAL CELLULAR COMMUNICATOR FOR THE ALARM BUSINESS



**MQ03-LTE-M**

**5G** READY

now with  
**LTE-M**

**RED**



## **FUTURE-PROOF LTE-M TECHNOLOGY**

with Dual-SIM, each supporting multiple operators per country



## **FAST AND EASY INSTALLATION**

with any panel using Contact ID, SIA and Pulse 4+2



## **RELIABLE DATA REPORTING**

to any Alarm Receiving Center



## **IMPROVED RECURRING REVENUE**

Low flat-rate monthly fees for improved profitability

## MAIN FEATURES

**REPORTING FORMATS** – Dial Capture Interface supporting Contact ID, SIA and Pulse 4+2

**EXCEPTIONAL REDUNDANCY** – Dual-SIM device, each SIM supporting multiple operators per country

**SUPERVISED CONNECTIVITY** – 10-minute polling of the connection

**ADMIN PORTAL** – Online 24/7 device management & real-time status monitoring of user accounts

**FULL EVENT REPORTING** – Reliable reporting to any Alarm Receiving Center

**INSTALLER MOBILE APP** – Real-time on-site communication diagnostics and device configuration

**UNIVERSAL PANEL COMPATIBILITY** – Works on 12 to 29 VDC, supporting a wide range of alarm panels

### SPECIFICATIONS

- Multi-band CAT-M1 LTE  
700/850/1700/1900/2100 MHz
- Dial Capture interface supporting CID, SIA, Pulse 4+2
- 2 inputs & 2 outputs (programmable)
- Supply voltage: +12 to +29 VDC
- Consumption: Standby 50mA, Peak 200mA
- Dimensions: 63 x 90 x 32 mm
- Weight: 73 g without antenna

### CERTIFICATIONS

- EN 50136
- EN 50131

### RCONTROL MOBILE APP

