



## Complete Plasticizing barrels

For inquiries, please use our website [contact form](#).

**Always provide the machine serial number and the required injection unit size, so we can verify the fitment individually.**

List No.	Diameter (mm)	Quality	Geometry	Suitable Injection Units	Condition	Execution
1	70V (L/D 24)	M3 + S8	G16S	1640, 1800	like new	EU
2	55 (L/D 20)	M3 + S8	G1.2	765, 860, 1060	like new	EU
3	18 (L/D 24)	M3 + S10	G1.2	50, 60	like new	EU
4	35 (L/D 20)	M3 + S10	G1.2	265, 320, 460, 465	like new	US
5	80 (L/D 20)	M3		2050, 2440, 2550	like new	EU
6	40 (L/D 16)	M3 + S1	LIM	330, 440, 500	like new	
7	30 (L/D 23.6)	M3 + S8	G1.2	265, 320, 460, 465	like new	EU
8	35 (L/D 20)	M9 + S10	G1.2	265, 320, 460, 465	like new	US
9	45 (L/D 20)	M3 + S8	G1.2	330, 440, 500	like new	EU

10	40 (L/D 20)	M3 + S8	G1.2	265, 320, 460, 465	like new	EU
11	22V (L/D 24)	M9 + S10	G1.2	210	like new	EU
12	35 (L/D 20)	M9 + S10	G1.2	265, 320, 460, 465	like new	EU
13	40 (L/D 20)	M3 + S10	G1.2	765, 860, 1060	like new	US
14	40 (L/D 20)	M3	G1.2	320/460/465	like new	can be modified
15	40 (L/D 20)	M3	G1.2	320/460/465	like new	can be modified
16	35 (L/D 20)	M3	G1.2	320/460/465	like new	can be modified
17	35 (L/D 20)	M3	G1.2	320/460/465	like new	can be modified
18	40 (L/D 20)	M3 + S8	G1.2	320/460/465	like new	can be modified
19	22 (L/D 24)	M3	G1.2	170/200	like new	can be modified
20	18 (L/D 24)	M3 + S10	G1.2	50/60	like new	can be modified
21	40 (L/D 16)	M3 + S1	LIM	330/440/500	like new	
22	55 (L/D 20)	M3 + S8	G1.2	765/860/1060	like new	can be modified
23	60 (L/D 20)	M3	G1.2	1560/1565	like new	can be modified
24	25 (L/D 24.8)	M9	G1.2	170/200	like new	can be modified
25	30 (L/D 16)	M3	LIM	265/310/330/500	like new	