

PHYSICAL PROPERTIES AVONITE® ECLIPSE 8240

Aristech Surfaces' Avonite Acrylic Solid Surface "Specialty Blend Solid Surface" sheet products in a variety of attractive colors provide exceptionally weatherable, strong, non-porous, scratch and stain resistant material for architectural designs and utilitarian surfaces.

PROPERTY	UNITS	12 MM	TEST METHOD
General			
Nominal Thickness*	mm	12	-
Density	g/cm ³	1.73	ASTM D 792
Water Absorption	%	0.05	ASTM D 570
Mechanical			
Tensile Strength	MPa	45.5	ASTM D 638
Tensile Modulus	MPa	10,640	ASTM D 638
Tensile Elongation	%	0.50	ASTM D 638
Flexural Strength	MPa	82.7	ASTM D 790
Flexural Modulus	MPa	8,970	ASTM D 790
Barcol Hardness	-	65	ASTM D 2583
Rockwell Hardness (M Scale)	-	92	ASTM D 785
Charpy Impact	J/m	55.8	ASTM D 6110
Ball Impact (½ lb. ball, no failure)	cm	350	NEMA LD3-3.8
Thermal			
DTUL @ 264 psi	°C	98	ASTM D 648
Coefficient of Thermal Expansion	cm/cm/°C	3.5 x 10 ⁻⁵	ASTM D 696
Boiling Water Resistance	-	No Effect	ISFA 2-01
High Temperature Resistance	-	No Effect	ISFA 2-01
Reaction to Fire	-	Class A	ASTM E 84
Combustion Toxicity	-	98	Pittsburgh Protocol
Total volatile Organic Compounds	µg/m²/hr	69.1	ASTM D 5116
Surface			
Consistency Of Color (Same Sheet)	-	Passes	ISFA 2-01
Light Resistance	-	No Effect	ISFA 2-01
Cleanability/Stain Resistance	-	Passes	NEMA LD3-3.4
Stain Resistance	-	Passes	ANZI/ICPA SS-1
Bacterial Resistance	-	No growth	ASTM G 22
Fungi Resistance	-	No growth	ASTM G 21
Food Zone Use	-	Approved	NSF 51







Note: for cautions and information on exposure to any Aristech Surfaces' product, please see the applicable material safety data sheet.

Information contained herein is: a) based on Aristech Surfaces' available technical data and experience; b) intended only for individuals having applicable technical skill, with such individuals assuming full responsibility for all design, fabrication, installation, and hazards; c) to be used with discretion and at one's own risk, after consultation with local codes and with one's independent determination that the product is suitable for the intended use; and d) not to be used to create designs, specifications, or installation guidelines. Aristech Surfaces makes no representation, or warranty, express or implied, and assumes no liability or responsibility as to: i) the accuracy, completeness or applicability of any supplied information; ii) results obtained from use of the information, whether or not resulting from Aristech Surfaces' negligence; iii) title, and/or non-infringement of third party intellectual property rights; iv) the merchantability, fitness or suitability of the product for any purpose; or v) health or safety hazards resulting from exposure to or use of the product. Aristech Surfaces shall not be liable for x) any damages, including claims relating to the specification, installation, or combination of this product with any other product(s), and y) special, direct, indirect or consequential damages.





2