



Welcome to ROTHENBERGER!

ROTHENBERGER was founded in 1949 as a trading company for tools, machines and welding technology. As early as 1967, ROTHENBERGER developed the first system solution: the R-System. It consisted of tools for expanding, extracting and bending pipes—revolutionary equipment that enabled installers to connect pipes without fittings. This allowed plumbers to install drinking water and heating systems much more efficiently.

Today, ROTHENBERGER serves installers and ACR technicians worldwide with products which have been co-developed, tested and improved by professional users.







Focus on users

At ROTHENBERGER, we focus on professionals in the sanitary, refrigeration and air conditioning sectors. Day after day, they face challenges on construction sites and in services. They need tools they can rely on. That's why ROTHENBERGER manufactures tools and machines are so easy to use. Our products are characterized by the highest quality and we are driven by innovation. Customers all over the world appreciate the reliability, durability and technical innovation of ROTHENBERGER pipe tools. Your demands are our motivation! To get the work done that needs to be done. Each and every day. Safe, fast and reliable.







Quality from the start

For more than 75 years, ROTHENBERGER has focused on customer satisfaction and success: from product development to production and quality control to service. We develop high quality, high performance and technically advanced pipe tools and machines.

Every development process begins with the specific needs of our users. We listen carefully, analyze the requirements and use our experience to create innovative solutions. ROTHENBERGER's production facilities use state-of-the-art technologies and processes to develop tools and machines while maintaining a high proportion of inhouse production—by professionals for professionals!







Sustainability means responsibility

In times of climate change and energy crisis, environmental protection is an important task for our society. ROTHENBERGER is taking responsibility and is committed to be climateneutral. Since 2020, we have been operating photovoltaic systems with monocrystalline solar cells on the roofs of all buildings at the Kelkheim (Taunus) site in Germany.

Sustainability is a key concern for ROTHENBERGER. That is why we are focused on durable products, system solutions and batteries that can be used across manufacturers. This saves material, costs and valuable resources. Another great example of this is our ROCASE case system which enables safe tool storage and reduces packaging waste.







"Sustained by"

Every used tool whose product life cycle has been extended by a repair or upgrade and is sold again receives the "Sustained by" sticker.

This shows that you have made a contribution to sustainability with your purchase and that a fixed amount of the sales profits has been donated to a climate protection project.

CAS—Cordless Alliance System



ROTHENBERGER, as one of the founding members, has been offering a comprehensive range of CAS cordless tools since 2018. The range extends from sanitary installations to refrigeration and air conditioning technology to service area. The proven battery and charging technology is developed by Metabo and is fully compatible with CAS products from other manufacturers.





AMPShare—Powered by Bosch

ROTHENBERGER has been a founding member of the AMPShare battery platform since 2022. It is based on the 18 V battery technology from Bosch. The batteries and chargers of this alliance are fully compatible with all AMPShare tools and machines of the alliance partners as well as with the battery-powered 18 V tools from Bosch Professional. In future, all ROTHENBERGER battery tools will be offered with an AMPShare interface.







Collect BONUS POINTS and benefit from rewards!

With ROTHENBERGER tools you earn bonus points that you can exchange for fantastic rewards. And the best thing about it: Our portfolio of bonus point products is constantly being expanded so that you always have a varied selection.





RO SERVICE+ for professionals: Always there for you!

Our maintenance and repair service ensures that your tools are ready for use again quickly and immediately. On request, we can pick it up, solve the problem and deliver the tool directly to the construction site. Simply use our portal and we will help you: rothenberger.com/roservice-portal



How to contact us

You can contact us via many channels—via our website rothenberger.com by email to info@rothenberger.com or by phone via our customer and technical customer service hotlines.









Visit us on Facebook, Instagram, YouTube and LinkedIn!



THE PRESS
MACHINES
INNOVATION!

Product details on page 26

ROMAX NANO: Small, slim, smart—the world's lightest 32 kN press machine!



The ROMAX NANO is the world's smallest and lightest 32 kN press machine for fittings made of metal, plastic and multilayer composite systems for nominal sizes of 12–110 mm (1/4–1.3/8").

The combination of eDirectDrive drive and 2-in-1 pressing jaw holder make the press machine particularly flexible. It is compatible with the particularly compact NANO iJAWS and standard jaws of the ROTHENBERGER R-System as well as the Conex Bänninger® >B< MaxiPro® System for the refrigeration and air conditioning sector.

Automatic pressure setting, app connectivity and CAS battery technology ensure safety and easy documentation.

Summary of contents

Page	Applications		Chapter
12	Cutting		1
20	Universal tools		2
24	Pressing	A 8	3
36	Expanding		4
44	Bending		5
58	Flare connections		6
61	Soldered joints		7
77	Complete solutions	A Secretaria de la constantina della constantina	8
80	Measuring and testing		9
88	Evacuation, recovery and weighing		10
99	Relevant informations		11

TUBE CUTTER 35

Pipe cutter for the precise cutting of pipes Ø 6–35 mm (1/4–1.3/8")

For the precise cutting of copper, brass, aluminium, thinwalled steel pipes.

Application Benefits

- Optimal for confined spaces
- Quick adjustment of the working area
- Spare cutter wheel in handle
- · Cuts near to flares are possible
- Retractable internal pipe deburrer
- Rugged and robust

Metal casing with DURAMANT coating: durable and extremely robust!







Technical Data

Working area	Ø 6-35 mm (1/4-1.3/8")
Material	DURAMAG magnesium
Cutting depth	3 mm

The 100% magnesium body is up to 30% lighter than the previous model!








For MLP pipes



For stainless steel pipes



TUBE CUTTER 35, DURAMAG







For cutting copper, brass, aluminium, thin-walled steel pipes.

Application Benefits

- Optimal for confined spaces
- Quick adjustment of the working area
- Spare cutter wheel in handle
- Cuts near to flares are possible
- · Retractable internal pipe deburrer
- Rugged and robust



Model	Weight	PU	No.
TUBE CUTTER 35, 6–35 mm (1/4–1.3/8″), DURAMAG	0.255 kg	4	70027
TUBE CUTTER 35 DURAMAG display, 6 pcs.	1.700 kg	1	070027DB

Handtool set "Prepare to Press" Set for preparing pressings



pipes with \emptyset 6–35 mm (1/4–1.3/8") for subsequent pressings.



Scope of delivery: TUBE CUTTER 35, Ø 6–35 mm (No. 70027), internal and external deburrer Ø 6–35 mm (No. 1500000237), permanent-marker "Prepare to Press" (No. 1500002640), ROBOX B2350 (No. 1500002641)

Model	Weight	PU	No.
Handtool set "Prepare to Press", 6–35 mm (1/4–1.3/8")	0.460 kg	1	1000002002

TUBE CUTTER 35 INOX, DURAMAG

Pipe cutter for the precise cutting of pipes Ø 6-35 mm (1/4-1.3/8")





For cutting stainless steel pipes.

Application Benefits

- · Hardened, special cutter wheel made of high-alloyed steel
- External burr-free cutting
- Stainless steel guide rolls, cuts near flares possible
- Optimum use in tight places
- · Quick adjustment of the working area
- Retractable pipe internal deburrer
- · Rugged and robust



Model	Weight	PU	No.
TUBE CUTTER 35 INOX, 6–35 mm (1/4–1.3/8″), DURAMAG	0.255 kg	4	70055

TUBE CUTTER 35 INOX with cutting wheels





TUBE CUTTER 35 INOX for cutting stainless steel pipes.

INOX



Scope of delivery: TUBE CUTTER 35 INOX, Ø 6-35 mm, DURAMA (No. 70055), cutter wheel for TUBE CUTTER 35, TUBE CUTTER 30 Pro and TUBE CUTTER 42 XL (No. 070056D), ROBOX B2350 (No. 1500002641)

Model	Weight	PU	No.
TUBE CUTTER 35 INOX with cutting wheels and ROBOX	0.500 kg	1	1000002222

TUBE CUTTER 42 PRO

Pipe cutter for the precise cutting of pipes Ø 6-42 mm (1/4-1.5/8")





For cutting copper, brass, aluminium, thin-walled steel pipes.

Application Benefits

- Optimal for confined spaces
- Quick adjustment of the working area
- Spare cutter wheel in handle
- · Cuts near to flares are possible
- Retractable internal pipe deburrer
- Rugged and robust



Model	Weight	PU	No.
TUBE CUTTER 42 PRO, 6–42 mm (1/4–1.5/8")	0.545 kg	4	70029

TUBE CUTTER 42 PRO INOX

Pipe cutter for the precise cutting of stainless steel pipes Ø 6–42 mm (1/4–1.5/8")

For cutting stainless steel pipes.

Application Benefits

- Hardened, special cutter wheel made of high-alloyed steel
- External burr-free cutting
- Stainless steel guide rolls, cuts near flares possible
- · Optimum use in tight places
- · Quick adjustment of the working area
- Retractable pipe internal deburrer
- · Rugged and robust



Model	Weight	PU	No.
TUBE CUTTER 42 PRO INOX, 6–42 mm (1/4–1.5/8″)	0.545 kg	1	70070

TUBE CUTTER 42 XL

Pipe cutter for the precise cutting of pipes \emptyset 6-42 mm (1/4-1.5/8")

For cutting copper, brass, aluminium, stainless steel and thin-walled steel pipes with a wall thickness of up to 1.2 mm.

Application Benefits

- The wide pipe support means that the pipe can be fixed well in place and cutting to length is quick and easy
- New cutter wheel: 20 × more cuts¹
- \bullet Suitable for thin-walled pipes starting at a wall thickness of 0.5 mm
- Quick adjustment of the pipe diameter by easy turning of the adjustment knob
- · Spare cutter wheel in handle compartment
- Retractable internal pipe deburrer

Wide bearing surface For easy and effortless cutting Gap for cuts near to flare Material saving

Model	Weight	PU	No.
TUBE CUTTER 42 XL, 6-42 mm (1/4-1.5/8″)	0.500 kg	1	1000001748
Spare cutter wheel, 5 pcs.	0.020 kg	1	070056D



ROTRAC 28





For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Constant working radius
- Cast aluminium design
- Protection of the cutter wheel with the rolling stop
- Retractable internal deburrer and spare cutter wheel in handle
- Protected screw spindle-protection against dirt and jamming



Model	Weight	PU	No.
ROTRAC 28, 3–28 mm (1/8–1.1/8")	0.220 kg	1	70010
ROTRAC 28 PLUS Chrome, Limited Edition	0.220 kg	1	1000000046
Spare axle	0.005 kg	1	70080
Spare cutter wheel INOX	0.002 kg	1	070007X
Spare cutter wheel Cu, Al, Br, 3 pcs.	0.020 kg	1	070007D

MINICUT I PRO/II PRO





For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Compact design with small working radius 38 mm (1.1/2") I PRO and 42 mm (1.5/8") II PRO allows use in hard-to-reach places
- Effortless pressure control with the large knurled knob and compact design
- Two guide rollers with recess for cuts near flares
- Monoblock design allows precision

Ideal for maintenance and repair work!







Model	Weight	PU	No.
MINICUT I PRO, 3–16 mm (1/8–5/8")	0.115 kg	4	70401
MINICUT I PRO C, 3–16 mm (1/8–5/8")	0.120 kg	4	070401C
MINICUT II PRO, 6–22 mm (1/4–7/8")	0.125 kg	4	70402
Spare cutter wheel Cu, Br, Al, Fe, 5 pcs.	0.020 kg	1	070017D

ROTRAC 42

High-precision pipe cutter Ø 6-42 mm (1/4-1.5/8")



For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Constant working radius
- Cast aluminium design
- Protection of the cutter wheel with the rolling stop
- Retractable internal deburrer and spare cutter wheel in handle
- Protected screw spindle-protection against dirt and jamming



Model	Weight	PU	No.
ROTRAC 42, 6-42 mm (1/4-1.5/8")	0.255 kg	1	70011
Spare axle	0.005 kg	1	70080
Spare cutter wheel INOX	0.002 kg	1	070007X
Spare cutter wheel Cu, Al, Br, 3 pcs.	0.020 kg	1	070007D

MINICUT 2000

Copper pipe cutter Ø 3–22 mm (1/8–7/8")





For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Compact design with small working radius 45 mm (1.3/4") allows use in hard-to- reach places
- Effortless pressure control with the large knurled knob and compact design
- Two guide rollers with recess for cuts near flares
- Ergonomic design of body and knob with seating surface for the hand during turning



Model	Weight	PU	No.
MINICUT 2000, 3–22 mm (1/8–7/8")	0.140 kg	4	70105
Spare axle	0.005 kg	1	70041
Spare cutter wheel Cu, Br, Al, Fe, 5 pcs.	0.020 kg	1	070017D

MINI MAX

Copper pipe cutter Ø 3-28 mm (1/8-1.1/8")





For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Compact design with very small working radius 58 mm (2.1/4") allows use in hard-to-reach places
- Effortless pressure control with the large knurled knob and compact design
- Two guide rollers with recess for cuts near flares
- Ergonomic design of body and knob with seating surface for the hand during turning



Model	Weight	PU	No.
MINI MAX, 3-28 mm (1/8-1.1/8")	0.270 kg	4	70015
Spare cutter wheel Cu, Br, Al, Fe, 5 pcs.	0.020 kg	1	070017D
Spare axle	0.005 kg	1	70041

TUBE CUTTER 30 PRO

Copper pipe cutter Ø 3-30 mm (1/8-1.1/4")

For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Two guide rollers with recess for cuts near flares
- Retractable internal deburrer and spare cutter wheel in handle



Model	Weight	PU	No.
TUBE CUTTER 30 PRO, 3–30 mm (1/8–1.1/4")	0.305 kg	4	71019
Spare cutter wheel Cu, Br, Al, Fe, 5 pcs.	0.020 kg	1	070017D
Spare axle	0.005 kg	1	70041

TUBE CUTTER 50

Copper pipe cutter Ø 12-50 mm (1/2-2")

For cutting copper, brass, aluminium and thin-walled steel pipes.

Application Benefits

- Two guide rollers with recess for cuts near flares
- Retractable internal deburrer and spare cutter wheel in handle

Technical Data

Working area	Ø 12–50 mm (1/2–2")
Cutting depth	1.2 mm
Suitable for	Cu, brass, Al, thin-walled steel pipes



Model	Weight	PU	No.
TUBE CUTTER 50, 12–50 mm (1/2–2″)	0.520 kg	1	70065
Spare axle	0.010 kg	1	70006

Automatic pipe cutter

Telescopic pipe cutter Ø 6-127 mm (1/4-5")

For cutting copper, brass, aluminium and thin-walled steel pipes as well as sound-insulated pipes.

Application Benefits

- Retractable internal deburrer and spare cutter wheel in handle
- Monoblock design
- Quick adjustment with the ratchet telescopic guide with automatic spring-driven release
- Self-clamping prevents release due to quick adjustment during the cutting process



Weight	PU	No.
0.755 kg	1	70030
1.875 kg	1	70142
0.005 kg	10	21652
0.005 kg	1	750004100
	0.755 kg 1.875 kg 0.005 kg	0.755 kg 1 1.875 kg 1 0.005 kg 10

Model	Weight	PU	No.
Spare axle Size 1	0.020 kg	1	70042
Spare cutter wheel for Automatic pipe cutter Size 2, 2 pcs.	0.020 kg	1	070057D
Spare cutter wheel Cu, Br, Al, Fe, 5 pcs.	0.020 kg	1	070017D

ROSLICE

Copper pipe cutter Ø 12-22 mm (1/2-7/8")

For cutting copper pipes.

Application Benefits

- Quick cutting of copper pipes with less turns
- No deformation of the pipe: self-clamping and self-alignment
- Less space required, ideal for hard-to-reach places
- · Reliable hold with the non-slip surface





Model	Weight	PU	No.
ROSLICE, 12 mm	0.240 kg	1	88812
ROSLICE, 15 mm	0.230 kg	1	88815
ROSLICE, 18 mm	0.260 kg	1	88818
ROSLICE, 22 mm	0.250 kg	1	88822
ROSLICE, 3/4"	0.240 kg	1	88832
Spare cutter wheel, 12 mm (1/2"), 5 pcs.	0.036 kg	1	088840D
Spare cutter wheel, 15 mm and 22 mm (5/8 and 7/8"), 5 pcs.	0.035 kg	1	088841D
Spare cutter wheel, 18 mm, (1/2–3/4″), 5 pcs.	0.037 kg	1	088842D





Pipe cutter for plastic / Plastic pipe shears

ROCUT Plastic Pro

One tool, two pipe diameters

The pipe cutter ROCUT Plastic Pro cuts PE, PP and PVC pipes. It cuts the pipe right angled, quickly and with only a few turns.

Application Benefits

- One tool can cut two pipe diameters and three different sizes are available
- Cut pipes with a wall thickness of up to 3.5 mm
- Requires only little working area and allows work in confined

Two diameters One tool for two diameters


Cassette for spare blade

Practical storage for replacement cutting sheets

0.540 kg

Technical Data

Working area	Ø 15-50 mm
Cutting depth	2–3.5 mm
Suitable for	PP, PE, PVC



Model	Weight	PU	No.
ROCUT Plastic Pro, 15–22 mm	0.340 kg	1	1000003051
ROCUT Plastic Pro, 32–40 mm	0.540 kg	1	1000003052

ROCUT 26 MSR

ROCUT Plastic Pro, 40-50 mm

Plastic pipe shears

The ROCUT 26 MSR is suitable for cutting multilayer composite and plastic pipes with a diameter of 0-26 mm (0-1").

Application Benefits

- Especially suitable for multilayer composite pipes with an aluminum core, it can also cut all standard plastic pipes up to a diameter of 26 mm.
- · The curved steel blade enables an exact, right-angled cut and minimizes deformation of the pipe
- · Wide pipe support: the pipe cannot tilt and can be cut precisely and straight
- · Rubberized handle: for a secure grip without slipping during
- Transport lock: the pliers legs can be locked in the transport position after use

Technical Data

1

Working area	Ø 0-26 mm (0-1")
Suitable for	PP, PE, PEX, PB, PVDF, MLP pipes

1000003106

The blade can be changed in just a few simple steps



broad seating for pipe

Fixes the pipe so that a straight cut can be made

Model	Weight	PU	No.
ROCUT 26 MSR, 0-26mm (0-1")	0.335 kg	1	1000004324

Pipe cutters, cutting wheels and spare parts

Only original ROTHENBERGER cutting wheels made of highalloyed hardened steel guarantee an exact, right-angled cut.





















Pipe cutter type	Model for pipe-Ø	No.	Cutting wheel No.	Sizes d/L/D mm	Cutting depth mm	Spare axle No.	Ø mm Length mm Thread	Spare roller No.	Deburring blade No.	Application area
MINICUT I PRO	3–16 mm	70401	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	70023	_	Copper pipe (Cu),
MINICUT II PRO	6-22 mm	70402	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	70023	_	brass pipe (Ms), aluminium pipe (Al), thin-walled steel pipe (Fe), PVC hard plastic pipe,
MINICUT 2000	3-22 mm	70105	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	_	_	
MINIMAX	3-28 mm	70015	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	_	_	plastic-coated pipe
TUBE CUTTER 30 PRO	3-30 mm	71019	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	70067	_	
TUBE CUTTER 35 + 35 C	6-35 mm	070027(C)	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	70067	21652	Copper pipe (Cu), brass pipe (Ms),
TUBE CUTTER 42 PRO	6-42 mm	70029	070017D	4.8/5.9/18.5	3.0	70041	4.7/14/M3	70067	21652	aluminium pipe (Al), thin-walled steel pipe (Fe),
TUBE CUTTER 35 MSR	6-35 mm	70108	070188D	4.8/5.9/19.3	4.0	70041	4.7/14/M3	70067	21652	PVC hard plastic pipe, plastic-coated pipe
TUBE CUTTER 42 PRO MSR	6-42 mm	70109	070188D	4.8/5.9/19.3	4.0	70041	4.7/14/M3	70067	21652	
TUBE CUTTER 50	12-50 mm	70065	070017D	4.8/5.9/18.5	3.0	70006	4.7/16/M4	_	_	Multilayered composite pipe
AUTOMATIC pipe cutter Size 1	6-67 mm	70030	070017D	4.8/5.9/18.5	3.0	70042	4.7/16/M4	_	21652	Cu, Ms, Al, Fe thin-walled
AUTOMATIC pipe cutter Size 1	6-67 mm	70031	070028D	4.8/5.9/23.6	7.0	70042	4.7/16/M4	_	21652	PE, PP, VPE, PB and PVDF pipes
AUTOMATIC pipe cutter Size 2	50-127 mm	70142	070057D	8.0/14.0/29.0	7.0	751004200	7.9 / 23.5 / 1/4"	_	21652	thin-walled Cu, Ms, Al, Fe
AUTOMATIC pipe cutter Size 2	50-127 mm	70032	055054D	8.0/13.0/40.0	13.0	751004200	7.9/23.5/1/4″	_	21652	PE, PP, VPE, PB and PVDF pipes
AUTOMATIC pipe cutter Size 2	50-127 mm	70032	055053D	8.0/13.0/30.5	8.0	751004200	7.9 / 23.5 / 1/4"	_	21652	thin-walled PP pipes
AUTOMATIC pipe cutter Size 2	50-127 mm	70032	055074D	8.0/11.0/45.0	16.0	751004200	7.9/23.5/1/4"	_	21652	PE, PP, VPE, PB and PVDF pipes
AUTOMATIC pipe cutter Size 3	100-168 mm	70033	055074D	8.0/11.0/45.0	16.0	751004200	7.9 / 23.5 / 1/4"	_	21652	PE, PP, VPE, PB and PVDF pipes
AUTOMATIC pipe cutter Size 3	100-168 mm	70033	055053D	8.0/11.0/30.5	8.6	751004200	7.9/23.5/1/4"	_	21652	thin-walled PP pipes
TUBE CUTTER 28	3-28 mm	70010	070007D	4.8/3.0/16.0	2.5	70080 + 70081	4.7/9/SR	80679	_	Cu, Ms, Al, Fe thin-walled
TUBE CUTTER 42	3-42 mm	70011	070007D	4.8/3.0/16.0	2.5	70080 + 70081	4.7/9/SR	80679	_	Cu, Ms, Al, Fe thin-walled
TUBE CUTTER 42 XL	3-42 mm	1000001748	070056D	4.8/9.8/18.5	5.5	70041	4.7/14/M3	1300003578	21652	Br, SS, Al, Fe thin-walled
TUBE CUTTER 42 PRO PVC	6-42 mm	70072	070028D	4.8/5.9/23.6	7.0	70041	4.7/14/M3	70067	_	PE, PP, VPE, PB and PVDF pipes
Steel pipe cutter SUPER	3/8-1.1/4"	70040	070046D	7.5/14.0/25.7	5.5	701011500	7.4/30/—	70047	_	Steel pipe (Fe)
Steel pipe cutter SUPER	3/8-2"	70045	070051D	9.0/17.0/31.5	6.0	70053	8.9/35/—	70052	_	Steel pipe (Fe)
Steel pipe cutter ENORM	2-4"	70060	070061D	9.7/20.0/41.0	8.0	70064	9.4/52/—	70063	_	Steel pipe (Fe)
TUBE CUTTER 30 PRO INOX	3-30 mm	71085	070056D	4.8/5.9/18.5	5.5	70041	4.7/14/M3	70068	_	Stainless steel pipe
TUBE CUTTER INOX	10-54 mm	70340	70341	5.0/21.0/30.0	3.5	753000700	4.7/14/M3	70068	21652	Stainless steel pipe
TUBE CUTTER 35 INOX	6-35 mm	70055	070056D	4.8/5.9/18.5	4.0	70041	4.7/14/M3	70068	21652	Stainless steel pipe
TUBE CUTTER 42 PRO INOX	6-42 mm	70070	070056D	4.8/5.9/18.5	4.0	70041	4.7/14/M3	70068	21652	Stainless steel pipe
TUBE CUTTER CSST	8-42 mm	1000001747	1000002077	4.8/9.5/24	0.5	1300003575 1300003574	4.7/39.3/M3	1300003573	_	INOX corrugated pipes
SUPER INOX	3/8-1.1/4"	70086	070088D	4.8/5.9/19.3	4.0	701011500	7.4/30/—	70047	_	Stainless steel pipe
SUPER INOX	3/8-2"	70087	070089D	9.0/19.0/31.5	7.0	70053	7.4/35/—	70052	_	Stainless steel pipe
Chain pipe cutter	100 mm	70285	-	4.0/3.8/17.8	3.0	-	-	70286	70286	Cu, Ms, Al, Fe thin-walled

Electrical power combination pliers



Application Benefits

- Equipped with an integrated ring spanner for M8 and M10 nuts/screws
- Inductive hardened blade to ensure a higher service life
- Asymmetric grip function can be used to grab round or flat materials



Model	Weight	PU	No.
Electrical power combination pliers	0.250 kg	1	1500003163

Electrical multi insulation stripper



Application Benefits

- Improvement of the common insulation stripper and does not need an adjusting screw
- Ideally suitable to strip Ø 5–16 mm cable coatings
- The stripping function enables cable stripping of singleor multicore cables up to Ø 5.0 mm



Model	Weight	PU	No.
Electrical multi insulation stripper	0.230 kg	1	1500003167

Electrical long nose pliers

☆ 1000 V IEC 60900

Application Benefits

- Inductive hardened blade to ensure a higher service life
- Integrated M10 ring spanner to tighten/loosen nuts and screws
- Grab wires precisely, the serrated gripping surface ensures a tight, firm grip



Model	Weight	PU	No.
Electrical long nose pliers	0.200 kg	1	1500003168

Electrical edge cutter

☆ 1000 V

Application Benefits

- Inductive hardened blade to ensure a higher service life
- Wave profile of the blade provides an anti-slip function:
 The wire does not slip out while being cut
- Comfortable handling thanks to ergonomic 3 K handles



Model	Weight	PU	No.
Electrical power edge cutter	0.210 kg	1	1500003164
Electrical power edge cutter	0.300 kg	1	1500003166

Voltage Detector E-Detector 90-1000 V

Application Benefits

- The non-contact voltage tester detects AC voltage in a range of 90–1,000 V
- When voltage is detected, a red LED lights up. In addition, a flashlight is attached to the voltage tester.



Model	Weight	PU	No.
Voltage Detector E-Detector 90–1000 V	0.030 kg	1	1500003374

Electrical installation pliers



Application Benefits

- Integrated stripping function, ring spanner and gripping zone for flat and round material
- Multi purpose tool makes lots of other tools obsolete
- · Angled design enables low-fatigue working



Chisel screwdriver set EUROLINE IMPAKT

Screwdriver with continuous, strengthened blade

Application Benefits

2 tools in 1!

 One-piece, strengthened blade with metal cap allows directed hammer blows, for example loosening stuck screws


Color coding for

Quick differentiation

different tips

Set (No. 73575) includes:





2 component handle made of high-quality, plastic, grip-friendly AS knob form

High force transmission





Surface treated precision tip

Guarantees perfect seat on screw head

Blade made of high-quality, tempered chrome vanadium steel

High torque proof

5 pieces set (No. 73575) includes: slot screwdriver 5.5×100 mm(No. 73565), 6.5×125 mm (No. 73566), 8×150 (No. 73567), Phillips PH 1×80 mm 1 (No. 73536), PH 2×100 mm (No. 73537)

Model	Weight	PU	No.
Chisel screwdriver set EUROLINE IMPAKT, 5 pcs.	0.750 kg	1	73575

Constant strenghtened blade with metal cap





VDE screwdriver set

Blades made of chrome vanadium molybdenum steel, thoroughly hardened, extrusion-coated blade insulation tightly joined with handle, 1,000 Volt



Model	Weight	PU	No.
VDE screwdriver set 7 pieces	0.680 kg	1	323126









ROGRIP M

Quick adjustable water pump pliers

Holds and grips a wide variety of pipe types up to Ø2".

Application Benefits

- Durable: Due to the double hardening, the teeth are particulary wear-resistant
- Non-slip: the soft-touch handle prevents the pliers from slipping off the pipe
- Firm grip: the shape of the teeth (self locking) and the 3-point grip on the pipe prevent slipping on the pipe
- Large gripping capacity: 30 % more gripping capacity 1): 10" pliers up to 2" pipe diameter

Technical Data

Working area diameter	2"
Working area diameter	0-60 mm
Material	Chrome vanadium steel

Model	Weight	PU	No.
ROGRIP M, 7", 1K	0.235 kg	6	1000002697
ROGRIP M, 7", 2K	0.250 kg	6	1000002698
ROGRIP M, 10", 1K	0.470 kg	6	1000002699
ROGRIP M, 10", 2K	0.495 kg	6	1000002700

Double hardened jaws, extremely durable

Firm grip on any surface even under the strongest conditions

ROTHENBERGER Curve-Shape-Design

Particularly ergonomic for large pipe diameters. Reduces the risk of pinching fingers

Large grip width

Reliable grip and hold up to 2" pipe diameter

New handle design

Good grip with two handle versions

Wide handles

More comfort and better power transmission

Thanks to the ROTHENBERGER curve-shape design the 7" ROGRIP has the same gripping capacity of a normal 10" WAPU!

ROGRIP F

Quick adjustable water pump pliers

Holds and grips a wide variety of pipe types up to Ø2".

Application Benefits

- Durable: Due to the double-hardened teeth, the teeth only wear slowly
- Firm grip: the shape of the teeth (self locking) and the 3-point grip on the pipe prevent slipping on the pipe
- Large gripping capacity: 30 % more gripping capacity: 10" pliers up to 2" pipe diameter
- Safety lock system: prevents unintentional opening and enables a 50% quicker adjustment

Curve-Shape-Design: especially ergonomic



3-point grip over the middle for reliable clam-ping. Perfect grip on pipes up to $\emptyset \, 2''$



Model	Weight	PU	No.
ROGRIP F, 10", 1K	0.405 kg	6	1000002704
ROGRIP F, 10", 2K	0.425 kg	6	1000002705
ROGRIP F, 7", 1K	0.215 kg	6	1000002701
ROGRIP F, 7", 2K	0.225 kg	6	1000002702

Double hardened jaws, extremely durable

Firm grip on any surface even under the strongest conditions

ROTHENBERGER Curve-Shape-Design

Particularly ergonomic for large pipe diameters. Reduces the risk of pinching fingers

Large grip width

Reliable grip and hold up to 2" pipe diameter

New handle design

Good grip with two handle versions

Wide handles

More comfort and better power transmission

Thanks to the ROTHENBERGER curve-shape design the 7" ROGRIP has the same gripping capacity of a normal 10" WAPU!



Safety blocking system

Prevents

unintentional

opening and enables up to 50 %

faster adjustment

ROFAST pliers wrench

For gripping, holding, pressing and bending surfacesensitive, chrome-plated screw fittings





Plastic protective jaws for optimum protection of the workpiece

Application Benefits

- Gentle on surfaces thanks to smooth, parallel jaws
- Versatile use: pliers and spanner in one tool
- Convenient handling thanks to stepless adjustment on the push button
- Includes 3 pairs of plastic protective jaws for optimum protection of the workpiece

Pliers wrench with onehand quick adjustment



 $20\,\%$ larger gripping capacity due to Curve Shape Design




Knob for one-hand operation for quick size adjustment



Scale for size presetting – Time saving and precise wrench size



Model	Weight	PU	No.
ROFAST pliers wrench 7″ 1K, with soft jaws, 3 pairs	0.325 kg	1	1000004325
ROFAST pliers wrench 7″ 2K, with soft jaws, 3 pairs	0.325 kg	1	1000004710
ROFAST pliers wrench 10″ 1K, with soft jaws, 3 pairs	0.575 kg	1	1000004802
ROFAST pliers wrench 10″ 2K, with soft jaws, 3 pairs	0.575 kg	1	1000004810
Soft jaws for ROFAST pliers wrench 7″, 3 pairs	0.325 kg	1	1000004811
Soft jaws for ROFAST pliers wrench 10″, 3 pairs	0.575 kg	1	1000004812





ROMAX NANO

Battery-operated electromechanical press machine for 1.4 up to 1.3/8" Conex Bänninger® >B< MaxiPro® fittings. Small, intelligent and ultra-light

The ROMAX NANO is the first hybrid press machine to combine two pressing force categories (iJAW and 32 kN) in one machine. It is suitable for the NANO iJAWS press jaw system as well as for standard jaws and presses 1.4 up to 1.3/8" Conex Bänninger® >B< MaxiPro® fittings. A sophisticated smart connectivity concept supports the users in their work.

Compatible press tools

The ROMAX NANO and the Standard press jaws are suitable for the innovative >B< MaxiPro® ACR fitting system from Conex Bänninger®. Press jaws see page 32.











Technical Data

Dimension	323 × 83 × 108 mm
Piston force / hub	hybrid/40 mm
Nominal size	Ø 1/4–1.3/8″ (Larger nominal sizes on request)
Service intervall	No limitation of pressings / 2 years
Press jaw fixture	180° rotation
Power supply	Battery
Operation temperature	-10 °C up to 60 °C



2 in 1 jaw mount

Suitable for NANO and standard iaws in one mount

Hybrid pressing machine

Combines 2 press force levels (iJAW and 32 kN) in one device

Constant Force Technology (CFT)

Keeps the pressing force constant at the required level

eRotationDrive

Enables the use of variable pressing forces and reduces the overall weight of the machine (approx. 2.3 kg)

Connected with the ROTHENBERGER App

The ROTHENBERGER app can be used to connect tool and smartphone. This gives the user real-time access to relevant machine and press data.

The app also provides press logs with intelligent logic quickly and easily on site. The maintenance status of the mould can also be read out.

Available for iOS and Android!



Fig. ROMAX NANO Set CAS (No. 1000004824)





Model	Weight	PU	No.
ROMAX NANO set CAS	3.300 kg	1	1000004824

Battery and charger are not included in the ROMAX NANO set!

Batteries and charger







No. 1000001652



No. 1000001653



No. 1000002548



No. 1000002549

Model	Weight	PU	No.
RO BP18/2, 2.0 Ah 18 V	0.420 kg	1	1000001652
RO BP18/4, 4.0 Ah 18 V	0.575 kg	1	1000001653
RO BP18/4, 4.0 Ah 18 V, Li-HD	0.515 kg	1	1000002548
RO BP18/8, 8.0 Ah 18 V, Li-HD	0.915 kg	1	1000002549
RO BC14/36 Ladegerät, 230 V	0.580 kg	1	1000001654

ROMAX COMPACT III

Electrohydraulic press machine for battery operated pressing of Conex Bänninger® >B< MaxiPro® refrigeration fittings up to 1.1/8" with 19 kN

The ROMAX COMPACT III is 3 seconds fast, 2.5 kg light and 19 kN strong. Through the perfect handling the machine is particularly suitable for ACR installations, high volume pressings or service installations.

Compatible press tools

The ROMAX COMPACT III and the Compact press jaws are suitable for the innovative >B< MaxiPro® ACR fitting system from Conex Bänninger®. Press jaws see page 32.







Technical Data

Dimension	336×143×76 mm (with 2.0 Ah battery)
Piston force / hub	19 kN / 30 mm
Nominal size	1/4-1.1/8″
Service intervall	40,000 pressings / 2 years
Press jaw fixture	270° rotation
Power supply	Battery
Operation temperature	-10°C up to 60°C
Pressings	approx. 150 press cycles with 2.0 Ah battery

Available in the manufacturer-independent battery systems AMPShare – Powered by Bosch or CAS – CORDLESS ALLIANCE SYSTEM

Push-2-Lock-Knob

New jaw locking system (springloaded knob) allows convenient attaching/detaching of press jaws

Balanced Design

Optimized in weight and size for better machine handling in daily use

Bluetooth® inside

Connects the machine with ROTHENBERGER App

Multiple battery systems

Suitable for CAS and AMPShare battery systems (2 different machine versions)



Jaw matching indicatior reduces misuse risk of attaching incompatible jaws

Black Colored Parts

New coloration of jaw fixture and bracket give the machine a High-End-Look

Flame-free: Flame-free installation avoids the need for a hot work permit and the risk of fire on site.



Model	Press jaws Ø	Weight	PU	AMPShare-No.	CAS-No.
ROMAX COMPACT III bare tool		4.530 kg	1	1000004266	1000004265
ROMAX COMPACT III basic set 1, 1 × 2 Ah		5.480 kg	1	1000004267	1000004261
ROMAX COMPACT III basic set 1, 1 × 2 Ah, UK		4.900 kg	1	1000004271	1000004269
ROMAX COMPACT III basic set 1, 2 × 2 Ah		5.965 kg	1	1000004272	1000004263
ROMAX COMPACT III set >B< MaxiPro, 2 Ah	1/4-1.1/8″	17.500 kg	1	1000004287	1000004286
ROMAX COMPACT III set >B< MaxiPro, 2 Ah, UK	1/4-1.1/8″	17.500 kg	1	1000004289	1000004288

ROMAX 4000

Electrohydraulic press machine for battery operated pressing of Conex Bänninger® >B< MaxiPro® refrigeration fittings up to 1.3/8" with 32–34kN

The ROMAX 4000 operates in just 5 seconds, weighs only 3.6 kg and uses a force of 32–34 kN. It can press from 1.4" up to 1.3/8" Conex Bänninger® >B< MaxiPro® fittings and is therefore the perfect all-rounder amongst the ROTHENBERGER press machines.

Compatible press tools

battery systems

(2 different machine versions)

The ROMAX 4000 and the Standard press jaws are suitable for the innovative >B< MaxiPro® ACR fitting system from Conex Bänninger®. Press jaws see page 32.







Technical Data

467 × 125 × 80 mm (with 4.0 Ah battery) 445 × 125 × 75 mm (with 2.0 Ah battery)
32-34 kN / 40 mm
1/4–1.3/8″ (Larger nominal sizes on request)
40,000 pressings / 2 years
270° rotation
Battery
-10 °C up to 60 °C



Model	Weight	PU	AMPShare-No.	CAS-No.
ROMAX 4000 bare tool	5.900 kg	1	1000004166	1000002683
ROMAX 4000 basic set 1 incl. 1 × 4.0 Ah battery	7.000 kg	1	1000004165	1000001840
ROMAX 4000 basic set 2 incl. 1 × 2.0 Ah battery and 1 × 4.0 Ah battery	8.000 kg	1	1000004167	1000001923

Constant Force Technology


The CFT guarantees a constant axial pressing force over the entire service interval. A very important requirement for the production of sealed press connections.

CFT guarantees:

- ROMAX NANO: several pressing force levels (iJAW and 32 kN) / no limitation of pressing cycles / 2 years
- ROMAX Compact III: 19 kN / 40,000 press cycles / 2 years
- ROMAX Compact TT: 19 kN / 40,000 press cycles / 2 years
- ROMAX 4000: 32 kN / 40,000 press cycles / 2 years
- ROMAX 3000 AC: 32 kN / 20,000 press cycles / 2 years
- ROMAX AC ECO: 32 kN / 10,000 press cycles / 2 years

Constant force due to CFT

Measurement under load—UPONOR NW 75



No system commitment

Users are free to decide which fitting systems they want to press. They are also free to choose the manufacturer of the press machines and press tools. There is no legal provision, DIN standard or other provision—for example, a regulation established by means of a DVGW worksheet—which obligates the tradesmen to exclusively use the press tools or press jaws of just one fitting or piping system manufacturer.

The only decisive factor is whether the fitting system and pressing tool are suitable for one another – only in this case is the tightness guaranteed. The Pressnavigator app provides guidance by enabling users to find the suitable press tool for the fitting system, or the suitable fitting system for the press tool.



Controlled press cycle

After reaching a predetermined pressing force the press cycle switches off automatically. The piston retracts after the necessary pressing force has been reached. This guarantees uniform and reliable pressings as leading system manufacturers require.

CAS—Cordless Alliance System

- cross-manufacturer battery alliance
- 100 % compatibility of batteries and chargers with tools and machines of all alliance partners
- 18-volt battery technology from Metabo
- Strong brands for the professional user and high specialization

Electronic control

The electronics of the ROMAX NANO, ROMAX Compact III, ROMAX Compact TT, ROMAX 4000, ROMAX 3000 AC provide for a safe pressing cycle:

- Control of the battery charge status
- Safety start-inhibitor when the battery is too low
- LED display of the service interval and any error messages

AMPShare—Powered by Bosch

- cross-manufacturer battery alliance
- 100 % compatibility of batteries and chargers with tools and machines of all alliance partners
- 18-volt battery technology from Bosch
- High availability and global distribution thanks to 100% compatibility with all Bosch Professional batteries since 2008—more than 80 million rechargeable batteries on the market



DURA LAZR TEC

The unique laser-hardening process

Long-lasting. Safe. Precise. Our DURA LAZR TEC press jaws set is a new industry standard. The unique ROTHENBERGER laser-hardening process, which is implemented in our own production, provides maximum stability and wear resistance. And, therefore, more safety and a longer service life!



Partial laser-hardening for highly stressed surfaces

Ideal accuracy of contour for highest precission during the complete live time

• 40 % increase in hardness¹

Highest degree of hardness

 ROTHENBERGER press jaws are performing with the highest degree of hardness at high stressed areas

 Even in the case of high burr formation during compression, the wear is reduced to a minimum



+100%
PRESS CYCLES
WITH LASER
HARDENING

Double lifetime

Partial Laser Hardening ensures an appropriate Optimization in Usage. Heavily Loaded Areas of the Press Jaw will be specifically hardened. Non-loaded Areas remain ductile for a proper Force Load Compensation.

Adjustment of the plate

Durability increased by approx. 45 %¹

Depth distribution of hardness was tested by the independent test laboratory of the State Materials Testing Institute Darmstadt (MPA).





Press jaws compact >B< MaxiPro

For ROMAX COMPACT III / ROMAX COMPACT TT

Suitable for use in pipe systems for refrigeration systems and heat pumps from -40 $^{\circ}$ C to +140 $^{\circ}$ C at a maximum operating pressure of 48 bar.

Application Benefits

- Flame free connection: No more working with open flame necessary
- Secure sealing: Reliable and durable connection through 3-point compression
- Fast, simple and cost-effective installation





Model	Press jaws Ø	Weight	PU	No.
Press jaw compact >B< MaxiPro	1/4″	1.265 kg	1	1000001749
Press jaw compact >B< MaxiPro	3/8″	1.250 kg	1	1000001750
Press jaw compact >B< MaxiPro	1/2″	1.180 kg	1	1000001751
Press jaw compact >B< MaxiPro	5/8″	1.180 kg	1	1000001752
Press jaw compact >B< MaxiPro	3/4″	1.190 kg	1	1000001753
Press jaw compact >B< MaxiPro	7/8″	1.290 kg	1	1000001754
Press jaw compact >B< MaxiPro	1″	1.930 kg	1	1000001755
Press jaw compact >B< MaxiPro	1.1/8″	1.275 kg	1	1000001756
Press jaw compact set >B< MaxiPro	1/4-5/8″	6.000 kg	1	1000003580
Press jaw compact set >B< MaxiPro	1/4-1.1/8″	14.000 kg	1	1000001989

Press jaws standard >B< MaxiPro

For ROMAX NANO, ROMAX 4000, ROMAX 3000 AC and ROMAX AC ECO

Suitable for use in pipe systems for refrigeration systems and heat pumps from -40 °C to +140 °C at a maximum operating pressure of 48 bar.

Application Benefits

- Flame free connection: No more working with open flame necessary
- Secure sealing: Reliable and durable connection through 3-point compression
- Fast, simple and cost-effective installation





Model	Press jaws Ø	Weight	PU	No.
Press jaw standard >B< MaxiPro	1/4″	2.050 kg	1	1000001889
Press jaw standard >B< MaxiPro	3/8″	2.040 kg	1	1000001890
Press jaw standard >B< MaxiPro	1/2″	1.940 kg	1	1000001891
Press jaw standard >B< MaxiPro	5/8″	1.945 kg	1	1000001892
Press jaw standard >B< MaxiPro	3/4″	1.895 kg	1	1000001893
Press jaw standard >B< MaxiPro	7/8″	2.000 kg	1	1000001894
Press jaw standard >B< MaxiPro	1″	1.930 kg	1	1000001895
Press jaw standard >B< MaxiPro	1.1/8″	1.930 kg	1	1000001896
Press jaw standard set >B< MaxiPro	1/4-5/8″	6.000 kg	1	1000003581
Press jaw standard set >B< MaxiPro	1/4-1.1/8″	18.100 kg	1	1000002207

Press rings >B < MaxiPro

FOR ROMAX NANO/ROMAX COMPACT III/
ROMAX COMPACT TT/ROMAX 4000/ROMAX 3000 AC/
ROMAX AC ECO

Suitable for use in pipe systems for refrigeration systems and heat pumps from -40 °C to +140 °C at a maximum operating pressure of 48 bar.











Actuator jaws are not included in the sets!

Model	Press ring Ø	Weight	PU	No.
Press ring >B< MaxiPro	1/4″	0.200 kg	1	1000003610
Press ring >B< MaxiPro	3/8″	0.200 kg	1	1000003611
Press ring >B< MaxiPro	1/2″	0.200 kg	1	1000003612
Press ring >B< MaxiPro	5/8″	0.250 kg	1	1000003613
Press ring >B< MaxiPro	3/4″	0.280 kg	1	1000003614
Press ring >B< MaxiPro	7/8″	0.310 kg	1	1000003615
Press ring >B< MaxiPro	1″	0.400 kg	1	1000003616
Press ring >B< MaxiPro	1.1/8″	0.380 kg	1	1000003617
Press ring set Small	1/4-5/8″	3.200 kg	1	1000003641
Press ring set Large	1/4–1.1/8″	3.600 kg	1	1000003703
Actuator jaw R Standard		2.360 kg	1	1000003589
Actuator jaw R Compact		1.370 kg	1	1000003590

Press chains standard >B< MaxiPro

For ROMAX NANO/ROMAX 4000/ROMAX 3000 AC/ ROMAX AC ECO

Suitable for use in pipe systems for refrigeration systems and heat pumps from -40 $^{\circ}$ C to +140 $^{\circ}$ C at a maximum operating pressure of 48 bar.







Fig. similar

Model	Press chains Ø	Weight	PU	No.
Press chain standard >B< MaxiPro	For actuator jaw >B< MaxiPro ZB1-MP1.3/8″	1.800 kg	1	1000004601
Actuator jaw >B< MaxiPro ZB1-MP	Press chain >B< MaxiPro 1.3/8"	2.100 kg	1	1000004602

Press jaw sets >B < MaxiPro

An innovative press system suitable for air-conditioning and refrigeration applications consisting of Conex Bänninger® >B< MaxiPro® fittings, suitable press jaws and press machines from ROTHENBERGER.

Tight connections up to 48 bar

- The O-ring is resistant against several oils including ester oil.
- The 3-point press, one on each side of the bead and one press compressing the O-ring, provides a permanent and secure joint.

The advantages

- Only 3 seconds per joint completion
- Saves approx. 3 minutes per connection
- · Flame-free joint, no hot work permit needed
- No need for nitrogen purge

Made-to-last through laser hardening

The press jaws are partially laser-hardened. This makes them particularly durable in those places that take the most pressure. Laser hardening increases the jaws' durability considerably.



Press jaw for ROMAX Compact III No. 1000001751



Press jaw for ROMAX 4000, ROMAX 3000 AC and ROMAX AC ECO No. 1000001891



Press ring set >B< MaxiPro No. 1000003641





Technical Data

Application	Air-conditioning and refrigeration
Connections	Copper to copper
Dimensions	1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1.1/8"
O-Ring	HNBR
Max. operating pressure	48 bar / 4,800 kPa / 700 psig
Leak tightness	He ≤7,5×10–7 Pa.m3/s at +20 °C, 10 bar
Vacuum	200 microns
Operating temperature	-40 °C up to 140 °C
UL listing continues operating temperature	121 °C
Compatible refrigerants	R32, R134a, R404A, R407C, R407F, R410A, R507, R1234ze, R1234yf, R718, R450A, R513A, R448A, R449A, R407A, R427A, R438A, R417A and R422D

3-point press technology

Three press points: one on each side of the bead and one compressing the O-ring for a permanent and secure joint



Set (No. 1000004286) includes: ROMAX Compact III press machine, 1 × RO BP18/2, 2.0 Ah 18 V (No. 1000001652), RO BC14/36 charger, 230 V (No. 1000001654), 8 × press jaws (No. see below), TUBE CUTTER 35 (No. 70027), internal and external deburrer (No. 1500000237), UNIGRAT pencil deburrer (No. 21660), ROVLIES cleaning pads (No. 45268), depth gauge (No. 1000002400), 2 × ROCASE 4414 case system

Model	Press jaws Ø	Weight	PU	AMPShare-No.	CAS-No.
Press jaw set compact >B< MaxiPro	1/4-5/8″	6.000 kg	1		1000003580
Press jaw set compact >B< MaxiPro	1/4–1.1/8″	14.000 kg	1		1000001989
Press jaw set standard >B< MaxiPro	1/4-5/8″	6.000 kg	1		1000003581
Press jaw set standard >B< MaxiPro	1/4–1.1/8″	18.100 kg	1		1000002207
ROMAX Compact III press jaw set >B< MaxiPro incl. 1 × 2.0 Ah battery	1/4-1.1/8″	17.750 kg	1	1000004287	1000004286
ROMAX Compact III press jaw set >B< MaxiPro incl. 1 × 2.0 Ah battery, UK	1/4-1.1/8″	17.750 kg	1	1000004289	1000004288
ROMAX 4000 press jaw set >B< MaxiPro incl. 1 × 4.0 Ah battery	1/4-1.1/8″	24.300 kg	1	1000004175	1000002945
ROMAX 4000 press jaw set >B< MaxiPro incl. 1 × 4.0 Ah battery, UK	1/4–1.1/8″	24.300 kg	1		1000002946

How to install the Conex Bänninger® >B< MaxiPro® system?

Conex Bänninger® >B< MaxiPro® benefits from a 3-point radial press—three press points, one on each side of the bead and one press compressing the O-ring. This provides a permanent and secure joint. As the connection is a mechanical joint, there is no need for nitrogen purge during the joining process.

1. Cut the tube to length.



4. Clean the tube end with a circular movement, avoiding grooves that run parallel to the tube.



7. Mark insertion depth using depth gauge and insert tube fully into the fitting.



2. Deburr and remove all external sharp edges.



5. Check for defects.



8. Align jaws squarely on the fitting and complete the joint.



3. Use a pencil deburrer on internal edges.



6. Ensure the O-ring is seated.



9. Mark the completed joint.



Please note: To ensure a safe and tight connection please follow the detailed Conex Bänninger® >B< MaxiPro® installation process. For more information, please visit the Conex Bänninger® website: conexbanninger.com









Accessories	Weight	PU	No.
TUBE CUTTER 35, 6–35 mm (1/4–1.1/2"), DURAMAG	0.255 kg	1	70027
Internal and external deburrer, 6–35 mm (1/4–1.3/8″)	0.100 kg	1	1500000237
UNIGRAT with HSS deburring blade	0.030 kg	10	21660
ROVLIES, 10 pcs.	0.080 kg	1	45268
Conex Bänninger® >B< MaxiPro® depth gauge	0.050 kg	1	1000002400

Batteries and charger

AMPShare	Weight	PU	No.
RO BP18/2, 2.0 Ah 18 V	0.400 kg	1	1000003859
RO BP18/4, 4.0 Ah 18 V	0.600 kg	1	1000003860
RO BP18/4, 4.0 Ah 18 V, ProCORE	0.520 kg	1	1000003863
RO BP18/8, 8.0 Ah 18 V, ProCORE	0.960 kg	1	1000003864
RO BC18 charger, 230 V	0.550 kg	1	1000003858

CAS	Weight	PU	No.
RO BP18/2, 2.0 Ah 18 V	0.420 kg	1	1000001652
RO BP18/4, 4.0 Ah 18 V	0.575 kg	1	1000001653
RO BP18/4, 4.0 Ah 18 V, Li-HD	0.515 kg	1	1000002548
RO BP18/8, 8.0 Ah 18 V, Li-HD	0.915 kg	1	1000002549
RO BC14/36 charger, 230 V	0.580 kg	1	1000001654

ROLOCK expander power torque

Expanding manual

For expanding, reducing and calibrating soft and semihard pipes Ø8-42 mm (5/16-1.3/4") as well as producing

For efficient, fitting-free installation of pipes in sanitary heating, gas, refrigeration and air-conditioning systems

Suitable for pipes made of:

Copper (soft and semi-hard):

Ø 8-42 mm, 5/16-1.3/4", max. wall thickness 1.6 mm Aluminium (soft):

Ø 8-28 mm, 5/16-1.1/8", max. wall thickness 1.6 mm Precision steel (soft):

Ø 8-28 mm, 5/16-1.1/8", max. wall thickness 1.6 mm Stainless steel (soft):

Ø 8-22 mm, 5/16-7/8", max. wall thickness 1.0 mm









EPT-Technology (Enclosed Power Transmission)

of the expander head offers the following technical benefits:

Concealed bent lever:

Protection against dirt and external mechanical damage

Energy efficient through optimised force transmission: Ergonomic, highly optimised force flow in relation to the hand force of the user, therefore reducing effort

Application Benefits

- Eliminates the cost of purchase and storage of fittings
- Converts deformed pipes into fittings, saves resources
- 50 % reduction of labour, soldering materials, joints and



Made in Germany

The know-how from the pioneer of expanding technology and the leading manufacturer of expanding tools for over 50 years!

according to DVGW standards

TiN Coating (Titannitrid-coating)

of the expander head offers the following technical benefits:

High durability 2,300 HV: Protection against abrasive wear Lower friction value compared to steel: Less effort **Good chemical resistance:** Good protection against corrosion Universal wear resistance: Long-lasting

Model	Weight	PU	No.	
ROLOCK Expander Power Torque 8–42 mm (5/16–1.3/4")	1.000 kg	1	12400	

ROLOCK expander power torque sets

For efficient, fitting-free installation of pipes





Model	Weight	PU	No.
10-12-14-16-18-22 mm	3.600 kg	1	12511
10-12-16-22-28 mm	3.280 kg	1	12505
10-12-15-16-18-22-28 mm	3.570 kg	1	12537
12-14-16-18-22 mm	3.300 kg	1	12509
12–15–18–22 mm	2.930 kg	1	12500
12-15-18-22-28 mm	3.385 kg	1	12503
12-16-18-22-28 mm	3.240 kg	1	12522
12-14-16-18-22-28-32 mm	3.700 kg	1	12538

Model	Weight	PU	No.
12-15-18-22-28-35-42 mm	4.200 kg	1	12526
3/8-1/2-5/8-3/4-1″	3.325 kg	1	12517
3/8-1/2-5/8-3/4-7/8-1.1/8"	3.600 kg	1	12518
3/8-1/2-5/8-3/4-7/8-1-1.1/8"	3.700 kg	1	12536
3/8-1/2-5/8-3/4-7/8-1.1/8-1.3/8"	4.500 kg	1	12541
1/2-5/8-3/4-7/8″	2.900 kg	1	12521
1/2-3/4-1″	2.900 kg	1	12535
1/2-5/8-7/8-1.1/8″	3.000 kg	1	12524

Expander heads

Expander head ROLOCK

For producing standard precision flares Ø8-42 mm (5/16-1.3/4") according to DVGW standards as well as the specifications for the Gas de France


For expanding copper, stainless steel and aluminum pipes in sanitary/heating and refrigeration/air-conditioning technology

Application Benefits

- 50 % reduction in labour, soldering materials and soldered joints
- Depth of the flare is consistent with DVGW standards
- Compulsory guidance guarantees a perfect centred position and uniform capillary gap
- Robust and long lasting with the hardened segments

Made in Germany

The know-how from the pioneer of expanding technology and the leading manufacturer of expanding tools for over 50 years!





Twist and lock system

Bayonet lock enables the expander head to be changed quickly



Specially hardened segments

Robust and long lasting



Step at the end of the segments

Enables recalibration of irregular

6 rivets and guide channels

Compulsory guidance guarantees a perfect centred position and uniform capillary gap

Extra long segments with DVGW standards

Depth of the flare is consistent

Ø		wall th			A-size	Wainbt	No
mm	Cu	AI	Fe	INOX	mm	Weight	No.
8	1.0	1.0	1.0	1.0	6.0	0.120 kg	12408
10	1.0	1.0	1.0	1.0	10.0	0.120 kg	12410
12	1.2	1.2	1.2	1.0	12.6	0.120 kg	12412
14	1.2	1.2	1.2	1.0	12.6	0.120 kg	12414
15	1.2	1.2	1.2	1.0	15.5	0.120 kg	12415
16	1.2	1.2	1.2	1.0	15.5	0.120 kg	12416
18	1.2	1.2	1.2	1.0	17.5	0.120 kg	12418
20	1.2	1.2	1.2	1.0	17.5	0.140 kg	12420
22	1.2	1.5	1.5	1.0	20.5	0.140 kg	12422
28	1.5	1.5	1.5		18.5	0.390 kg	12428
32	1.5				19.5	0.410 kg	12432
35	1.6				19.5	0.430 kg	12435
38	1.6				19.5	0.450 kg	12438
40	1.5				19.5	0.470 kg	12440
42	1.5				19.5	0.470 kg	12442

Ø	Ø max. wall thickness mm		A-size				
Inch	Cu	Al	Fe	INOX	mm	Weight	No.
5/16″	1.0	1.0	1.0	1.0	6.0	0.120 kg	12408
3/8″	1.0	1.0	1.0	1.0	7.4	0.120 kg	12452
1/2″	1.2	1.2	1.2	1.0	11.0	0.120 kg	12453
5/8″	1.2	1.2	1.2	1.0	14.0	0.120 kg	12454
3/4″	1.2	1.2	1.2	1.0	18.1	0.120 kg	12455
7/8″	1.2	1.2	1.2	1.0	18.0	0.140 kg	12456
1″	1.5	1.5	1.5		15.8	0.150 kg	12457
1.1/8″	1.6	1.6	1.6		17.0	0.390 kg	12458
1.1/4″	1.6				17.0	0.410 kg	12459
1.3/8″	1.6				17.0	0.430 kg	12435
1.1/2″	1.6				17.0	0.450 kg	12438
1.5/8″	1.6				17.5	0.470 kg	12462
1.3/4″	1.6				17.5	0.500 kg	12463

Availability, delivery time and price of custom products for other pipe diameters available upon request.

Expander head standard

For producing standard precision flares Ø8-42 mm (5/16-1.3/4") according to DVGW standards as well as the specifications for the Gas de France


For expanding copper, stainless steel and aluminum pipes in sanitary/heating and refrigeration/air-conditioning technology

Application Benefits

- \bullet 50 % reduction in labour, soldering materials and soldered joints
- Depth of the flare is consistent with DVGW standards
- Compulsory guidance guarantees a perfect centred position and uniform capillary gap
- Robust and long lasting with the hardened segments


Made in Germany

The know-how from the pioneer of expanding technology and the leading manufacturer of expanding tools for over 50 years!





Specially hardened segments



Step at the end of the segments

Enables recalibration of irregular

centred position and uniform capillary gap

Extra l	ong se	gments
---------	--------	--------

Depth of the flare is consistent with DVGW standards

	Ø	max.	wall th	ickne	ss mm	A-size		
r	nm	Cu	Al	Fe	INOX	mm	Weight	No.
	8	1.0	1.0	1.0	1.0	6.0	0.120 kg	11008
	10	1.0	1.0	1.0	1.0	10.0	0.120 kg	11010
	12	1.2	1.2	1.2	1.0	12.6	0.120 kg	11012
	14	1.2	1.2	1.2	1.0	12.6	0.120 kg	11014
	15	1.2	1.2	1.2	1.0	15.5	0.120 kg	11015
	16	1.2	1.2	1.2	1.0	15.5	0.120 kg	11016
	18	1.2	1.2	1.2	1.0	17.5	0.120 kg	11018
	20	1.2	1.2	1.2	1.0	17.5	0.140 kg	11020
	22	1.2	1.5	1.5	1.0	20.5	0.140 kg	11022
	28	1.5	1.5	1.5		18.5	0.390 kg	11028
	32	1.5				19.5	0.410 kg	11032
	35	1.6				19.5	0.430 kg	11035
	38	1.6				19.5	0.450 kg	11038
	40	1.5				19.5	0.470 kg	11040
	42	1.5				19.5	0.470 kg	11042

Ø	max.	wall th	ickne	ss mm	A-size		
Inch	Cu	ΑI	Fe	INOX	mm	Weight	No.
5/16″	1.0	1.0	1.0	1.0	6.0	0.120 kg	11008
3/8″	1.0	1.0	1.0	1.0	7.4	0.120 kg	11052
1/2″	1.2	1.2	1.2	1.0	11.0	0.120 kg	11053
5/8″	1.2	1.2	1.2	1.0	14.0	0.120 kg	11054
3/4"	1.2	1.2	1.2	1.0	18.1	0.120 kg	11055
7/8″	1.2	1.2	1.2	1.0	18.0	0.140 kg	11056
1″	1.5	1.5	1.5		15.8	0.150 kg	11057
1.1/8″	1.6	1.6	1.6		17.0	0.390 kg	11058
1.1/4″	1.6				17.0	0.410 kg	11059
1.3/8″	1.6				17.0	0.430 kg	11035
1.1/2″	1.6				17.0	0.450 kg	11038
1.5/8″	1.6				17.5	0.470 kg	11062
1.3/4″	1.6				17.5	0.500 kg	11063

Availability, delivery time and price of custom products for other pipe diameters available upon request.

ROLOCK COMBI KIT expander / extractor

Practical, compact and cost-saving set combinations with ROLOCK expander power torque and tee-extractors. For all common pipe dimensions Ø 12-28 mm (1/2-1.1/8")

Suitable for pipes made of:

Copper, aluminium and steel (soft):

Ø 12-28 mm, 1/2-1.1/8"

Made in Germany

The know-how from the pioneer of expanding technology and the leading manufacturer of expanding tools for over 50 years!



Application Benefits

- Increases safety by reducing the number of connections
- Suitable for making branches even in confined spaces through the compact design
- Toolless fine adjustment of the capillary gap
- Reduces effort required and increases work space
- Up to 67% reduction of soldering materials and soldered joints
- Accurate drilling
- Saves resources by converting scrap pipes into fittings
- Reliable pipe connections to DVGW standards






Fig. similiar

Sets include: ROLOCK expander power torque (No. 12400), ROLOCK expander heads, tee-extractor, special ratchet (No. 27180), adaptor (No. 1500002894), $UNIDRILL\ Automatic\ 28\ (No.\ 21583),\ extractor\ cam\ pincer\ (No.\ 22080),\ carrying\ case$

Model	Weight	PU	No.
1/2-3/4-1"	2.500 kg	1	12605
1/2-5/8-7/8-1.1/8″	2.800 kg	1	12604
12-14-16-18 mm	2.600 kg	1	12602
12-15-18-22 mm	4.400 kg	1	12601

Extractor set

For efficient production of T-branches (extractions) for fitting-free pipe installations, Ø 10-42 mm (3/8-2.1/8")

Suitable for pipes made of:

Copper (soft, semi-hard, hard):

Ø 10–42 mm, 3/8–2.1/8″, max. wall thickness 2.5 mm

Aluminium:

Ø 10–42 mm, 3/8–2.1/8″, max. wall thickness 2.5 mm **Precision steel:**

Ø 10-42 mm, 3/8-2.1/8", max. wall thickness 2.5 mm

& SOTHERWIERGER

Application Benefits

- Eliminates the cost for T-pcs., purchase and storage of fittings
- Extractions even on installed pipes possible
- Accurate drilling
- Optimal positioning with the cam pincher depth adjustment





Fig. similar

Sets include: tee-extractor according to chart, special ratchet (No. 27180), adaptor (No. 1500002894), cam pincer (No. 22080) and special conical drill, UNIDRILL Automatic 42 (No. 21575), carrying case

Model	Weight	PU	No.
1/2-3/4-1″	3.300 kg	1	22135
1/2-5/8-3/4-7/8″	3.480 kg	1	22121
1/2-5/8-7/8-1.1/8″	3.700 kg	1	22124
10-12-14-16-18-22 mm	3.780 kg	1	22111
12-14-16-18-22 mm	3.600 kg	1	22109
12-15-18-22 mm	3.400 kg	1	22100
12-15-18-22-28 mm	3.900 kg	1	22103
12-15-18-22-28-35-42 mm	5.500 kg	1	22126
15-22-28 mm	3.600 kg	1	22127

Extractor

Suitable for producing extractions on copper pipes with Ø 10-54 mm (3/8-2.1/8")

Application Benefits

- Uniform and material friendly extractions without scratches
- Burr-free operation due to specially polished extractor hooks
- Easy insertion into the drilled hole with the special hook desian
- Secure support and positioning for precise 90° branches

Model	Weight	PU	No.
Extractor 10 mm	0.130 kg	1	22010
Extractor 12 mm	0.150 kg	1	22012
Extractor 14 mm	0.160 kg	1	22014
Extractor 15 mm	0.160 kg	1	22015
Extractor 16 mm (5/8")	0.220 kg	1	22016
Extractor 18 mm	0.220 kg	1	22018
Extractor 22 mm	0.350 kg	1	22022
Extractor 28 mm	0.470 kg	1	22028
Extractor 35 mm (1.3/8")	0.700 kg	1	22035
Extractor 38 mm (1.1/2")	0.700 kg	1	22038
Extractor 42 mm	0.890 kg	1	22042

Double V-block

Accurate and firm positioning for exact 90° branches



Specially polished, forged and tempered extractor hooks

Burr-free operation

Special hook design

Easy insertion into the drilled hole

Ratchet adaptor (No. F80053 and F80054) with No. 22050 / 22054 included in scope of delivery (square, 3/4")




Model	Weight	PU	No.
Extractor 54 mm (2.1/8")	1.380 kg	1	22054
Extractor 3/8″	0.110 kg	1	22060
Extractor 1/2"	0.140 kg	1	22061
Extractor 3/4"	0.220 kg	1	22062
Extractor 7/8″	0.350 kg	1	22063
Extractor 1"	0.470 kg	1	22064
Extractor 1.1/8"	0.480 kg	1	22065
Extractor 1.1/4"	0.700 kg	1	22066
Extractor 1.5/8"	0.900 kg	1	22068
Extractor 2"	1.380 kg	1	22050

Spare extractor hook

Hooks, specially polished, tempered from Ø 10-54 mm (3/8-2.1/8")

Model	Weight	PU	No.
Extractor hook 14 mm	0.090 kg	1	1300005047
Extractor hook 42 mm	0.320 kg	1	1300005056
Extractor hook 54 mm (2.1/8")	0.560 kg	1	1300005057
Extractor hook 3/4"	0.140 kg	1	1300005060
Extractor hook 3/8"	0.060 kg	1	1300005058
Extractor hook 7/8″	0.200 kg	1	1300005061


Precise drilling of the pipe without a centre punch—drill stop prevents perforation of the pipe



Insert extractor hook into the drilled hole and screw the bell firmly against




Model Weight No. Extractor hook 1" 1300005062 0.210 kg 1



Using the ratchet, turn the extractor to the left, while paying attention that the V-block is seated securely



After extraction, set correct insertion depth (dependant on pipe Ø) with cam



Simply calibrate the tee Ø on the UNIDRILL Automatic and the drilled hole Ø will automatically correspond to the extractor hook required.

Extractor ratchet

In combination with the neckers for an even and material-friendly necking of pipes and suitable for right- and left-handers.

Application Benefits

- Made of chrome vanadium steel
- Fine toothed, reversible right/left



Model	Weight	PU	No.
Extractor ratchet 10–42 mm (3/8–1.3/4″)	0.435 kg	1	27180
Extractor ratchet 50–54 mm, (2–2.1/8")	1.140 kg	1	27181

Extractor cam pincer

For marking and limiting the insertion depth on the tube for \emptyset 13–38 mm (1/2–1.1/2")

Application Benefits

 Marking point ensures exact insertion depth and prevents poking through



Extractor cam pincer

Limits insertion depth for Ø 13–38 mm (1/2–1.1/2")

Model	Weight	PU	No.
Extractor cam pincer 13–38 mm (1/2–1.1/2″)	0.150 kg	1	22080

TUBE BENDER

Manual bending device for bending tubes, Ø 5–12 mm (1/4–1/2")

Suitable for pipes made of:

Copper (soft) and aluminium: Ø 5–12 mm, 1/4–1/2″ **Precision steel (soft):** Ø 5–12 mm, 1/4–1/2″

Application Benefits

Dimensionally accurate bending even in constrained positions

 Production of overbends, counterbends, floor bends and connecting bends possible in all planes

• Simple and fast change of the bending segment

Quick release and reset of the bending segment

One-handed operation due to ergonomic designFast and precise bending



Quick change of the bending formers

Open bending frame

Production of U-bends, counter bends, swan-neck bends and connecting bends possible at all levels





Release lever

Model	Weight	PU	No.
TUBE BENDER set 5–6–8–10 mm	2.840 kg	1	24131
TUBE BENDER set 6-8-10-12 mm	3.030 kg	1	24132
TUBE BENDER set 8–10–12 mm	2.820 kg	1	24133
TUBE BENDER set 1/4-5/16-3/8-1/2"	2.920 kg	1	24134
TUBE BENDER bare tool without bending segments	0.360 kg	1	766004016
Side shape for TUBE BENDER MAXI 1 piece	0.050 kg	1	24048
Counter-holding plate without side shapes	0.140 kg	1	24049



TUBE BENDER bending segments

Model	Weight	PU	No.
Bending segment for TUBE BENDER 5 mm (3/16")	0.190 kg	1	24001
Bending segment for TUBE BENDER 6 mm (1/4")	0.210 kg	1	R2403200
Bending segment for TUBE BENDER 8 mm (5/16")	0.250 kg	1	R2403300
Bending segment for TUBE BENDER 9 mm	0.360 kg	1	R2403400
Bending segment for TUBE BENDER 10 mm	0.390 kg	1	R2403500
Bending segment for TUBE BENDER 12 mm	0.390 kg	1	24007
Bending segment for TUBE BENDER 3/8″	0.270 kg	1	24006
Bending segment for TUBE BENDER 1/2"	0.390 kg	1	24008

TUBE BENDER MAXI

For accurate one-handed bending up to 90°, Ø 12–26 mm (3/8-7/8'')

For the bending of pipes made of soft copper and aluminium, coated copper and precision steel pipes as well as multilayered composite pipes. Suitable for pipe made of:

 Copper (soft) and aluminium:
 Ø 10-22 mm, 3/8-7/8"


 Copper (coated):
 Ø 10-18 mm, 3/8-5/8"

 Precision steel (soft):
 Ø 10-22 mm, 3/8-7/8"

 MLP (Multilayer):
 Ø 14-26 mm, 5/8-7/8"

Application Benefits

- Quick release and reset of the bending segments
- Bending segments are easily exchanged
- Optimum bending results



Optimum bending results

Plastic bending segments and support segments with high sliding ability

Adjustable bending frame

Production of U-bends, counter bends, swan-neck bends and connecting bends possible at all levels

Model	Weight	PU	No.
TUBE BENDER MAXI set 12–15–18–22 mm	3.500 kg	1	023020X
TUBE BENDER MAXI set 12–14–16–18–22 mm	3.500 kg	1	023021X
TUBE BENDER MAXI set 3/8-1/2-5/8-3/4-7/8"	3.300 kg	1	023022X
TUBE BENDER MAXI set MLP 14-16-18-20-25 mm	3.300 kg	1	023090X
TUBE BENDER MAXI set MLP 14-16-18-20-26 mm	3.300 kg	1	023091X
TUBE BENDER MAXI bare tool without bracket	1.000 kg	1	766100016
Support segment set for TUBE BENDER MAXI MLP R/L, 14–25 mm	0.500 kg	1	23008
Support segment set for TUBE BENDER MAXI R/L, 12–22 mm (1/2–7/8")	0.100 kg	1	23047



TUBE BENDER MAXI bending segments

Model	Weight	PU	No.
Bending segment 10 mm	0.080 kg	1	23001
Bending segment 12 mm	0.080 kg	1	23002
Bending segment 14 mm	0.080 kg	1	23003
Bending segment 15 mm	0.090 kg	1	23004
Bending segment 16 mm	0.100 kg	1	23005
Bending segment 18 mm	0.140 kg	1	23006

Model	Weight	PU	No.
Bending segment 20 mm	0.150 kg	1	23052
Bending segment 22 mm	0.170 kg	1	23007
Bending segment 3/8"	0.070 kg	1	23010
Bending segment 1/2"	0.080 kg	1	23011
Bending segment 5/8"	0.100 kg	1	23012
Bending segment 3/4"	0.120 kg	1	23013

Manual bending devices

PRO BENDER

For Bending of pipes out of copper, stainless steel and carbon steel in the sizes Ø 10 and 16 mm (3/8–3/4")

Suitable for bending copper, stainless steel and carbon steel pipes with Ø 10 and 16 mm (3/8–3/4")

Application Benefits

- Bending of pipes out of copper, stainless steel and carbon steel possible
- Long lasting due to iron body
- Comfortable working due to long levers and rubber handles
- Clamping surface for working with a vice



Model	Weight	PU	No.
PRO BENDER 10 mm (3/8")	2.200 kg	1	1000001431
PRO BENDER 1/2"	2.100 kg	1	767050016
PRO BENDER 16 mm (5/8")	4.000 kg	1	1000000445
PRO BENDER 3/4"	3.900 kg	1	767750016

MULTIBEND

For accurate bending up to 180° of pipes made of soft copper, aluminium and precision steel Ø 10–18 mm (1/4–5/8″)

Application Benefits

- Bending radius display of 0–180° for accurate bending
- Clamp mechanism for better pipe hold allows the bending of shorter pipe pieces
- Light construction allows for fatigue-free hand operation



Measurement scale

Accurate bending possible


Model	Weight	PU	No.
MULTIBEND 180°, 10 mm	0.370 kg	1	25401
MULTIBEND 180°, 12 mm	0.640 kg	1	25402
MULTIBEND 180°, 14 mm	0.980 kg	1	25403
MULTIBEND 180°, 15 mm	1.450 kg	1	25404
MULTIBEND 180°, 16 mm (5/8")	1.460 kg	1	25405
MULTIBEND 180°, 18 mm	2.000 kg	1	25406


MINIBEND

For accurate two handed bending up to 180° of pipes made of soft copper, brass, aluminium and precision steel Ø 6–10 mm (1/4–3/8")

Application Benefits

 Suitable for use in refrigeration and air-conditioning, oil supply, automotive, hydraulic and pneumatic industries







Minimum size chard and bending
radius display on measurement scale

Model	Weight	PU	No.
MINIBEND 1/4-5/16-3/8"	0.420 kg	1	25151
MINIBEND 6-8-10 mm	0.420 kg	1	25150

Copper external bending springs

For free-handed bending of soft copper pipes Ø 8–16 mm (1/4–5/8")

Application Benefits

- Coiled cone for ideal handling even with longer pipes
- Tough and long lasting with the cadmium-plated spring steel
- Optimal spring form prevents buckling in bending radius area



Model	Weight	PU	No.
8 mm	0.070 kg	1	25181
10 mm	0.080 kg	1	25182
12 mm	0.160 kg	1	25183
15 mm	0.220 kg	1	25185

Model	Weight	PU	No.
16 mm	0.230 kg	1	25186
5/16″	0.070 kg	1	25181
1/2″	0.130 kg	1	25190
5/8″	0.220 kg	1	25186

Manual bending devices

ROBEND H+W PLUS bender

For accurate cold bending up to 180°, Ø 8-22 mm (5/16-7/8")

For accurate bending up to 180° on pipes made of:

Copper (soft, semi-hard, hard thin-walled):

Ø 8-22 mm (5/16-7/8")

Copper (coated, also thin-walled):

Ø 10-18 mm (3/8-5/8")

Aluminium and brass:

Ø 8-22 mm (5/16-7/8")

Precision steel (also coated):

Ø 10-22 mm (3/8-5/8")


Seamless stainless steel:

Ø 8-22 mm (5/16-7/8")



Application Benefits

- Accurate bending on continuous pipe
- Retains shape and remains stable
- Two-handed bending possible with the additional handle up to Ø 18 mm (5/8")
- Easy bending through clamping on a vice
- Exact bending with the minimum size chart and bending radius display



Model	Weight	PU	No.
ROBEND H+W PLUS with handle bar, 8 mm 5/16", R 22 mm	0.660 kg	1	24508
ROBEND H+W PLUS with handle bar, 10 mm, R 32 mm	1.180 kg	1	24510
ROBEND H+W PLUS with handle bar, 12 mm, R 38 mm	1.110 kg	1	24512
ROBEND H+W PLUS with handle bar, 14 mm, R 45 mm	1.370 kg	1	24514
ROBEND H+W PLUS with handle bar, 15 mm, R 45 mm	1.375 kg	1	24515
ROBEND H+W PLUS with handle bar, 16 mm 5/8″, R 64 mm	2.620 kg	1	24516
ROBEND H+W PLUS with handle bar, 18 mm, R 64 mm	2.620 kg	1	24518
ROBEND H+W PLUS with handle bar, 22 mm 7/8", R 81 mm	3.800 kg	1	24522
ROBEND H+W PLUS with handle bar, 3/4", R 81 mm	3.850 kg	1	24519
ROBEND H+W PLUS with handle bar, 1/2"	1.110 kg	1	24552

distribution of lubrication

ROBEND H+W PLUS bending sets

For accurate cold bending up to 180°, Ø 8-22 mm (5/16-7/8")

For accurate bending up to 180° on pipes made of: **Copper (soft, semi-hard, hard thin-walled):** Ø 8–22 mm (5/16–7/8″)

Copper (coated, also thin-walled): \emptyset 10–18 mm (3/8–5/8") Aluminium and brass: \emptyset 8–22 mm (5/16–7/8") Precision steel (also coated): \emptyset 10–22 mm (3/8–5/8") Seamless stainless steel: \emptyset 8–22 mm (5/16–7/8")

Application Benefits

- Accurate bending on continuous pipe
- Form and pressure stable
- Free-hand bending with additional lever up to Ø 18 mm (5/8")
 Simple bending by clamping in the vice
- Precision bending with minimum size chart and bending angle display directly on the toolFor accurate cold bending up to 180°, Ø 8–22 mm (5/16–7/8")





ROLUB Anti-Block special gliding shoe

Especially adapted to the ROBEND H+W PLUS bender the ROLUB guide shoe with two-point lubricating chamber system

For copper pipe DIN EN 1057/12735-1/13348, aluminum/precision steel pipe DIN 2391/93/94, stainless steel pipe and others

Application Benefits

- Original spare part from ROTHENBERGER
- ROLUB technology for a wrinkle-free bending results

Elastic honeycomb construction	
Up to 42% less effort due to less friction	52
Constitution of the Consti	
an and a second	
ROLUB special guide Shoe made of high-quality polyamide	Two-point lubricating chamber system
Perfect bending results without	Ensures optimum

Model	Weight	PU	No.
8 mm (5/16")	0.020 kg	1	25308
10 mm (3/8")	0.020 kg	1	25310
12 mm	0.030 kg	1	25312
14 mm	0.030 kg	1	25314
15 mm	0.030 kg	1	25315

Model	Weight	PU	No.
16 mm (5/8")	0.050 kg	1	25316
18 mm	0.050 kg	1	25318
22 mm (7/8")	0.090 kg	1	25322
1/2″	0.030 kg	1	25313
3/4″	0.090 kg	1	25319







Accessories	No.
Handle bar for ROBEND H+W Plus, 8mm (3/8")	25075
Handle bar ROBEND H+W Plus, 10–15 mm	25076
Robend H+W Handle (18–22 mm)	25078
Bending spray 150 ml	25120
ROCASE 6414 red without clip for user manual	1300003542

friction marks

ROBEND 4000 E

Electrical bending machine for bending pipes with Ø 12–35 mm (1/2–1.3/8")

Universal application in sanitary and heating installations, in pipeline construction, refrigeration and air-conditioning systems as well as industrial systems and batch production. Fewer joints means less potential for leaks. Safety implies less likelihood of injury.

Suitable for pipes made of:

Copper (hard, semi-hard and soft DIN EN 1057, 12735-1, 13348): \emptyset 12–35 mm, (1/2–1.3/8")

Copper and precision steel (coated):

Ø 12-28 mm, (1/2-1.1/8")

Precision steel (soft DIN 2391/2393/2394):

Ø 12-28 mm, (1/2-1.1/8")

Threaded steel (DIN 2440/2441):

Ø 1/2", 3/4"

Seamless stainless steel (GW 541):

Ø 12-28 mm, (1/2-1.1/8")






Application Benefits

- Quick return on investment through the savings from joints, soldering material and energy
- Universal application: U-bends, counter-bends, swan-neck bends and connecting bends possible at all levels
- Retains shape and remains stable: bending formers made of high-quality forged aluminium
- · Top-quality, precise and simple to use
- Bending without deformation or ripples due to less friction

Available in the manufacturer-independent battery systems AMPShare—Powered by Bosch or CAS—Cordless Alliance System



ROBEND 4000 E

Model	Weight	PU	AMPShare-No.	CAS-No.
ROBEND 4000 E bare tool 1/2–5/8–3/4–7/8–1.1/8" without battery and charger	29.450 kg	1	1000004881	
ROBEND 4000 E set 1 × 4 Ah battery, 1/2–5/8–3/4–7/8–1.1/8″	29.450 kg	1	1000004193	1000003394
ROBEND 4000 E set 1 × 4 Ah battery, 12–14–16–18–22–28 mm	30.150 kg	1	1000004192	1000003393
ROBEND 4000 E bare tool without battery and charger	17.450 kg	1	1000004190	1000003391
ROBEND 4000 E set 1 × 4 Ah battery, 15–18–22–28 mm	29.150 kg	1	1000004191	1000003392








Forged aluminium segments with bending angle scale $\,$



Comfortable carry handle



Working with a Tripod



Compact, rectangular shape

Bending machines

ROBEND 4000

Portable, sturdy and powerful. Cold bending up to 180°, Ø 12-35 mm (1/2-1.3/8")

Universal application in sanitary and heating installations, in pipeline construction, refrigeration and air-conditioning systems as well as industrial systems and batch production. Fewer joints means less potential for leaks. Safety implies less likelihood of injury.

Suitable for pipes made of:

Copper (hard, semi-hard and soft DIN EN 1057, 12735-1, 13348): Ø 12-35 mm, 1/2-1.3/8")

Copper and precision steel (coated):

Ø 12-28 mm, (1/2-1.1/8")

Precision steel (soft DIN 2391/2393/2394):

Ø 12-28 mm, (1/2-1.1/8")

Threaded steel (DIN 2440/2441):

Ø 1/2", 3/4"

Seamless stainless steel (GW 541):

Ø 12-28 mm, (1/2-1.1/8")

Application Benefits

- · Quick return on investment through the savings from joints, soldering material and energy
- Universal application: U-bends, counter-bends, swan-neck bends and connecting bends possible at all levels
- Retains shape and remains stable: bending formers made of high-quality forged aluminium
- Top-quality, precise and simple to use
- Bending without deformation or ripples due to less friction
- · Motor rating: 1,010 W








Technical Data

Voltage	230 V
Working area diameter	1/2-1.3/8″
Working area diameter	12-35 mm
Output power	1,010 W
Power cable length	300 cm





Fast batch production possible

ROBEND 4000

Model	Weight	PU	No.
ROBEND 4000 bare tool in carrying case without bending segments	14.500 kg	1	1000001559
ROBEND 4000 set 12–14–16–18–22 mm	21.900 kg	1	1000001551
ROBEND 4000 set 12–14–16–18–22–28 mm	24.100 kg	1	1000001552
ROBEND 4000 set 12–15–18–22–28 mm	23.500 kg	1	1000001549
ROBEND 4000 set 15–18–22 mm	24.120 kg	1	1000001554
ROBEND 4000 set 15–18–22–28mm	24.120 kg	1	1000001550
ROBEND 4000 set 15–18–22–28–35 mm	29.000 kg	1	1000001738
ROBEND 4000 set 15–18–22–28–32–35 mm	32.000 kg	1	1000001567
ROBEND 4000 set 15–22–28 mm	21.100 kg	1	1000001545
ROBEND 4000 set 1/2-5/8-3/4-7/8"	19.600 kg	1	1000001553
ROBEND 4000 set 1/2-5/8-3/4-7/8-1.1/8-1.3/8"	29.000 kg	1	1000001565
ROBEND 4000 set 7/8-1.1/8-1.3/8"	22.000 kg	1	1000001566



Bending of pipes made of various materials possible



Comfortable carry handle



Seven-fold drive



ROBEND 4000 with tripod stand

ROBEND 4000 / 4000 E bending sets

For bending pipes Ø 12-35 mm (1/2-1.3/8")

For steel pipe DIN 2440 and DIN 2441 (except 3/4")



For copper pipe DIN EN 1057, 12735-1, precision steel pipe DIN 2391/93/94, stainless steel pipe and others

Model	Weight	PU	No.
Bending set for ROBEND 4000 / 4000 E 12 mm	0.480 kg	1	25612
Bending set for ROBEND 4000 / 4000 E 14 mm	0.480 kg	1	25614
Bending set for ROBEND 4000 / 4000 E 15 mm	0.530 kg	1	25615
Bending set for ROBEND 4000 / 4000 E 16 mm	0.600 kg	1	25616
Bending set for ROBEND 4000 / 4000 E 18 mm	1.170 kg	1	25618
Bending set for ROBEND 4000 / 4000 E 20 mm	1.420 kg	1	25620
Bending set for ROBEND 4000 / 4000 E 22 mm	1.420 kg	1	25622
Bending set for ROBEND 4000 / 4000 E 28 mm	2.900 kg	1	25628
Bending set for ROBEND 4000 / 4000 E 32 mm	3.400 kg	1	1000001561
Bending set for ROBEND 4000 / 4000 E 35 mm	3.600 kg	1	1000001563

For imperial copper pipe DIN EN 1057, 12735-1, precision steel pipe DIN 2391/93/94, stainless steel pipe and others

Model	Weight	PU	No.
Bending set for ROBEND 4000 / 4000 E 1/2"	0.530 kg	1	25652
Bending set for ROBEND 4000 / 4000 E 3/4"	1.420 kg	1	25619
Bending set for ROBEND 4000 / 4000 E 5/8"	0.600 kg	1	762955300
Bending set for ROBEND 4000 / 4000 E 7/8"	1.420 kg	1	762955700
Bending set for ROBEND 4000 / 4000 E 1"	2.900 kg	1	25625
Bending set for ROBEND 4000 / 4000 E 1.1/8"	2.900 kg	1	25626
Bending set for ROBEND 4000 / 4000 E 1.1/4"	3.400 kg	1	1000001561
Bending set for ROBEND 4000 / 4000 E 1.3/8″1	3.600 kg	1	1000001563

¹⁾ Bending former sets (No. 1000001561 / No. 1000001563) are only compatible with ROBEND 4000 / ROBEND 4000 E. Only matching with optional plastic carrying case (No. 1000001564).

Push bending bending mark


Symbols

 $L_1 L_2 = Leg length$ a = Lay out length


L = Total length of the pipe piece L_w = Distance/pipe end—wall A_w = Distance/pipe middle—wall

 $L_{M}^{W} = Minimum length^{2}$ $L_{D} = Reserve length^{2}$

45°-arc



90°-arc



$$L = L_1 + L_2 - L_M$$

 $a = L_1 - L_R$

Fig. ROBEND 4000/4000 E bending

set with ROLUB special guide shoe

Calculation examples TUBE BENDER MAXI

Specifications:


Installation in corner areas L_w = 1,200 mm A_w = 30 mm Pipe-Ø 12 mm, 90°-arc

Sought after:

Leg length L₁ Applied size a

Solution:

Summary from the TUBE BENDER MAXI bending table



Leg length $L_1 = L_w - A_w = 1,200 - 30 = 1,170 \text{ mm}$

Applied size $a = L_1 - L_R = 1,170 - 7.5 = 1,162.5 \text{ mm}; L_R ... \text{ Tabular value}$


TUBE	BENDER	at	45°	at	90°	at '	180°
for Ø mm/inch	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm
4.75 / 5"	20.0	4.5	1.0	4.5	10.0	_	_
6	23.5	5.0	1.2	5.0	11.5	_	_
8	28.0	7.0	1.4	7.0	14.0	_	_
9	30.0	7.0	1.5	7.0	15.0	_	_
10	34.0	7.5	1.8	7.5	17.5	_	_
12	37.5	8.5	1.9	8.5	19.0	_	_
3/16″	20.0	4.5	1.0	4.5	10.0	_	_
1/4″	23.5	5.0	1.2	5.0	11.5	_	_
5/16"	28.0	7.0	1.4	7.0	14.0	_	_
3/8″	34.0	7.5	1.8	7.5	17.5	_	_
1/2″	37.5	8.5	1.9	8.5	19.0	_	_

TUBE BEN	IDER MAXI	at 45°		at 90°		at 180°
for Ø mm/inch	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm
12	35.0	0.8	10.0	7.5	35.5	_
14	42.5	0.9	12.5	9.0	42.5	_
15	48.5	1.1	14.0	10.5	48.5	_
16	49.0	1.1	14.5	10.5	49.0	_
18	74.0	1.7	22.0	16.0	74.0	_
22	87.0	1.9	22.5	18.5	87.0	_
3/8″	35.0	0.8	10.0	7.5	35.0	_
1/2″	35.0	0.8	10.0	7.5	35.0	_
5/8″	49.0	1.1	14.5	10.5	49.0	_
3/4″	74.0	1.7	22.0	16.0	74.0	_
7/8″	87.0	1.9	25.5	18.5	87.0	_

TUBE BENI	TUBE BENDER MAXI CT		at 45°		90°	at 180°	
Tube Ø Ws mm	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	
10×0.6	42.5	0.8	12.5	9.0	42.5		
12×0.6	49.0	1.1	14.5	10.5	49.0		
15×0.7	74.0	1.7	22.0	16.0	74.0		
18×0.7	87.0	1.9	25.5	18.5	87.0		



Pull bending



Symbols

 L_1 L_2 = Leg length a = Lay out length


L = Total length of the pipe piece L_w = Distance/pipe end—wall A_w = Distance/pipe middle—wall


 $L_{M}^{"}$ = Minimum length¹ $L_{R}^{"}$ = Reserve length¹


45°-arc

90°-arc

180°-arc







Calculation examples ROBEND 4000 / ROBEND 4000 E

Specifications:


Installation in corner areas L_w = 1,200 mm A_w = 30 mm Pipe-Ø 12 mm, 90°-arc

Sought after:

Leg length L₁ Applied size a

Solution:

Summary from the ROBEND 4000 / ROBEND 4000 E



Leg length

 $L_1 = L_W - A_W = 1,200 - 30 = 1,170 \,\text{mm}$

Applied size

 $a = L_1 - L_R = 1,170 - 42 = 1,128 \text{ mm}; L_R ... Tabular value}$

ROBEND	H+W PLUS	at	45°	at	90°	at 1	180°
for Ws mm/inch	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _m mm
8	22	9	_	22	9.5	22	47
10	32	12	_	32	15.0	32	34
12	38	15	_	40	20.0	38	39
14	45	17	_	44	22.0	44	51
15	45	17	_	44	22.0	44	51
16	64	25	_	67	30.0	68	65
18	64	25	_	67	30.0	68	65
20	81	30	_	85	40.0	86	83
22	81	30	_	85	40.0	86	83
5/16"	22	9	_	22	9.5	22	47
3/8″	32	12	_	32	20.0	32	34
1/2″	38	15	_	40	22.0	38	39
5/8″	64	25	_	67	30.0	68	65
3/4"	81	30	_	85	40.0	86	83
7/8″	81	30	_	85	40.0	86	83

MIN	IBEND	END at 45°		at	90°	at 180°	
for Ws mm/inch	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm
6	25.0	10.4	1.0	22.0	10.0	22.0	26.0
8	24.0	9.9	1.0	32.0	15.0	32.0	34.0
10	23.0	9.5	1.0	32.0	15.0	32.0	34.0
1/4″	25.0	10.4	1.0	22.0	10.0	22.0	26.0
5/16"	24.0	9.9	1.0	32.0	15.0	32.0	34.0
3/8″	23.0	9.5	1.0	32.0	15.0	32.0	34.0

Standard	bender 180°	at	at 45°		90°	at 1	180°
for Ø mm/inch	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm
6	18.0	7.0	0.8	18.5	8.0	18.5	20.0
10	30.0	11.5	1.3	30.5	14.5	30.5	34.0
12	36.0	14.0	1.5	36.5	15.0	36.5	37.5
14	47.5	18.5	2.0	48.5	20.5	48.5	52.5
15	54.0	21.0	2.3	56.0	24.5	56.0	58.0
16	58.0	22.5	2.5	64.0	28.5	64.0	67.0
18	66.0	25.5	2.8	68.0	31.0	68.0	72.0
1/4″	18.0	7.0	0.8	18.5	8.0	18.5	20.0
5/6″	24.0	9.5	1.0	24.0	12.0	24.0	27.0
1/2″	42.0	16.5	1.8	49.5	22.5	49.5	53.0
5/8″	58.0	22.5	2.5	64.0	28.5	64.0	67.0

MUL	TIBEND	at 45° at 90		90°	at 180°		
for Ø mm/inch	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm
8	24.0	9.5	1.0	24.0	10.0	24.0	26.0
10	30.0	12.0	1.3	30.5	14.5	30.5	32.5
12	36.0	14.0	1.5	36.5	15.5	36.5	37.5
14	42.0	16.5	1.8	42.0	19.5	42.5	44.0
15	48.0	19.0	2.0	48.0	22.0	48.0	53.0
16	48.0	19.0	2.0	48.0	22.0	48.0	53.0
18	54.0	21.0	2.3	54.0	26.0	54.5	58.0

ROBE	ROBEND 4000 / 4000 E		at 45°		at 90°		at 180°	
for Ø mm/inch	Pipe	Bending radius R (mm)	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm	Reserve lenght L _R mm	Minimum lenght L _M mm
12		42.0	16	_	42	24	42	68
14	wated	52.5	21	_	53	30	53	87
15		52.5	21	_	53	30	53	87
17	wated	72.0	28	_	72	41	72	107
18		72.0	28	_	72	41	72	107
20	wated	88.5	35	_	89	51	89	121
22		88.0	35	_	88	50	88	119
24	wated	112.0	43	_	110	62	110	144
28		112.0	44	_	112	64	112	148
30	wated	112.0	45	_	114	66	114	152
32/1.1/4"		128.0	52	_	140	70	135	140
35 / 1.3/8"		140.0	55	_	150	80	145	150
3/8″	steel	12.0	31	_	80	46	80	103
1/2″	copper	45.0	18	_	45	26	45	74
1/2″	steel	88.0	35	_	88	50	88	119
5/8″	copper	56.0	23	_	56	32	56	93
3/4"	steel	112.0	43	_	112	64	112	148
3/4"	copper	80.0	31	_	80	46	80	103
7/8″	copper	88.0	35	_	88	50	88	119
1″	copper	112.0	44	_	112	64	112	148
1.1/8"	copper	112.0	45	_	114	66	114	152

ROFLARE REVOLVER

Revolver reeling flaring tool

For the reliable and fast production of standard single 45° flares in accordance with EN 14276-2 and JIS B8607:2008 on copper soft pipes Ø 6–18 mm and 1/4–3/4″

Application Benefits

- Guaranteed norm flares
- Produces leak free joints
- One-handed quick clamping system
- Automatic depth stop: perfect positioning of the pipe to the flaring cone





Adapter recording
For ratchet and electric drive

Spring loaded safety clutch
No reduction of wall thickness

High-quality revolver die
Highest fitting accuracy with long service life

Recuperating spring
Automatic support to pull back the flexible revolver die

Durable and slip-proof

Set (No. 100000230) includes: ROFLARE REVOLVER metric incl. ratchet adaptor, dies \emptyset 6, 8, 10, 12, 16 and 18 mm, pipe cutter ROTRAC 28 PLUS chrome limited edition (No. 1000000046), ROCASE 4212 (No. 1300003334)

Set (No. 1000000231) includes: ROFLARE REVOLVER imperial incl. ratchet adaptor, dies Ø 1/4 , 5/16, 3/8, 1/2, 5/8 and 3/4", pipe cutter ROTRAC 28 PLUS chrome limited edition (No. 1000000046), ROCASE 4212 (No. 1300003334)

Model	Weight	PU	No.
Metric, 6-8-10-12-16-18 mm	1.300 kg	1	1000000222
Imperial, 1/4–5/16–3/8–1/2–5/8–3/4″	1.710 kg	1	1000000223
Set metric with ROTRAC 28 PLUS chrome, limited edition	1.300 kg	1	1000000230
Set imperial with ROTRAC 28 PLUS chrome, limited edition	1.900 kg	1	1000000231

Compact design enables use in confined spaces



Automatic depth stop: perfect positioning of the pipe to the flare



6

Reeling flaring tool

For producing precise 45° single flares on copper pipes \emptyset 6–18 mm (1/8–3/4")

Application Benefits

- Controlled expanding and shaping of the pipe without tearing
- No reduction in wall thickness
- No slipping of the pipe
- · Sturdy and long lasting







single flare



Flaring

Fig. similar

Reeling flaring tool set includes: reeling flaring tool in plastic case with mould in metric and / or imperial format

Model	Weight	PU	No.
Dies metric, 6–8–10–12–14–15–16–18 mm	0.400 kg	1	222413
Dies imperial, 1/8–3/16–1/4–5/16–3/8–1/2–5/8–3/4″	0.400 kg	1	222412
Set metric, 6–8–10–12–14–15–16–18 mm	2.080 kg	1	222403
Set imperial, 1/8–3/16–1/4–5/16–3/8–1/2–5/8–3/4″	2.030 kg	1	222402
Set metric and imperial, 6-8-10-12-14-15-16-18 mm 1/8-3/16-1/4-5/16-3/8-1/2-5/8-3/4″	2.650 kg	1	222401

Universal flaring tool

For producing precise 45° single flares on copper pipes Ø 4–16 mm (3/16–5/8″)

Application Benefits

- Universal application and highest flare precision through selfcentring pipe clamp for all diameters
- Controlled flaring without tearing, forming perfect surfaces
- · Hardened flare cone with special geometry







Universal flaring tool set (No. 222601) includes: universal flaring tool for pipe diameters 4–16 mm, 3/16–5/8", in plastic case

Model	Weight	PU	No.
Universal flaring tool 4–16 mm (3/16–5/8″)	0.900 kg	1	222601

Expanding/Extracting/Flaring accessories

ROTORQUE AIRCON/REFRIGERATION

Step-less torque wrench

Self-locking rack and pinion drive enables quick and reliable fastening of flare nuts sizes 15-32 mm in accordance with EN 378-2:2012-08

Application Benefits

- Always fits, covers all flare nut sizes from 15–32 mm
- Won't slip thanks to the self-locking rack and pinion drive and ratchet function
- Simple and reliable: required torque in accordance with EN 378-2:2012-08 is embossed on the head for every size and can not be rubbed off
- Embossed torque data: easy tightening according to norm
- ROTORQUE REFRIGERATION is suitable for cylinder heads work





Fully opened head



ROTORQUE sets include: torque wrench, head, carrying bag

Model	Weight	PU	No.
ROTORQUE AIRCON	1.500 kg	1	1000000224
ROTORQUE REFRIGERATION	1.400 kg	1	1000000225

Connection 9 × 12

Head can be exchanged between ROTORQUE AIRCON and ROTORQUE REFRIGERATION

All-In-One: one head fits all sizes!



The torque can be read of

Always tighten according to the standard

ROTORQUE AIRCON torque wrench

- 10-110 Nm
- ±4% accuracy
- 1 Nm adjustment steps

ROTORQUE REFRIGERATION torque wrench

- 10-70 Nm
- ±3% accuracy
- 1/2 Nm adjustment steps
- Suitable for cylinder heads' work



Fig. ROTORQUE AIRCON torque wrench



Fig. ROTORQUE REFRIGERATION torque wrench

Torque wrench set

For proper tightening of flange connections

Set with adjustable torque wrench (10-70 Nm) and 6 spanner inserts sizes 17, 22, 24, 26, 27 and 29 mm for flange connections on 1/4", 3/8", 1/2" and 5/8" pipe lines according to DIN EN 378-2:2012-08

Application Benefits

- For proper tightening of flare nuts
- Torque adjustable between 10 and 70 Nm
- 6 interchangeable spanner inserts with width 17, 22, 24, 26, 27 and 29 mm
- For flare connections with pipe diameter of 1/4", 3/8", 1/2" and 5/8" according to DIN EN 378-2: 2016
- · All components in a carrying case

Fix with torque urgently necessary!







Fig. similiar

Pipe-Ø	Spanner width	Locking torque
1/4″ / 6 mm	17 mm	14–18 mm
3/8″/10 mm	22 mm	33-42 mm
1/2″/12 mm	24 mm	50-62 mm
1/2″/12 mm	26 mm	50-62 mm
5/8″/15/16 mm	27 mm	63-77 mm
5/8″/15/16 mm	29 mm	63-77 mm

7 pcs. set (No. 175001) includes: spanner wrench sizes 17, 22, 24, 26, 27, 29 mm. torque wrench, carrying bag

Model	Weight	PU	No.
Torque wrench set 17–22–24–26–27–29 mm	3.500 kg	1	175001

SUPER FIRE 3

Ergonomic HEAVY DUTY brazing tool

For brazing and soldering up to Ø 28 mm as well as for other applications, e.g. dissolving paint or shrinking hoses

Hard soldering: up to \emptyset 28 mm

(with flame reflector in wind-protected environment)

Soft soldering: up to Ø35 mm

Application Benefits

- Fast heating, less consumption!
- Long service life
- "Twist 'n' Load" system (5 different burners)—change burners with one handle
- Exact flame adjustment

Burners with swirl flame
Rapid heat-up, less consumption!

- Up to 2.5 hours brazing with one cartridge
- Comfort for longer working (locking knob)
- Reliable piezo ignition (up to 30,000 ignitions)
- Double safety, as No. gas escape without locking the torch (piezo ignition)

Elaborately manufactured brass/stainless steel design

Long service life

lock









Technical Data

Coupling	7/16" EU
Handle	Aluminium, bolted
Burner	Brass/stainless steel

"Twist 'n' Load"

Fast "Twist 'n' Load" system

Exchange of the burners with one movement (5 different burners available)

Fine regulating valve

Precise flame adjustment



Robust and optimum handling made of high-quality aluminium



High-performance piezo

Only ignites if burner has been securely locked

Reliable (up to 30,000 ignitions)

Locking button

Dual safety

Continual use with only one hand

ROTHENBERGER MAPP¹ gas

Up to 2.5 hours of brazing with one cartridge





High flame temperature based on cyclone swirl



Brazing in refrigeration / air-conditioning technology



For fine soldering; precise and stable flame



Standard burner (700°C)

For soft soldering and other jobs with lower heat application; precise, powerful $% \left(1\right) =\left(1\right) \left(1\right)$ and stable flame



Cyclone burner (950°C)

For hard and soft soldering with an efficient swirl flame (allows pipe to heat up evenly)



Hot air burner (400°C)

For the removal of paint and for shrinking work up to approx. 80 mm diameter; wind-stable, powerful current of hot airpowerful, wind-stable soft flame



Shrinking burner (720°C)

For shrinking up to Ø 300 mm and for heating; powerful, wind-stable soft flame



SUPER FIRE 3 HOT BOX

Application Benefits

- The ideal service kit
- For repairs, heating installations and refrigeration/ air-conditioning technology







5-part set (No. 1000002369) includes: handle (No. 35445), cyclone burner (No. 35457), pin-point burner (No. 35455), flame reflector (No. 31043), universal torch support (No. 35461), 2 × MAPP¹ gas A cartridges (No. 035521-A), ROCASE 4414 (No. 1000001945)

Model	Weight	PU	No.
SUPER FIRE 3 HOT BOX EU incl. MAPP ¹ gas A	4.270 kg	1	1000002369
SUPER FIRE 3 HOT BOX EU incl. MAPP ¹ gas B	4.165 kg	1	1000002370
SUPER FIRE 3 HOT BOX EU incl. MAPP ¹ gas C	4.165 kg	1	1000002371

SUPER FIRE 3



No. 35436

When placing your order, remember to order the universal torch support (No. 35461) for stationary soldering, too!



No. 035648X

Set (No. 35436) includes:

handle (No. 35445), cyclone burner (No. 35457)

Model	Weight	PU	No.
SUPER FIRE 3 with cyclone burner 7/16″ EU	0.550 kg	1	35436
SUPER FIRE 3 with cyclone burner 1″ US	0.700 kg	1	35431
SUPER FIRE safety adaptor 7/16" to 1"	0.102 kg	1	035648X

SUPER FIRE 4

Ergonomic professional soldering tool

For hard soldering up to Ø 28 mm and soft soldering up to Ø 35 mm as well as for other applications, such as dissolving paint or shrinking hoses

Hard soldering: up to Ø 28 mm

(with flame reflector in wind-protected environment)

Soft soldering: up to Ø35 mm

Application Benefits

- Fast heating of the material, less consumption!
- "Twist 'n' Load" system (5 different burners)—Replacing the burner with just one handle.
- · Precise flame adjustment
- Improved locking mechanism for one-handed use
- Reliable piezo ignition (up to 30,000 ignitions)
- Double safety, No. gas leakage without locking the burner (piezo ignition)
- Longer handle for even more stable positioning on the gas cartridge









Technical Data


Coupling	7/16" EU
Handle	Plastic, rubberized
Burner	Brass/stainless steel

"Twist 'n' Load"


Fast "Twist 'n' Load" system



Brazing in refrigeration / air-conditioning technology



High flame temperature based on cyclone swirl



Brazing in refrigeration / air-conditioning technology



For fine soldering; precise and stable flame

Standard burner (700°C)

For soft soldering and other jobs with lower heat application; precise, powerful $% \left(1\right) =\left(1\right) \left(1\right)$ and stable flame



Cyclone burner (950°C)

For hard and soft soldering with an efficient swirl flame (allows pipe to heat up evenly)



Hot air burner (400°C)

For the removal of paint and for shrinking work up to approx. 80 mm diameter; wind-stable, powerful current of hot airpowerful, wind-stable soft flame



Shrinking burner (720°C)

For shrinking up to Ø 300 mm and for heating; powerful, wind-stable soft flame



SUPER FIRE 4 HOT BOX

Application Benefits

- The ideal service kit
- For repairs, heating installations and refrigeration/ air-conditioning technology







5-part set (No. 1000002364) includes: handle (No. 1500001354), cyclone burner (No. 35457), pin-point burner (No. 35455), flame reflector (No. 31043), universal torch support (No. 35461), $2 \times MAPP^1$ gas A cartridges (No. 035521-A), ROCASE 4414 (No. 1000001945)

Model	Weight	PU	No.
SUPER FIRE 4 HOT BOX EU incl. MAPP¹ gas A	4.055 kg	1	1000002364
SUPER FIRE 4 HOT BOX EU incl. MAPP¹ gas B	3.965 kg	1	1000002366
SUPER FIRE 4 HOT BOX EU incl. MAPP¹ gas C	4.095 kg	1	1000002368
SUPER FIRE 4 HOT BOX US incl. MAPP ¹ gas US	4.055 kg	1	1000001630

SUPER FIRE 4



No. 1500001355

When placing your order, remember to order the universal torch support (No. 35461) for stationary soldering, too!



No. 035648X

Set (No. 1500001355) includes:

handle (No. 1500001354), cyclone burner (No. 35457)

Model	Weight	PU	No.
SUPER FIRE 4 with cyclone burner 7/16″ EU	0.400 kg	1	1500001355
SUPER FIRE 4 with cyclone burner 1″ US	0.370 kg	1	1500001503
SUPER FIRE safety adaptor 7/16" to 1"	0.102 kg	1	035648X

MAPP¹ gas

High-performance gas for brazing and soldering

Flame temperatures up to 2,700 °C and 35 % faster than propane

Application Benefits

- Excellent heat transfer, faster than propane, even in winter below 0 $^{\circ}\text{C}.$
- Increased safety and stability thanks to solid valve and protective collar
- Provides high flame output in any position, even overhead (360°)



- Easy handling
- · Guarantees constant high burning performance
- Longer operating time





Patented design for high pressure gases

Protection collar

Stabilizes the burner on the bottle and protects in case of accidental drop











SUPER FIRE 4 HOT BOX (see page 64)



Protective collar stabilizes the torch and protects against accidental drops

Model	Weight	PU	No.
MAPP ¹ gas 7/16″ EU, version A Languages: DE, GB, FR, ES, IT, PT	0.900 kg	12	035521-A
MAPP ¹ gas 7/16″ EU, version B Languages: DK, NL, SE, FI, FR, RUS	0.900 kg	12	035521-В
MAPP ¹ gas 7/16″ EU, version C Languages: CZ, PL, HU, BG, TR, RO	0.900 kg	12	035521-C

Packaging profile

rackaging prome	
Model	MAPP ¹ gas
No.	035521-A
EAN code	4004625400180
Product size (mm) (W×H)	70×270
Contents (ml)	800
Weight (g)	400
Unit per box	12
Boxes per layer / pallet	10
Layer per pallet	3
Units per pallet	360
Number of pallets per truckload	60
Units per truckload	21,600
Pallet weight (kg)	324
Pallet size (mm) (L×W×H)	800 × 1,200 × 1,000
Carton size (mm) (L×W×H)	290×310×240

Maxigas 400

High-performance welding, cutting and brazing gas for flame temperatures up to 2,200 °C. Gas cartridge with 7/16″ EU coupling thread.







Packaging profile

Model	Maxigas 400
No.	035570-A/-B
EAN code	4004625355701 (A)
Product size (mm) (W×H)	65×260
Contents (ml)	600
Weight (g)	352
Unit per box	24
Boxes per layer / pallet	9
Layer per pallet	3
Units per pallet	648
Number of pallets per truckload	60
Units per truckload	38,880
Pallet weight (kg)	195
Pallet size (mm) $(L \times W \times H)$	800×1,200×1,000
Carton size (mm) (L×W×H)	405×272×264

Multigas 300

Propane / butane gas mixture for flame temperatures up to 1,900 °C. Gas cartridge with 7/16″ EU connection thread.







Packaging profile

Model	Multigas 300
No.	035510-A/-B
EAN code	4004625355107 (A)
Product size (mm) (W×H)	65×260
Contents (ml)	600
Weight (g)	338
Unit per box	24
Boxes per layer / pallet	9
Layer per pallet	3
Units per pallet	648
Number of pallets per truckload	60
Units per truckload	38,880
Pallet weight (kg)	191
Pallet size (mm) (L × W × H)	800×1,200×1,000
Carton size (mm) (L×W×H)	405×272×264

TURBOPROP brazing set

Propane high-performance torch for brazing up to Ø 28 mm and soft soldering Ø 54 mm

For brazing and soft soldering of copper and steel pipes up to $2,200\,^{\circ}\text{C}$ without oxygen, as well as for warming up, shrinking and flame cleaning

Application Benefits

- Bundled, concentrated and hot flame due to built-in gas turbine in brazing burner
- Absolutely gas-tight due to optimized valve technology
- · Gas-saving operation due to smooth-running economy valve
- Quick replacement of burners without tools












Technical Data

Self-induced air	Turbine and combustion chamber
Torch	Surface treated, chromed brass
Hose coupling	G 3/8″LH







Sets include: safety handle with push-in coupling (No. 211121116), brazing burner with push-in nipple Ø 12 mm (No. 31032) / Ø 15 mm (No. 221031500) / Ø 18 mm (No. 221031800), propane hose, 2.5 m with 3/8" LH coupling (No. 32201), safety igniter (No. 32077), replacement flints (No. 32088), open-ended spanner (No. 32073), steel case (No. 31005)

Model	Weight	PU	No.
TURBOPROP brazing set without propane regulator	2.800 kg	1	31090
TURBOPROP brazing set with propane regulator (No. 32081E)	3.100 kg	1	31094

Brazing burner with push-in nipple coupling

Ø mm	Length mm		kWh-kcal-BTU	Weight	No.
12	175	110	1.41-1,210-4,815	0.090 kg	31032
15	195	180	2.30-1,980-7,855	0.110 kg	221031500
18	230	240	3.07-2,640-10,485	0.160 kg	221031800

ALLGAS 2000 set

Universal oxyacetylene soldering and welding torch

The ideal soldering and welding torch for plumbers, heating engineers, refrigeration/air conditioning technicians, the automotive trade and for tinsmiths.

 $\textbf{Soldering range:} \ \mathsf{Up\ to\ 2.5\,mm\ material\ thickness}$

Welding range: 0.2-5 mm

Applicable with fuel gases: Acetylene with oxygen, propane with oxygen, natural gas with oxygen, town gas with oxygen









Application Benefits

- Universally applicable with all common fuel gases and cylinder oxygen
- Almost residue-free emptying of gas cylinders (cost-saving)
- Handy and compact for working in hard-to-reach places
- · Economical and cost-effective for professional use



Model

Flexible pipe welding attachments



Safe and quick flame positioning







ALLGAS 2000 set

Fig. similar

17-part set (No. 35300) includes: handle (No. 35303), mixing burners with union nut (No. 35304), welding tips 0.2–1.0 mm (No. 35305)/1.0–2.0 mm (No. 35306)/2.0–3.0 mm (No. 35307)/3.0–4.0 mm (No. 35308)/4.0–5.0 mm (No. 35309), flexible welding tips size 1 (No. 35313)/size 2 (No. 35314), coupling/union nut size 14 (No. 35315), dispersion burners (No. 35311), 2.5 m dual-hose package (No. 35221), open-ended spanner size 14×19 mm (No. 32073), welding tip holder/spanner (No. 35312), safety igniter (No. 32077), replacement flints (No. 32088), steel case (No. 35319)

Coupling Coupling

Weight

No.

Model	oxygen	fuel gas	Weight	No.
ALLGAS 2000 set (acety	rlene)		3.100 kg	35300
ALLGAS 2000 handle	G 1/4" RH	G3/8″LH	0.280 kg	35303
Mixing burners with un	ion nut		0.040 kg	35304
Model		ng range mm	Weight	No.
Welding tip size 1	().2-1	0.010 kg	35305
Welding tip size 2	1.	0-2.0	0.010 kg	35306
Welding tip size 3	2.	0-3.0	0.010 kg	35307
Welding tip size 4	3.	0-4.0	0.010 kg	35308
Welding tip size 5	4.	0-5.0	0.010 kg	35309
Welding tip holder, can	be used as	a spanner	0.020 kg	35312
Flexible welding tip size	e 1 2.	0-3.0	0.040 kg	35313
Flexible welding tip size	2 4.	0-5.0	0.040 kg	35314
Coupling/union nut siz	e 14		0.010 kg	35315

ALLGAS 2000 PS 0,5/2 Compact

Portable brazing equipment with carrying frame

For brazing iron, steel, sheet steel, pipes and non-ferrous metals

Application Benefits

- Secure transport in closed supporting frame
- Portable, light brazing equipment
- Ideal for mobile building-site and repair use
- Small propane cylinders can be refilled

Technical Data

Gas	Propane and oxygen
Flame temperature	3,100°C
Working temperature	1,300°C

With safety devices to prevent flashbacks

24-part set (No. 35655) includes: ALLGAS 2000 handle (No. 35303), propane hose, 2.5 m (No. 32201), oxygen hose, 2.5 m (No. 35210), propane regulator adjustable 0-6 bar (No. 242206000), oxygen pressure reducer 10 bar (No. 35364), mixing burners with union nut (No. 35304), welding tips 0.2–1.0 mm (No. 35305)/1.0–2.0 mm (No. 35306)/2.0–3.0 mm (No. 35306)/2.0–4.0 mm (No. 35308)/4.0–5.0 mm (No. 35309), flexible welding tips size 1 (No. 35313)/size 2 (No. 35314), dispersion burners (No. 35311), welding tip holder/spanner (No. 35312), multi-size spanner (No. 35738), safety igniter (No. 32077), replacement flints (No. 32088), nylon safety goggles (No. 540620), small propane cylinder 0.425 kg, empty (No. 33079), steel oxygen cylinder 2.01, full (No. 35635), oxygen safety device (No. 1000000633), carrying frame (No. 35629)

Model	Weight	PU	No.
ALLGAS 2000 PS 0,5/2 Compact set	21.400 kg	1	35655
Carrying frame without accessories	10.300 kg	1	35629















Carrying comfort





ALLGAS 2000 welding tips

For brazing iron, steel, sheet steel, pipes and non-ferrous metals

Model	Welding range mm	Weight	No.
Welding tip size 1	0.2-1	0.010 kg	35305
Welding tip size 2	1.0-2.0	0.010 kg	35306
Welding tip size 3	2.0-3.0	0.010 kg	35307
Welding tip size 4	3.0-4.0	0.010 kg	35308
Welding tip size 5	4.0-5.0	0.010 kg	35309
Welding tip holder, can be	used as a spanner	0.020 kg	35312



Welding tips, thread M8×1



No. 35309








No. 35312

Flexible pipe welding attachments

Model	Welding range mm	Weight	No.
Flexible welding tip size 1	2.0-3.0	0.040 kg	35313
Flexible welding tip size 2	4.0-5.0	0.040 kg	35314
Coupling / union nut size 1	4	0.010 kg	35315



Mobile brazing machine with safety devices

For brazing copper, brass, aluminum, iron, steel, sheet metal, pipes and non-ferrous metals

Application Benefits

ALLGAS Mobile Pro

- Mobile soldering set with a weight of less than 6 kg incl. cartridges
- High quality safety devices for both cartridges to prevent flame flashback

 MAPP¹ gas pressure regulator with adjustment range 0–2 bar for constant, low consumption and efficient flame adjustment











Technical Data

Gas	MAPP ¹ gas with oxygen
Flame temperature	over 3,100 °C
Working temperature	1,300°C





Fig. similar

High quality safety devices

Reliable prevention ofgas returns and flashbacks

Pressure regulator 0-2 bar

Constant, low consumption and efficient flame adjustment

Total weight < 6 kg


High mobility in construction site use

High quality rubber hoses

20 bar, certified according to DIN EN ISO 3821, length: 2.5 m

Welding and brazing torches

Including 5 interchangeable burners and a bendable welding attachment for a material thickness up to 5 mm



Model	Weight	PU	No.
MAPP¹ gas 1″ US, 750 ml	0.900 kg	12	35698
MAPP ¹ gas 7/16″ EU, 800 ml	0.900 kg	12	035521-A
Oxygen, disposable, 950 ml, 110 bar	1.330 kg	12	35750
Pressure regulator 1″ US for MAPP¹/LPG	0.380 kg	1	1000000620
Pressure regulator M10 × 1 for oxygen	0.350 kg	1	1000000629

ALLGAS 2000 PS 0,5/2 Basic

Portable fitter's brazing equipment


For brazing iron, steel, sheet steel, pipes and non-ferrous metals

Application Benefits

- · Compact and handy construction for mobile building-site and repair use
- Job compatible combination, assembled and ready to use

18-part set (No. 35651) includes: ALLGAS 2000 handle (No. 35303), propane hose, 2.5 m (No. 32201), oxygen hose, 2.5 m (No. 35210), propane regulator adjustable 0-6 bar (No. 242206000), oxygen pressure reducer 10 bar (No. 35634), mixing burners with union nut (No. 35304), welding tips 0.2–1.0 mm (No. 35305)/1.0– 2.0 mm (No. 35306)/2.0-3.0 mm (No. 35307)/3.0-4.0 mm (No. 35308)/4.0-5.0 mm (No. 35309), welding tip holder/spanner (No. 35312) multi-size spanner (No. 35738), safety igniter (No. 32077), replacement flints (No. 32088), steel oxygen cylinder 2.01, $filled \, (No.\, 35635), \, propane \, cylinder \, 0.5 \, kg, \, empty \, (No.\, 33079), \, ALLGAS \, stand$ (No. 35628)

Model	Weight	PU	No.
ALLGAS 2000 PS 0,5/2 Basic set	14.400 kg	1	35651















without obligation! Fig. similar

ROXY 400 L Set

Standard gas-welding equipment for flame temperatures up to 3,100 °C

For brazing copper, brass, aluminum, iron, steel, sheet metal, pipes and non-ferrous metals

19-part set (No. 035780X) includes: handle with fine regulating valve (No. 35580), Maxigas 400 (No. 035570-A), oxygen cylinder 2.01 (No. 35635), fine regulating valve (No. 263003700), oxygen pressure 10 bar (No. 35634), hose set, 3 m without handle (No. 35785), oxygen blowback protection (No. 1000000633), gas blowback protection (No. 35691), mixing burners with union nut (No. 35587), high-performance tips 1.5 mm (No. 263005600)/2.0 mm (No. 263005400), micro-tips 0.3 mm (No. 35712)/0.5 mm (No. 35696)/0.7 mm (No. 35713), micro-tip adaptor (No. 35585), welding goggles A5 (No. 35621), safety igniter (No. 32077), multi-size spanner (No. 35738), carrying frame (No. 35727)

Model	Weight	PU	No.
ROXY 400 L complete	10.800 kg	1	035780X
ROXY 400 L without oxygen	6.000 kg	1	35782
Welding-handle M14×1	0.120 kg	1	35580
Dual hose set 3 m	0.950 kg	1	35785
Micro-tip adaptor	0.010 kg	1	35585
Micro-tip 0.3 mm	0.010 kg	1	35712
Micro-tip 0.4 mm	0.010 kg	1	35695
Micro-tip 0.5 mm	0.020 kg	1	35696
Micro-tip 0.6 mm	0.020 kg	1	35697
Micro-tip 0.7 mm	0.020 kg	1	35713
High-performance tip 0.7 mm	0.060 kg	1	263005800
High-performance tip 1.5 mm	0.040 kg	1	263005600
High-performance tip 2.0 mm	0.040 kg	1	263005400

Space saving storage in service vehicles!













The bottle colors shown are without obligation! Fig. similar

Magnet welding mirror

Model	Weight	PU	No.
With flexible metal tube/ball joint	0.450 kg	1	540855
Spare steel mirror	0.050 kg	1	540851



Burners cleaner

Model	Weight	PU	No.
In folding case, 11 pcs.	0.020 kg	1	510105



Torch spanner

Model	Weight	PU	No.
With 10 wrench sizes	0.210 kg	1	510106



Welding goggles EN 166

With thermal glasses as per EN 169

Model	Glass	Weight	No.
Nylon safety goggles	A 4	0.060 kg	540620
	Α5	0.060 kg	540621
	clear, non- splintering	0.060 kg	540622
Replacement glass (pair)	A 4	0.030 kg	540625
	Α5	0.010 kg	540626
	clear, non- splintering	0.030 kg	540627
Screw-ring safety goggles	A 4	0.090 kg	540640
	Α5	0.090 kg	540641
Replacement glass (Ø 50 mm)	A4	0.030 kg	540675



ROVLIES cleaning pads

Groove-free cleaning of solder joints on copper tubes due to metal-free fleece

Application Benefits

- Reduction of corrosion damage
- No metallic abrasion, can be used wet and dry
- Removes oxide layers, corrosion, surface dirt, greasy and oily residues
- Solvent resistant and elastic

Model	Weight	PU	No.
ROVLIES, 10 pcs.	0.080 kg	1	45268
ROVLIES counter display, 36 pcs.	2.180 kg	1	045268D





7

Internal brushes for copper pipe

For simple and effective pretreatment of the solder joint with sturdy plastic handle

Ø mm	Weight	PU	No.
12	0.080 kg	1	1000004630
15	0.100 kg	1	1000004632
18	0.120 kg	1	1000004634
22	0.140 kg	1	1000004635
28	0.140 kg	1	1000004636



Hand wire brushes

Model	Rows	Weight	PU	No.
Standard steel	3 rows	0.130 kg	1	561351



Welding blanket

Flame retardant and temperature resistant up to 840 °C

Application Benefits

- Continuous temperature resistant up to 700 °C under direct Flame exposure and liquid slag
- Good formability, long service life, asbestos-free and harmless to health
- Edges chained





Model	L×W×H	Weight	PU	No.
Welding blanket	330 × 500 × 3 mm	0.300 kg	1	31050

Flame reflectors

Application Benefits

- Made of high quality stainless steel
- Protection of surrounding combustible materials
- Optimal heat utilization, saves time and energy



Model	Width mm	Adaptor Ø mm	Weight	PU	No.
65/15	65	8-15	0.100 kg	1	31042
65/22	65	15-22	0.100 kg	1	31043



Soldering & welding - consumables

Hard solder rings

Made of high-quality, silver-phosphorous safety brazing alloy, guaranteed according to EN ISO 17672, CuP 279

Application Benefits

- Ideal for capillary gap soldering in copper pipe installation in sanitary and heating technology
- Exactly matched to the inside diameter of the brazed pipes and fittings according to EN 1254
- · Complete through-soldering of the soldered joints
- Particularly economical work due to precisely metered solder quantity
- · No preparation and rework at the soldering point

Technical Data	
Alloy (weight %)	Ag 1.5–2.5/P 5.9–6.5/Cu rest
Melting range	650-810°C
Joinable materials	Copper, gunmetal, brass, bronze
Flux required with	Gunmetal, brass, bronze with hard solder paste LP 5
Package size	250 g plastic bag





Simple insertion

Precise quantity of solder

Simply heat, no dripping, no reduction of cross-section







Model **Content Weight** No. Hard solder rings S 2, Ø 14 mm 268 pcs. 0.260 kg 40514

Hard solder paste LP 5

Flux for brazing at working temperatures above 600 °C, according to EN 1045, type FH 10, DVGW tested Reg. No. DV-0101AT2245, for gas and water installations with copper pipes, recommended by DVGW according to worksheet GW 2 and GW 7, to be used with silver-containing brazing alloys and any base materials made of steel, copper and copper alloys, brass, gunmetal, effective temperature range 500-800 °C, flux residues must be removed carefully.

Model	Weight	PU	No.
LP 5 in plastic bottle	0.180 kg	1	40500



Hard solder powder HKM

Flux for brazing at working temperatures above 800 °C, according to EN 1045-FH 21, effective temperature range 800-1,100 °C, for copper and copper alloys, brass, red brass, nickel silver, bronze, steel and galvanized steel sheet, gray and malleable cast iron, to be used for welding copper and brass in dry condition, can be mixed to paste with purified water, flux residues must be removed carefully. Free of boric acid.

Model	Weight	PU	No.
HKM in plastic bottle	0.065 kg	1	35611



7

ROLOT hard solders

For copper pipe installation

ROTHENBERGER ROLOT special hard solders are particularly suited for copper pipe installations in cold and hot water systems, for open and closed heating systems, for gas installations in accordance with DVGW Worksheet GW 2 (liquid, natural and town gas) as well as for HVAC and refrigeration applications, and oil pipes. ROTHENBERGER ROLOT is especially suited for capillary soldering of copper pipes without fittings. Copper / phosphorus / silver solders are highly formable, and are therefore recommended for joints that are subjected to high thermal and mechanical alternating loads.

Application Benefits

- Non-foaming
- Heat resistant up to 200°C
- No flux required for copper/copper brazing (except S 34 and S 45)
- Environmentally friendly manufactured with newly developed production technology, corrosion-neutral, scale-free, improved flow behavior



ROLOT S94 CuP 179

Quality hard solder guaranteed according to EN ISO 17672, due to low phosphorus content, the solder has a wide melting range, and creates soldered joints with increased strength. Standard solder for normally-stressed copper pipe installation, especially for capillary soldering with copper pipe installation without fittings.

Technical Data

Alloy (weight %)	Cu 94/P6
Melting range	710-880°C
Working temperature	760°C
Joinable materials	Copper, gunmetal, brass, bronze
Flux required with	Gunmetal, brass, bronze with LP 5



		Weight	PU	No.
2×2	500	1.025 kg	1	40094
	section mm		section mm mm Weight	section mm mm Weight PU

ROLOTS 2

Special quality hard solder, not standardised, similar to EN ISO 17672, with low silver content, matched to normally-stressed copper pipe system, ideal for capillary gap soldering.

Technical Data

Melting range	700-850°C
Working temperature	760°C
Joinable materials	Copper, gunmetal, brass, bronze
Flux required with	Gunmetal, brass, bronze with hard solder paste LP 5



Content	Squared section mm		Weight	PU	No.
1 kg carton	2×2	500	1.025 kg	1	40202

Soldering & welding - consumables

ROLOT S 2 CuP 279

Silver/phosphorus safety hard solder, guaranteed according to EN ISO 17672, for higher-stressed copper pipe systems, ideal for capillary soldering in sanitary, heating and gas installations.



Technical Data

Alloy (weight %)	Ag 2/Cu 91.8/P 6.2
Melting range	645-825°C
Working temperature	710°C
Joinable materials	Copper, gunmetal, brass, bronze
Flux required with	Gunmetal, brass, bronze with hard solder paste LP 5

Content	Squared section mm	Lenght mm	Weight	PU	No.
1 kg carton	2×2	500	1.025 kg	1	40212
1 kg carton	3×3	500	1.025 kg	1	40213

ROLOTS5

Particularly high-quality hard solder, not standardised, similar to EN ISO 17672, with low silver content, ideal for capillary and joint soldering in sanitary, heating and gas installations.



Technical Data

Melting range	710-840°C
Working temperature	750°C
Joinable materials	Copper, gunmetal, brass, bronze
Flux required with	Gunmetal, brass, bronze with hard solder paste LP 5

Content	Squared section mm		Weight	PU	No.
1 kg carton	2×2	500	1.025 kg	1	40502

ROLOT S 5 CuP 281

High-quality silver/phosphorus safety hard solder, guaranteed according to EN ISO 17672, for higher-stressed copper pipe systems, ideal for capillary and joint soldering in sanitary, heating and gas installations.



Alloy (weight %)	Ag 5/Cu 89/P 6
Melting range	645-815°C
Working temperature	710°C
Joinable materials	Copper, gunmetal, brass, bronze
Flux required with	Gunmetal, brass, bronze with hard solder paste LP 5



Content	Squared section mm		Weight	PU	No.
1 kg carton	2×2	500	1.025 kg	1	40005

ROKLIMA MULTI 4F

Fully automatic commissioning and maintenance of air-conditioning units and heat pumps

The innovative unit enables safe and comfortable operation on refrigeration systems. With simple menu navigation, 4 functions (4F) are automatically controlled.

Application Benefits

- Pressure resistance up to 80 bar guarantees full use with heat pumps
- Everything you need within reach
- · Simple menu guidance guarantees appropriate use
- Fully automatic control gives time for parallel work
- Safe transpor
- 4 functions (4F) in one:
- Evacuation
- Charging
- Leakage test
- Control of the recovery process























R134a

Technical Data

Working area pressure	25 micron
Frequency	50 Hz
Voltage	240 V
Working area temperature	-25-50°C
Connection	Bottle adaptor / 1/4" SAE
Suction volume	42 l/min
Resolution Weighing	10 g
Hose length	2,500 mm

Sturdy, compact metal casing

Protects all components such as vacuum pump and scale

Integrated high vacuum pump with 42 l/min suction power

For evacuation of the system in accordance with DIN 8975



small containers

Shock-resistant low pressure and high pressure gauges for various



Secure storage of all accessories



Pressure hoses: 2.5 m long with shut-off



3 different pressure gauges

can be easily entered

Interactive 16-digit display with 4 function buttons All required parameters

Universal use on air-conditioning units with all common refrigerants and operation in the high pressure range with R410A

"Pulse-free", class 1.6, 80 mm

2 pressure hoses (2,500 mm) from the series "Plus" with ball valve

Safe and comfortable operation with refrigerants without the risk of refrigerant loss

Plastic capillary hose

Safe, leak-free filling due to shut-off valve




Bottle adaptor No. 173204/05 for scale

and 1/4" reducing pieces



ROKLIMA MULTI 4F



ROKLIMA MULTI 4F in use (evacuation and charging)



Set (No. 100000138) includes: 2-stage vacuum pump, 2 × low pressure gauges, 1 × high pressure gauge R410A, 2 × pressure hoses with ball valve à 2,500 mm, 2 × bottle connection adaptors (1/4" SAE No. 173205, 5/16" SAE No. 173204), 2 × reducing pieces 1/4" SAE F-5/16" SAE M (No. 170016), precision digital scale up to 100 kg, automatic control, vacuum and pressure switch, mineral oil (No. 169200)

Secure storage of accessories: pressure hoses bottle adaptor, plastic capillary



Precision scale up to 100 kg Resolution: 10 g Accuracy: ±1 %



 Model
 Weight
 PU
 No.

 ROKLIMA MULTI 4F
 17.000 kg
 1
 1000000138

 Reducer pieces
 0.100 kg
 1
 170016

 1/4" SAE F-5/16" SAE M
 0.100 kg
 1
 170016

Ergonomic and compact



Light



ROCADDY 120 R32 (CL) Analog / Digital

Universal sets for evacuation and charging

The universal set ROCADDY is suitable for the installation, maintenance and repair of refrigeration and air conditioning systems and heat pumps.

Application Benefits

- Everything you need within reach
- Flexible use with the individual use of the tools
- · Easy to transport
- Electronic digital scale ROSCALE 120 with a weighing capacity of 120 kg and a measuring accuracy per measuring step of 5 g
- 2-stage high vacuum pump ROAIRVAC (corded / accumulator) with integrated vacuum gauge and solenoid check valve

























- Digital installer aid for automatic calculation of superheat and subcooling. More than 80 refrigerants stored in the unit
- 2 analog 4-way installer aids for the common refrigerants R22, R134a, R404A, R407C and the high-pressure refrigerants R410A and R32
- Pressure hose set of 3 PLUS series hoses with shut-off valve for safe working with refrigerants
- TUBE CUTTER 35 and MINICUT II PRO for cutting tubes of diameter 6-35 mm to length

Flexible application with corded or battery-powered vacuum pump




Secure mounting of the bottle during charging

ROCADDY 120 R32 Analog / Digital (No. 1000002560/1000002561) includes: 2-stage vacuum pump ROAIRVAC R32 1.5 (No. 1000002399), 4-way manifold (No. 170502) / 4-way manifold (No. 1000001427) (Analog), ROCOOL 600 (No. 1000000569) / clamping thermometer (No. 1000000540) (Digital), pressure hose set 5/16"SAE 1,500 mm (No. 1500000030), pressure hose set 1/4"SAE 1,500 mm (No. 1500000028), ROSCALE 120 (No. 173004), 3/8"SAE F-1/4"SAE M (No. 89501), 2 × 5/16"SAE F-1/4"SAE M (No. 01700RD), 5/16"SAE M-1/4"SAE F (No.170016), bottle connection 1/4" (No. 173205), bottle connection 5/16" (No. 73204), mineral oil (0,41), TUBE CUTTER 35 (No. 70027), MINICUT II PRO (No. 70402), transport case (No. 169051)

Model			Weight	PU		No.
R410A	R22	R134a	R407C	R40)4A	R32
ROCADDY	120 R32 A	nalog	20.000 kg	1	10	00002560
ROCADDY	120 R32 D	igital	19.000 kg	1	10	00002561

ROCADDY 120 R32 CL Analog / Digital (No. 1000003622/1000003623) includes: 2-stage battery vacuum pump ROAIRVAC R32 2.0 CL (No. 1000003229), 4-way manifold (No. 170502) / 4-way manifold (No. 1000001427) (Analog), ROCOOL 600 incl. clamping thermometer (Digital) (No. 1000000569), pressure hose set 5/16"SAE 1.5 m (No. 1500000030), pressure hose set 1/4"SAE 1.5 m (No. 1500000028), ROSCALE 120 (No. 173004), 3/8"SAE F-1/4"SAE M (No. 89501), 2×[5/16"SAE F-1/4"SAE M (No. 01700RD), 5/16"SAEM-1/4"SAE F (No. 170016)], bottle connection 1/4" (No. 173205), bottle connection 5/16" (No. 173204), bottle connection for R32 (No. 173206), mineral oil (0,41), TUBE CUTTER 35 (No. 70027), MINICUT II PRO (No. 70402), 8.04h Li-HD battery (No. 1000002549), charger (No. 1000001654), transport case (No. 169051)

Model			Wei	ght	PU		No.
R410A	R22	R134a	R407C	R404	1A	R507	R32
ROCADD	Y 120 R32	2 CL Analog	21.00	00 kg	1	1000	0003622
ROCADD	Y 120 R32	2 CL Digital	20.00	00 kg	1	1000	0003623







ROCOOL 600

For commissioning, maintenance work and documentation of refrigeration systems of all kinds

Application Benefits

- Modular system: The basic device can be fitted with the optional Red Box incl. the Data Viewer software for reading out or recording data on a PC.
- More than 80 refrigerants incl. R32 and R744 (sub-critical) are stored in the device. New refrigerants can be added later using the update function
- Simultaneous calculation of superheat and subcool
- The documentation software Data Viewer generates an automatic report based on the data recorded. Ideal for handing out to the customer (client)
- An external Pirani vacuum probe allows reading of the vacuum where the most precise measurement is possible: directly at the refrigeration system











Technical Data

Working area pressure	-1-60 bar
Working area Temperature	-10-50°C
Recording time	96 h
Connection	1/4″SAE
Display size	11 cm

An absolute all-rounder due to the unique modular system!

Large screen

All important data at a single glance. Strong backlight for dark environment

Connection for the temperature sensor T1

For automatic measurement of superheat data

Connection for the external vacuum probe

For very precise measurement of the vacuum level directly at the refrigeration system

Pressure sensors "Made in Germany"

Precise measurement from -1 to 60 bar

T-connection with Schrader valve 1/4" SAE

3-way function: Evacuation and filling without changing a hose

Y-connections 1/4" SAE

A connection and sealing plug in one. Simple transport of hoses when not in operation





Prevents shock damages and allows a safe handling

Connection for the temperature sensor T2

For automatic measurement of subcool data

Green and red LEDs

An optical signal is displayed once an adequate vacuum level is reached or leakage in the system and also a warning of overpressure



Connection of the Red Box

To record data for up to 96 hours and independent read out of data at a PC

Temperature sensor for a pipe diameter of up to Ø 32 mm



External vacuum probe for very precise measurement of the vacuum



Set (No. 1000000569) includes: ROCOOL 600, 1 temperature sensor Set (No. 1000000570) includes: ROCOOL 600, 2 temperature sensors, carry case Set (No. 1000000572) includes: ROCOOL 600, 2 temperature sensors, red box and data viewer software, carry case

Model Weight PU No. ROCOOL 600 Set with 1 1.495 kg 100000569 temperature sensor, blister ROCOOL 600 Set with 2 4.060 kg 1 1000000570 temperature sensors, case ROCOOL 600 Set with 2 1000000572 temperature sensors, red box, 4.435 kg data viewer software, case

Set (No. 1000000539) includes: Red box, data viewer software, connection cable, external power supply

Model	Weight	PU	No.
Red box, software, connection cable, external power supply	0.338 kg	1	1000000539
Temperature sensor	0.120 kg	1	1000000540
Vacuum probe	0.155 kg	1	1000000541

Analog manifolds

2- and 4-way manifolds

The ROTHENBERGER 4-way manifolds are used for the commissioning and maintenance of air conditioning and refrigeration systems as well as heat pumps.

Pressure gauge Ø80 mm, with pulse-dampening class 1.6

Easy-to-read, high precision display

Large hand valve with color coding


Light, secure and precise opening and closing of the diaphragm $\,$ valve, maintenance free





























Pressure gauge with shock-proof rubber protector

Protects against damage

Valve body made of aluminium with gauge glass

Sturdy despite low weight



2-way manifold

Model			Weight	PU	No.
R22	R134a	R407C	R404A		
2-way, 1/4	″SAE, 34 ba	r	0.700 kg	1	170501
4-way, 1/4	″SAE, 34 ba	ır	0.900 kg	1	170502
R410A	R32				
2-way, 5/1	6″SAE, 60 b	ar	1.010 kg	1	1000001426
4-way, 5/1	6″SAE, 60 b	ar	1.105 kg	1	1000001427

Model	No.
Blue rubber protector for manifold	170545
Red rubber protector for manifold	170546
Valve sets for manifold	170547

Manifold sets

Manifold sets and pressure hoses

2-way manifold (for 170600 and 170607) 4-way manifold (for 170601, 170606, 170602 and 170608)



No. 170602

Pressure hose with ball valve "Plus" (only for 170602 and 170608)

No loss of refrigerant



















Scope of delivery: manifold, pressure gauge with Ø80 mm, "Pulse-free", class 1.6, 3×1,500 mm pressure hoses, plastic carrying case

No.	PU	Weight		Model
		R404A	84a R407C	R22
170600	1	2.700 kg	way, Standard	Manifold s
			32	R410A
170607	1	2.700 kg	way, Standard	Manifold s
		R404A	84a R407C	R22
170601	1	2.800 kg	way I, Standard	Manifold s
			32	R410A
170606	1	2.800 kg	way I, Standard	Manifold s
		R404A	84a R407C	R22
170602	1	2.800 kg	way II, Plus	Manifold s
			32	R410A
170608	1	2.800 kg	way II, Plus	Manifold s

3-piece pressure hose sets

Available in "Standard" and "Plus"

Application Benefits


- No confusion and safe use with the colour coding (blue, red, yellow)
- Teflon seal with up to 10 × longer service life compared to neoprene seal
- Working pressure 60 bar/burst pressure 300 bar. This is an 8% better pressure resistance as previously












"Standard" series	Weight	PU	No.
Vacuum hose 3/8″ SAE, 1.5 m	0.220 kg	1	1500000032
R22 R134a R407C R404A			
Set of 3 pressure hoses 1/4″SAE, 1.5 m	0.760 kg	1	1500000024
Pressure hose yellow, 1/4" SAE, 1.5 m	0.250 kg	1	1500000025
R410A R32			
Set of 3 pressure hoses 5/16″SAE, 1.5 m	0.730 kg	1	1500000026
Pressure hose yellow, 5/16″SAE, 1.5 m	0.250 kg	1	1500000027



"Plus" series with ball valve	Weight	PU	No.
R22 R134a R407C R404A			
Set of 3 pressure hoses 1/4″ SAE, 1.5 m	0.895 kg	1	1500000028
Pressure hose yellow, 1/4″ SAE, 1.5 m	0.250 kg	1	1500000029
R410A R32			
Set of 3 pressure hoses 5/16″SAE, 1.5 m	0.840 kg	1	1500000030
Pressure hose yellow, 5/16″SAE, 1.5 m	0.250 kg	1	1500000031

Tool set Climate I and II

Practical tool set with all tools required

R32



R32

R22

R407C

R404A

For the installation and maintenance of refrigeration systems and heat pumps $% \left(1\right) =\left(1\right) \left(1$

Application Benefits

- Monitor temperature and pressure
- Quality hoses with high bursting pressure
- Pipe cutter for all pipe cross-sections from 3–35 mm (1/8″–1.1/8″)
- Measurement of ambient and ventilator air temperature
- Clean, kink-free bending of all common pipe cross-sections
- Optimum flaring connections for all types of air-conditioner

The ideal introduction into a whole new area of business!



No. 170604

Set Climate I (No. 170604) includes: 2-way manifold (No. 170501), set of pressure hoses standard 1/4" SAE, TUBE CUTTER 35 C (No. 070027C), MINICUT pipe cutter (No. 070401C), thermometer, set of bending springs 3/8"–1/2"–5/8", universal flaring tool (No. 222601), plastic case

Set Climate II (No. 170605) includes: 2-way manifold (No. 1000001426), set of pressure hoses standard 5/16" SAE, TUBE CUTTER 35 C (No. 070027C), MINICUT pipe cutter (No. 070401C), thermometer, set of bending springs 3/8"-1/2"-5/8", reeling flaring tool (No. 222402), plastic case

Model	Weight	PU	No.
Tool set Climate I	2.300 kg	1	170604
Tool set Climate II	2.400 kg	1	170605

Nitrogen set

Multiple uses for refrigeration systems

Application Benefits

- Fine scaled 1.0 gauge—precise reading of the testing pressure
- Spring loaded pressure reducing valve—simple and safe handling
- Connection for large bottles—easy connection for bottles of all sizes possible
- 950 cm³ nitrogen bottle included—complete set



Ideal for split air-conditioning units and heat pumps!



950 cm³ nitrogen bottle included

Complete Set can be used without large Nitrogen bottle

Fine scaled 1.0 pressure gauge

Precise reading of the testing pressure

Spring loaded pressure reducing valve

Simple and safe handling

Connection for large bottles

Any size of bottle can be connected without a problem





Bottle adaptor for connecting 950 cm³



Set (No. 1000003865) includes: pressure reducing valve, connection hose, bottle adaptor, pressure gauge, nitrogen bottle and plastic case

Model	Weight	PU	No.
Nitrogen set incl. 1 kg bottle	4.070 kg	1	1000003865
Nitrogen bottle à 1,900 cm ³	2.900 kg	1	259018
Nitrogen bottle à 950 cm ³	1.235 kg	6	259008

ROLEAK PRO

Electronic leak detection device for locating leaks in refrigeration systems (3 g/a)

Application Benefits

- Durable and highly sensitive sensor tip with a leak detection rate of 3 g/a within 3 seconds
- Suitable for R32
- Simple determination of the refrigerant concentration
- Adjustment of the sensor tips zero measurement point for simple detection of the leak
- Reference leak for functionality test included
- Easy accessibility of even hard to reach leaks

		(
Α	l	_

R407C

R134a









Technical Data

R22


Leak status	LED display
Sensor length	40 cm
Leak detection rate	3 g/a within 3 seconds
Working temperature	0°C up to 40°C
Voltage	6 V (4 AA batteries included)



No. 1500002241

Model	Weight	PU	No.
ROLEAK PRO	1.085 kg	1	1500002241





ROAIRVAC CL

Battery driven two-stage vacuum pump







Application Benefits

- Compatible with CAS or AMPShare battery system
- Solenoid check valve to protect the refrigeration system from oil contamination during power outage
- Protects the integrated components with the light and high-quality casing
- Gas ballast valve for reduction of water vapor in the oil container
- Special filter reduces oil mist on exhaust vent
- · Gauge-glass enables easy oil-stand monitoring
- Fast filling of oil without spilling, no special funnel is necessary
- Easy access to the oil drain plug makes emptying quick
- Thermal switch protects the unit from the motor overheating
- Standard 1/4" SAE connection as well as 5/16" SAE and 3/8" SAE adaptor included in delivery

Technical Data	R32 2.0 CL	R32 5.0 CL
Pump rating	2.0 CFM / 57 l/min	5.0 CFM / 142 l/min
Vacuum stages	2	2
Final vacuum	23 micron	15 micron
Motor power	185 W / 3,600 r/m	550 W / 1,800 r/m
Voltage	18 V	18 V
Connection	1/4″	1/4″
with Adapter	5/16″ SAE M / 3/8″ SAE M	5/16″ SAE M / 3/8″ SAE M
Oil capacity	180 ml	350 ml

Ergonomic handle

Light, compact and easy to transport

Gas ballast valve

Reduction of water vapour in the oil container, guarantees higher evacuation power and service life

Special filter

Reduces oil mist on exhaust vent



Battery LED indicator

Easy management of remaining battery power

Multiple battery systems

Suitable for CAS and AMPShare battery systems (2 different machine versions)

Brushless motor

For wear-free working and a longer life time

high-quality casing
Protects the integrated components

Light and

Available in the manufacturer-independent battery systems AMPShare – Powered by Bosch or CAS – CORDLESS ALLIANCE SYSTEM

1/4″ SAE standard connection with adaptors for 5/16″ SAE and 3/8″ SAE



Optimal positioned viewing glass and oil drains for simple draining of the oil



The battery can be combined accross products and manufacturers



ROAIRVAC CL Series

MPShare-No. 1000004180 / CAS-No. 1000003229 0 CFM / 57 l / min / 4 m³/h	AMPShare-No. 1000004182 / CAS-No. 1000003231 5.0 CFM / 142 I / min / 8.5 m ³ /h
.4 m³/h	8.5 m ³ /h
	0.5111711
	2
3 micron / 0.03 mbar	15 micron / 0.02 mbar
85 W / 3,600 r/m	550 W / 1,800 r/m
8 V	18 V
0 Hz / 60 Hz	50 Hz / 60 Hz
/4"	1/4″
/16″ SAE M / 3/8″ SAE M	5/16″ SAE M / 3/8″ SAE M
80 ml	350 ml
7001/~	7.500 kg
2	BV 0 Hz / 60 Hz 4" 16" SAE M / 3/8" SAE M

Future-proof product for the increased use of R32 refrigerants

ROAIRVAC R32 2.0 CL—vacuum pump in use with the digital manifold ROCOOL 600











No. 1000003229

No. 1000003231

No. 1000003230

No. 1000003233

Model	Weight	PU	AMPShare-No.	CAS-No.
ROAIRVAC R32 2.0 CL, 1×8 Ah battery, charger, ROBUCKET	6.100 kg	1	1000004181	1000003230
ROAIRVAC R32 2.0 CL, without battery and charger	3.700 kg	1	1000004180	1000003229
ROAIRVAC R32 5.0 CL, 1 × 8 Ah battery, charger, ROBUCKET	10.000 kg	1	1000004183	1000003233
ROAIRVAC R32 5.0 CL, without battery and charger	7.500 kg	1	1000004182	1000003231

Vacuum pumps

ROAIRVAC

Two-stage vacuum pump For evacuation in accordance with DIN 8975 with vacuum gauge and solenoid valve

The ROTHENBERGER ROAIRVAC vacuum pumps are used for evacuating all refrigeration circuits according to DIN 8975. The two-stage rotary vane pump achieves a vacuum of less than 25 micron. As a result, air conditioning systems, refrigeration systems and heat pumps can be freed of residual moisture.

RO SERVICE+









Application Benefits

- Solenoid check valve to protect the refrigeration system from oil contamination during power outage
- Vacuum gauge with integrated drag indicator enables simple and quick control of the evacuation process
- Protects the integrated components with the light and high-quality casing
- Gas ballast valve for reduction of water vapour in the oil container
- Special filter reduces oil mist on exhaust vent
- · Gauge-glass enables easy oil-stand monitoring

- Fast filling of oil without spilling, no special funnel is necessary
- · Easy access to the oil drain plug makes emptying quick
- Thermal switch protects the unit from the motor overheating
- Standard 1/4" SAE connection as well as 5/16" SAE and 3/8" SAE adaptor included in delivery
- Removable cable prevents cable damage

ROTHENBERGER

Ergonomic handle

Light, compact and easy to transport

Removable cable

Prevents cable damage

Integrated vacuum gauge

Simple and fast control of the evacuation process

Integrated solenoid valve

Prevents backwash of oil into the refrigeration system

Four-pole motor

Increased torque and long service life (only with ROAIRVAC R32 1.5, 3.0 and 6.0)

Gas ballast valve

Reduction of water vapour in the oil container, guarantees higher evacuation power and service life

Special filter

Reduces oil mist on exhaust vent

Protects the integrated components

Light and high-quality casing

1/4″ SAE standard connection with adaptors for 5/16″ SAE and 3/8″ SAE



Optimal positioned viewing glass and oil drains for simple draining of the oil



Practical: operating instructions always within view



ROAIRVAC series

Тур	ROAIRVAC R32 1.5	ROAIRVAC R32 3.0	ROAIRVAC R32 6.0	ROAIRVAC R32 9.0
No.	1000002399	1000002713	1000001231	1000002714
Pumprating	1.5 CFM / 42 l / min /	3.0 CFM / 85 l / min /	6.0 CFM / 170 l / min /	9.0 CFM / 2551/min /
	2.5 m ³ /h	5.1 m³/h	10.2 m ³ /h	15.3 m³/h
Vacuum stages	2	2	2	2
Final vacuum	15 micron / 0.02 mbar	15 micron / 0.02 mbar	15 micron / 0.02 mbar	15 micron / 0.02 mbar
Motor rating	190 W / 1,720 r/m	250 W / 1,720 r/m	550 W / 1,720 r/m	750 W / 3,440 r/m
Voltage	230 V	230 V	230 V	230 V
Frequency	50 Hz / 60 Hz	50 Hz / 60 Hz	50 Hz / 60 Hz	50 Hz / 60 Hz
Connection	1/4″	1/4″	1/4″	1/4″
with adaptor	5/16″ SAE M / 3/8″ SAE M	5/16″SAE M / 3/8″SAE M	5/16″ SAE M / 3/8″ SAE M	5/16″ SAE M / 3/8″ SAE M
Oil capacity	250 ml	330 ml	580 ml	590 ml
Manifold Ø	45 mm	50 mm	80 mm	80 mm

Future-proof product for the increased use of R32 refrigerants







ROAIRVAC R32 1.5 (42 l/min)

ROAIRVAC R32 3.0 (85 l/min)

ROAIRVAC R32 9.0 (255 l/min)

Mineral oil is included in all pump deliveries






ROAIRVAC R32 6.0 (170 l/min)

Scope of delivery: vacuum pump with 1/4", 5/16" SAE and 3/8" SAE connections, plastic bottle with mineral oil

Model	Weight	PU	No.
ROAIRVAC R32, 1.5 42 l/min	10.100 kg	1	1000002399
ROAIRVAC R32, 3.0 85 l/min	11.900 kg	1	1000002713
ROAIRVAC R32, 6.0 170 l/min	17.500 kg	1	1000001231
ROAIRVAC R32, 9.0 255 l/min	18.400 kg	1	1000002714
Mineral oil, 1 litre	0.945 kg	1	169200





ROREC

Refrigerant recovery device

Compact, portable device for recovery and recycling refrigerants of all kinds.

Application Benefits

- Maintenance-free operation through oil-free compressor
- 4-pole motor guarantees durability of the machine
- Low noise and vibration emissions because of its compact design
- Simple and safe work through intuitive operation
- Emptying of refrigerant residue by using the PURGE function for working with different refrigerants

Ideal for mono and multi-split air-conditioning units and heat pumps!








Technical Data

Suitable for	all A1 refrigerants of the type CFC, HCFH and HFC
Capacity	gaseous: 0.26 kg/min fluid: 1.85 kg/min push/pull: 6.22 kg/min
Electrical data	230 V / 50-60 Hz
Power	370 W
High pressure switch	38.5 bar



Recovery of refrigerant



ROTHENBERGER

Simple and precise reading with the glycol filled pressure gauge



Model	Weight	PU	No.
ROREC	17.000 kg	1	168605
Filter	0.120 ka	1	168713

Practical storage compartment for accessories on the back



ROREC Pro A3

Refrigerant extractor

Refrigerant extraction unit with high extraction capacity for complete emptying of refrigeration and air conditioning systems.

Application Benefits

- Explosion-proof: Suitable for refrigerants of classes A1, A2L, A2 and A3 (e. g. R290)
- Compact design and weight of less than 12 kg
- Digital display and one-button operation
- Maintenance-free operation due to oil-free 2-piston compressor
- · 4-pole motor guarantees longevity of the machine
- Automatic shutdown and automatic start as soon as the pressure rises again
- Draining of refrigerant residues through PURGE function









Technical Data

Recovery rate	gaseous: 0.5 kg/min; 30 kg/h fluid: 3.5 kg/min; 210 kg/h push/pull: 9.5 kg/min; 570 kg/h
Working area pressure	38.5 bar
Input power	750 W
Frequency	50-60 Hz
Voltage	220-240 V

Digital display

Low pressure switch

Automatic shut-off and

automatic restart once

the pressure increases again

Clearly structured display of the measured pressure values



Oil-free 2-piston compressor

Very high recovery rate with maintenance free operation

Purge function for complete draining of the recovery unit



Refrigerant filter for safe recovery included in the



Securely attached power cable



Model	Weight	PU	No.
ROREC Pro A3	12.000 kg	1	1500004451
Filter	0.120 kg	1	168713

ROSCALE 120

Electronic refrigerant scale

Precise, easy to handle refrigerant scale for filling and evacuation processes with a maximal weight capacity of 120 kg.

Application Benefits

- Resolution of 5 g enables very precise filling
- Weight capacity sufficient for all common refrigerant bottles
- Cable connection enables comfortable use in every situation
- Bottle adaptor for connecting small refrigerant bottles (1l and 2l bottles)
- Refrigerant bottles of all sizes have enough space
- Large LCD display for comfortable reading of the result
- Simple use







Technical Data

Weight capacity	120 kg or 264 lbs
Accuracy	± 0.5 %
Resolution	5 g / 0.2 oz.
Working temperature	-10 °C up to 49 °C / 14 °F up to 120 °F
Connection	1/4" SAE for 1–21 bottles
Battery	9 V
Platform size	230×230×53 mm





ROSCALE 120 in carrying case

Set (No. R17300416) includes: ROSCALE 120, 9 V battery, carrying case

Model	Weight	PU	No.
ROSCALE 120 up to 120 kg	3.280 kg	1	R17300416

Refrigerant for air-conditioning units

Non-chlorinated refrigerant of the HFC group in practical 40 bar steel bottles (bursting pressure: 165 bar) TÜV seal No. 0036-043/03D and TPED accepted as per 9/36/CE

With ROTHENBERGER refrigerant, installers and refrigeration technicians can fill air conditioning and refrigeration systems that are particularly difficult to access. Due to the compact bottle, transport to roofs etc. is also easy.

Standardised SAE thread on all bottle valves

Universal application







R32



Model		Weight	PU	No.
R32	Refrigerant R32 in cardb	oard packagin	ıg	
1 I steel bo	ttle 1/2″SAE, 40 bar	1.535 kg	6	170960
2 I steel bo	ttle 1/2″SAE, 40 bar	3.320 kg	4	170961

10

SANIFRESH

Deodorising cleaning spray

Application Benefits

- Removes the threat of disease and allergies—practical and ecologically friendly solution for removing mites, dust, bacteria and spores
- Spray is applied directly to affected surface
- Economical spray can with spray nozzle and spray tube
- Removes unpleasant odours. Pleasant mint smell



Model	Weight	PU	No.
SANIFRESH 12 bottles	3.960 kg	1	85800

Bottle connection and adaptors

For refrigerant bottles

For use with new refrigerant bottles on existing equipment



Model	No.
Adapter 1/2" to 1/4" SAE	170901
Adaptor 1/4" SAE M, 5/16" SAE F, with valve trigger	01700RD
Adapter 1/4" SAE F to 5/16" SAE, M connection	170016
Adapter 1/4″ SAE M, 3/8″ SAE F	89501
Adapter 3/8″ SAE M, 1/4″ SAE F	89503
Bottle adapter 1/4" connection	173205
Bottle adapter 5/16" connection	173204
Bottle adapter W21.8×1/4″ SAE, M connection, seal for 21 sized bottles	170950
Bottle adapter W21, 8 × 1/4″ SAE, M connection (left)	1500003381
Lock valve W 1/4" SAE to M 1/4"	1500004790
Lock valve R32/R410A W 5/16″	1500004791

Torque wrench set

For proper tightening of flange connections

Set with adjustable torque wrench (10–70 Nm) and 6 spanner inserts sizes 17, 22, 24, 26, 27 and 29 mm for flange connections on 1/4'', 3/8'', 1/2'' and 5/8'' pipe lines according to DIN EN 378- 2:2012-08.



Fix with torque urgently necessary!

17-22-24-26-27-29 mm





7-piece set (No. 175001) includes: spanner wrench sizes 17, 22, 24, 26, 27, 29 mm, torque wrench, carrying bag

Ø	Spanner widtl	h I	ockin	g torque
1/4" / 6 mm	17 mm		1	4–18 Nm
3/8″/10 mm	22 mm		3	3-42 Nm
1/2" / 12 mm	24 mm		5	0-62 Nm
1/2" / 12 mm	26 mm	50-62 Nn		
5/8" / 15/16 mm	27 mm		6	3-77 Nm
5/8″/15/16 mm	29 mm		6	3-77 Nm
Model		Weight	PU	No.
Torque wrench set	nm	1.700 kg	1	175001

Accessories

Schrader valve tool

Application Benefits

- For exchanging the Schrader valve on air-conditioners under pressure, without having to recover the unit
- For safe and easy change of spring insert of the Schrader valve tool
- With safety thread for risk-free use





Model	Weight	PU	No.
Schrader valve tool	0.450 kg	1	87800

Plate fin comb

Application Benefits

- For straightening the plate fins of heat-exchangers
- 6 different sizes in one too



Model	Weight	PU	No.
Plate fin comb 8–9–10–12–14–15 fins per inch	0.095 kg	1	224500

Pictograms



230 V



115 V



110 V



Three-phase current 400 V



Batterypowered



Can be used in confined spaces







Light and compact



Basic soft soldering up to 450°C



Hot brazing 450-1,100°C



Max autogen welding 1,100°C



Fast cut



deformation



Dry drilling



Wet drilling



Up to 50% time-saving



Portable operation



360° rotatable



Ergonomic



Meets DIN standards



Propane



Oxygen



Acetylene



Shock absorption



Inspection window



Pressure hose length



Lock button



Bayonet coupling



Push lock



Thread lock



Pressure gauge display adjustable



Pressure gauge classe 1-6



Pressure gauge size



Counter display



Measuring accuracy up to X g



Scale range $up\ to\ X\,kg$



Economy



With USB connection



Touchscreen



WiFi



Piezo ignition



Fine adjustment of the flame



With video function



With photo function



Memory card



Cable length



Sturdy casing



Shock absorption



Transport case



ROCASE case system



RO SERVICE+ warranty



Electric motor without carbon brushes



DURA LAZR TEC laser hardening



Constant Force Technology





eTOOL (NFC tag)



One-handed operation



180° rotatable



App fopr Android and iOS



Optimised cutting geometry

11

Refrigerant data from CFC-alternative refrigerants

Refrigerant	Composition	ODP	GWP	Temperature glide
R22 (HFCKW refrigerant)	CHCLF ₂	0.05	1,810	
R134a (HFKW-chlorine-free refrigerant)	CF₃CH₂F	0	1,430	
R32 (HFKW-chlorine-free refrigerant)	CH ₂ F ₂	0	675	
R404A (HFKW-chlorine-free blends)	52 % R143a, 44 % R125, 4 % R134a	0	3,922	
R507 (HFKW-chlorine-free blends)	50 % R143a, 50 % R125	0	3,985	
R407C (HFKW-chlorine-free blends)	23 % R32, 25 % R125, 52 % R134a	0	1,774	7.5 K
R410A (HFKW-chlorine-free blends)	50 % R32, 50 % R125	0	2,088	0.2 K

ODP = Ozone Depletion Potential (degree in which the ozone layer is destroyed)
GWP = Global Warming Potential (degree in which it contributes to the greenhouse effect)

Instructions for safe and proper use of the refrigerants

Refrigerant

- Wear protective gloves and safety goggles
- · Do not let refrigerant come in contact with skin
- Do not inhale high concentrations of vapours (Lack of oxygen causes a narcotic effect and is a danger to life)
- Do not smoke around refrigerant
- Working place / room must be thoroughly aired, if necessary extracted

Refrigerant bottles

- · Secure against accidents, do not throw
- Do not expose to direct sunlight and do not place near radiators or other heat sources
- Do not use open flame

- Do not disassemble or remove valves
- Damaged bottles need to be properly returned
- Close empty containers

Air-conditioners

- Air-conditioner leaks need to be repaired immediately
- Do not allow refrigerant to leak while filling or doing maintenance work
- In high concentrations (for example pipe burst), leave the room and do not enter again until it has been properly ventilated
- Only do brazing work together with protective nitrogen gas and only in well ventilated areas

Flare connections

Normal flare size in accordance with JIS B8607:2008 Flare outer diameter in relationship to the pipe diameter

Pipe outer diameter mm/inch	Metric	Wall thickness mm/inch	Flare outer diameter with R22-, R134a-, R404-, R407C air-conditioners	Flare outer diameter with R410A air-conditioners
6 mm		1 mm	8.5 mm	9.1 mm
8 mm		1 mm	11.1 mm	11.1 mm
10 mm		1 mm	13.6 mm	13.2 mm
12 mm		1 mm	15.3 mm	16.5 mm
16 mm		1 mm	19.5 mm	19.2 mm
18 mm		1 mm	22.0 mm	22.7 mm
1/4″	6.35 mm	0.35″	9.0 mm	9.1 mm
5/16″	7.94 mm	0.35″	11.0 mm	11.1 mm
3/8″	9.52 mm	0.35″	13.0 mm	13.2 mm
1/2″	12.70 mm	0.35″	16.2 mm	16.6 mm
5/8″	15.88 mm	0.35″	19.4 mm	19.7 mm
3/4″	19.05 mm	0.35″	23.3 mm	24.0 mm

Conversion table pressure

mbar	Micron	TORR	mm HG Vakuum
10	7,516	7.5	752
5	3,759	3.6	756
2	1,503	1.5	758
1	752	0.75	759
0.5	376	0.36	
0.4	300	0.30	
0.3	225	0.23	
0.2	150	0.15	
0.1	75	0.08	
0.09	68		
0.07	53		
0.06	45		
0.05	38		
0.04	30		
0.03	22		
0.02	15		
0.01	8		

Conversion table temperature

Conversion from °C in °F: °C \times 1.8 + 32 = °F Conversion from °F in °C: (°F-32): 1.8 = °C

°C	°F	°C	°F	°F	°C	°F	°C
100	212	30	86	212	100	70	21
95	203	25	77	200	93	60	16
90	194	20	68	190	88	50	10
85	185	15	59	180	82	40	4
80	176	10	50	170	77	30	-1
75	167	4	39	160	71	20	-7
70	158	0	32	150	66	10	-12
65	149	-10	14	140	60	0	-18
60	140	-20	-4	130	54	-10	-23
55	131	-30	-22	120	49	-20	-29
50	122	-40	-40	110	43	-30	-34
45	113	-50	-58	100	38	-40	-40
40	104	-60	-76	90	32	-50	-46
35	95	-273	-460	80	27	-60	-51
						-112	-80
						-460	-273

Common threads

UNF-Thread	SAE-Thread	Outer diameter (max. mm)	Internal diameter (min. mm)	Lodes per inch	Increment (mm)
7/16″–20	1/4″	11.079	9.738	20	1.270
1/2″-20	5/16	12.667	11.328	20	1.270
5/8″–18	3/8″	15.839	14.348	18	1.411
3/4″-16	1/2″	19.012	17.330	16	1.588
7/8″–14		22.184	20.262	14	1.814
7/8″–14	5/8″	22.184	20.262	14	1.814
1″-14	3/4″	25.357	23.437	14	1.814
11/16″–14		26.947	25.024	14	1.814
11/8″-12		28.529	26.284	12	2.117
11/4″–12	7/8″	31.704	29.459	12	2.117
13/8″-12		34.877	32.634	12	2.117
11/2″-12	1″	38.052	35.809	12	2.117

ROTHENBERGER

Imprint

This catalog is a publication of

ROTHENBERGER Werkzeuge GmbH

Industriestraße 7 65779 Kelkheim (Taunus) Germany Phone +49 6195 800 - 0

Fax +49 6195 800 - 0 info@rothenberger.com

Company register and number: Königstein im Taunus, HRB 2732

Great care was taken in compiling this catalog and reproduction of the product information. Nevertheless we cannot completely exclude the possibility of error. For this reason, ROTHENBERGER disclaims any liability for any errors which may have arisen despite careful checking of the contents.

The design, compilations, performance data, features, dimensions and weight of products can alter as a result of further technical developments and adaptation of our products to the requirements and wishes of our customers, without any duty on our part to announce this in advance.

We are not obliged to alter already delivered products to match such new developments. We also reserve the right to remove articles from our product program.

This catalog invalidates all previous versions. Standard specifications are non-binding. The operating instructions and suggestions for use and safety are non-binding and do not in any way replace legal or other regulations, such as employer's liability insurance association regulations, in the respective countries.

No part of this catalog may be reproduced in any way whether by reprinting, photocopying, putting onto microfilm or any other process, or be converted into a machine-readable language or stored in any electronic systems and processed there without prior written permission from ROTHENBERGER Werkzeuge GmbH.

It is not permitted to make any changes and additions to the catalog. We reserve all rights for all countries.

© 2025 ROTHENBERGER Werkzeuge GmbH, Germany

ROTHENBERGER worldwide

Australia ROTHENBERGER Australia Pty. Ltd.

Unit 6/13 Hoyle Avenue Castle Hill NSW 2154 Australia Phone: +61 2 9899 7577 sales-au@rothenberger.com rothenberger.com.au

ROTHENBERGER Werkzeuge und Maschinen Austria

Handelsgesellschaft mbH

Gewerbeparkstraße 9, 5081 Anif, Austria

Phone: +43 6246 72091 - 250, Fax: +43 6246 72091 - 215

office@rothenberger.at rothenberger.com/at-de

Belgium ROTHENBERGER Benelux by

Antwerpsesteenweg 59, 2630 Aartselaar, Belgium

Phone: +32 3 877 22 77 sales-be@rothenberger.com

rothenberger.be

Brazil

ROTHENBERGER do Brasil LTDA Avenida Fagundes de Oliveira, 538 Galpão A4, Piraporinha, Diadema, Sao Paulo, Brazil Phone: +55 11 4044 4748

contato-br@rothenberger.com rothenberger.com.br

ROTHENBERGER Bulgaria EOOD Bulgaria

Blvd. Sitnjakovo 79, BG-1111 Sofia, Bulgaria

Phone: +359 2 946 14 59 info@rothenberger.bg rothenberger.com/bg-bg

China

ROTHENBERGER (Wuxi) Pipe Technologies Co., Ltd Building D, No 9 Lianhe Road Hudai Industrial Park, 214161 Wuxi, Jiangsu, China Phone: 00886-0510-85516011

info@rothenberger.cn

Czech Republic **ROTHENBERGER CZ**

Prumyslova 1306/7, 102 00 Praha 10, Czech Republic

Phone: +420 271 730 183 prodej@rothenberger.com rothenberger.cz

ROTHENBERGER France

39 Quai de Marne, F-51206, Épernay, Cedex, France Phone: +33 3 87 74 92 92

info-fr@rothenberger.com rothenberger.fr

ROTHENBERGER Deutschland GmbH Germany

Industriestraße 7, 65779 Kelkheim (Taunus), Germany Phone: +49 6195 800 - 0, Fax: +49 6195 800 - 3500 verkauf-deutschland@rothenberger.com

rothenberger.com

Greece ROTHENBERGER Hellas S.A.

Head Office: 5 Amfitheas Av., 17122 N. Smyrni, Greece Warehouse: 45 Agias Kyriakis Str., 17564 P. Faliro, Greece Phone: +30 21 09 40 20 49, +30 21 09 40 73 02-3

Fax: +30 21 09 40 73 22 ro-he@otenet.gr rothenberger.com

ROTHENBERGER Szerszám és Gép Kereskedelmi Kft, Hungary

Gubacsi út 24, H-1097 Budapest, Hungary Phone: +36 1 3 47 50 40

info-hu@rothenberger.com rothenberger.hu

ROTHENBERGER India Pvt. Ltd. India

Office No. 06, Rama Palace, Phase II Sector 20B, Faridabad, Haryana – 121003

Phone: +91 9910152019 https://rothenberger.com/in-en

Italy ROTHENBERGER Italiana s.r.l.

Via G. Reiss Romoli 17–19, I-20019 Settimo Milanese, Italy Phone: +39 02 33 50 601 rothenberger.italia@rothenberger.com

rothenberger.it

Netherlands ROTHENBERGER Nederland by

Postbus 45, NL-5120 AA Rijen, Netherlands Phone: +31 1 61 29 35 79

sales-nl@rothenberger.com rothenberger.nl

Poland ROTHENBERGER Polska Sp. z o.o.

Ul. Annopol 4A, Hala C, PL-03-236 Warszawa, Poland

Phone: +48 22 213 59 00 biuro@rothenberger.pl rothenberger.pl

ROTHENBERGER WERKZEUGE GmbH Sweden

Sales Office Nordio SE-171 26 Solna, Sweden Visiting address:

Hemvärnsgatan 22, Solna, Sweden Phone: +46 8 629 2299 roscan@rothenberger.com

South Africa ROTHENBERGER TOOLS SA (Ptv) Ltd

P.O. Box 4360, Edenvale 1610

165 Van Der Bijl Street, Meadowdale Germiston Gauteng (Johannesburg), South Africa Phone: +27 11 372 9631, Fax: +27 11 372 9632

info@rothenberger.co.za rothenberger.com/za-en

Spain / Portugal ROTHENBERGER Werkzeuge GmbH

Ctra. Durango-Elorrio, Km. 2,

48220 Abadiano (Vizcaya), Spain Phone: +34 94 621 01 00, Fax: +34 94 621 01 02

ventas@rothenberger.com

rothenberger.es

ROTHENBERGER (Schweiz) AG Switzerland

Herostr. 9, CH-8048 Zürich, Switzerland

Phone: +41 44 435 30 30 info@rothenberger-werkzeuge.ch

ROTHENBERGER Türkiye Turkey

ROTHENBERGER Center, Barbaros Bulvarı No:9 TR-34775 Şerifali / Ümraniye İstanbul, Turkey Phone: +90 216 449 24 85, Fax: +90 216 449 24 87

rothenberger@rothenberger.com.tr

rothenberger.com.tr

UAE ROTHENBERGER Middle East FZCO

PO Box 261190, Jebel Ali Free Zone Dubai, United Arab Emirates Phone: +971 4 883 97 77, Fax: +971 4 883 97 57

office-ae@rothenberger.com

ROTHENBERGER Middle East Equipment Trading LLC

PO Box 261190, Al Quoz Industrial Area 3

Dubai, United Arab Emirates

Phone: +971 4 885 48 65, Fax: +971 4 883 97 57 servicecenter-ae@rothenberger.com

ROTHENBERGER UK Ltd. UK

2, Kingsthorne Park, Henson Way Kettering, GB-Northants NN16 8PX, UK

Phone: +44 15 36 31 03 00, Fax: +44 15 36 31 06 00

sales@rothenberger.co.uk rothenberger.com/gb-en/

USA ROTHENBERGER USA Inc.

7130 Clinton Road, Loves Park, IL 61111, USA Phone: +1 80 05 45 76 98, Fax: +1 81 56 33 08 79 customerservice-us@rothenberger.com

rothenberger.com/us-en

ROTHENBERGER Partners

Romania ROWALT S.R.L.

Strada 1 Mai, nr. 4, Otopeni, Ilfov, 075100, Romania

Phone: +40 21 350 37 44/45/46 info@rothenberger-romania.ro rothenberger.com/ro-ro

Ukraine ROTHENBERGER-CENTER LTD.

Salskoho str. 11, Kyiv, 04060, Ukraine Phone: +380 444941597

info@rothenberger.com.ua





ROTHENBERGER Werkzeuge GmbH

Industriestraße 7 65779 Kelkheim (Taunus) Germany

Phone +49 6195 800 - 0 Fax +49 6195 800 - 3500 info@rothenberger.com