

# Anwendungstabelle für **Stufenbohrer**

Größe Nr.	Bohrbereiche mm													
0/5	Für metrische Lochmaße													
	Ø 4,0	Ø 6,0	Ø 8,0	Ø 10,0	Ø 12,0									
0/9	Für metrische Lochmaße													
	Ø 4,0	Ø 5,0	Ø 6,0	Ø 7,0	Ø 8,0	Ø 9,0	Ø 10,0	Ø 11,0	Ø 12,0					
1	Für metrische Lochmaße													
	Ø 4,0	Ø 6,0	Ø 8,0	Ø 10,0	Ø 12,0	Ø 14,0	Ø 16,0	Ø 18,0	Ø 20,0					
2	Für metrische Lochmaße													
	Ø 4,0	Ø 6,0	Ø 8,0	Ø 10,0	Ø 12,0	Ø 14,0	Ø 16,0	Ø 18,0	Ø 20,0	Ø 22,0	Ø 24,0	Ø 26,0	Ø 28,0	Ø 30,0
3	Für metrische Lochmaße													
	Ø 6,0	Ø 9,0	Ø 13,0	Ø 16,0	Ø 19,0	Ø 21,0	Ø 23,0	Ø 26,0	Ø 29,0	Ø 32,0	Ø 35,0	Ø 38,0		
4	Für Panzerrohrgewinde Kernlochmaße													
	PG 7 / Ø 11,4	PG 9 / Ø 14,0	PG 11 / Ø 17,25	PG 13,5 / Ø 19,0	PG 16 / Ø 21,25	PG 21 / Ø 26,75								
5	Für metrische Lochmaße													
	Ø 4,0	Ø 6,0	Ø 9,0	Ø 12,0	Ø 15,0	Ø 18,0	Ø 21,0	Ø 24,0	Ø 27,0	Ø 30,0	Ø 33,0	Ø 36,0	Ø 39,0	
6	Für Rohrgewinde Außen-Ø Durchgangsmaße													
	R 1/8" / Ø 11,2	R 1/4" / 14,5	R 3/8" / Ø 18,2	R 1/2" / Ø 22,3	R 3/4" / Ø 27,9									
7	Für Rohrgewinde Kernlochmaße													
	G 1/8" / Ø 8,8	G 1/4" / 11,8	G 3/8" / Ø 15,3	G 1/2" / Ø 19,0	G 3/4" / Ø 24,5									
8	Für Panzerrohrgewinde Durchgangsmaße													
	PG 7 / Ø 12,5	PG 9 / Ø 15,2	PG 11 / Ø 18,6	PG 13,5 / Ø 20,4	PG 16 / Ø 22,5	PG 21 / Ø 28,3								
9	Für Panzerrohrgewinde Durchgangsmaße													
	PG 7 / Ø 12,5	PG 9 / Ø 15,2	PG 11 / Ø 18,6	PG 13,5 / Ø 20,4	PG 16 / Ø 22,5	PG 21 / Ø 28,3	PG 29 / Ø 37,0							
10	Für Blindnietmuttern M3 - M4 - M5 - M6 - M8													
	Ø 4,8	Ø 6,4	Ø 7,2	Ø 9,6	Ø 10,65									
11	Für metrische Lochmaße mit extra hohen Stufen													
	Ø 6,0	Ø 9,0	Ø 12,0	Ø 16,0	Ø 20,0	Ø 22,5	Ø 25,0							
12	Für metrische Lochmaße mit extra hohen Stufen													
	Ø 6,0	Ø 9,0	Ø 12,0	Ø 16,0	Ø 20,0	Ø 22,5	Ø 25,0	Ø 28,5	Ø 32,0					
13	Für metrische Lochmaße und großen Durchmessern													
	Ø 6,0	Ø 11,0	Ø 17,0	Ø 23,0	Ø 29,0	Ø 30,0	Ø 31,0	Ø 32,0	Ø 33,0	Ø 34,0	Ø 35,0	Ø 36,0	Ø 37,0	Ø 38,0
	Ø 39,0	Ø 40,0												
14	Für metrische Kabelverschraubungen, Kernlochmaße nach DIN/EN 60423													
	M 6	M 8	M 10	M 12	M 16	M 20	M 25	M 32						
	Ø 5,3	Ø 7,0	Ø 9,0	Ø 10,5	Ø 14,5	Ø 18,5	Ø 23,5	Ø 30,5						
15	Für metrische Kabelverschraubungen, Durchgangsmaße nach DIN/EN 50262													
	M 6	M 8	M 10	M 12	M 16	M 20	M 25	M 32						
	Ø 6,5	Ø 8,5	Ø 10,5	Ø 12,5	Ø 16,5	Ø 20,5	Ø 25,5	Ø 32,5						
16	Für metrische Kabelverschraubungen, Kernlochmaße nach DIN/EN 60423													
	M 6	M 8	M 10	M 12	M 16	M 20	M 25	M 32	M 40					
	Ø 5,3	Ø 7,0	Ø 9,0	Ø 10,5	Ø 14,5	Ø 18,5	Ø 23,5	Ø 30,5	Ø 38,5					
17	Für metrische Kabelverschraubungen, Durchgangsmaße nach DIN/EN 50262													
	M 6	M 8	M 10	M 12	M 16	M 20	M 25	M 32	M 40					
	Ø 6,5	Ø 8,5	Ø 10,5	Ø 12,5	Ø 16,5	Ø 20,5	Ø 25,5	Ø 32,5	Ø 40,5					
18	Für metrische Kabelverschraubungen / Panzerrohrgewinde, Durchgangsmaße													
	M 6	M 8	M 10	M 12 / PG 7	PG 9	M 16	PG 11	M 20 / PG 13,5	PG 16	M 25	PG 21	M 32		
	Ø 6,5	Ø 8,5	Ø 10,5	Ø 12,7	Ø 15,7	Ø 16,2	Ø 18,6	Ø 20,4	Ø 22,5	Ø 25,5	Ø 28,3	Ø 32,5		

