



# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)  
Issue date: 7/30/2025 Version: 1.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : AcryGel

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Nail Care  
Restrictions on use : None known

#### 1.4. Supplier's details

V Beauty Pure  
2257 Vista Parkway  
Ste 23  
West Palm Beach, Florida 33411  
T 888-390-4259  
[regulatory@vbeautypure.com](mailto:regulatory@vbeautypure.com)

#### 1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)  
CCN 854185  
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

### SECTION 2 Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Acute toxicity (inhalation:dust,mist), Category 4	H332	Harmful if inhaled.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (respiratory system) through prolonged or repeated exposure.

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H351 - Suspected of causing cancer.

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Precautionary statements (GHS US)

- H373 - May cause damage to organs (respiratory system) through prolonged or repeated exposure
- : Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust, fume, gas, mist, vapors, spray.
- Wash hands, forearms and face thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
- If on skin: Wash with plenty of water.
- If skin irritation or rash occurs: Get medical advice or attention.
- Take off contaminated clothing and wash it before reuse.
- If inhaled: Remove person to fresh air and keep comfortable for breathing.
- Call a poison center or doctor if you feel unwell.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice or attention.
- If exposed or concerned: Get medical advice/attention.
- Store locked up.
- Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acrylates Copolymer	CAS-No.: 25212-88-8	60 – 70	Acute Tox. 4 (Inhalation:dust,mist), H332
Hydroxypropyl methacrylate	CAS-No.: 27813-02-1	≤ 15	Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 3, H402
[ethoxy(phenyl)phosphoryl]-(2,4,6-trimethylphenyl)methanone	CAS-No.: 84434-11-7	1 – 5	Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Eosin	CAS-No.: 17372-87-1	≤ 3	Eye Irrit. 2, H319
Iron oxide	CAS-No.: 1309-37-1	≤ 3	STOT RE 2, H373 Aquatic Chronic 3, H412
Titanium dioxide	CAS-No.: 13463-67-7	≤ 3	Carc. 2, H351

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Name	Product identifier	%	GHS US classification
Aluminum	CAS-No.: 7429-90-5	≤ 3	Flam. Sol. 1, H228 Water-react. 2, H261 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled.
Symptoms/effects after skin contact	: May cause irritation to skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.
Chronic symptoms	: Suspected of causing cancer. May cause damage to organs (respiratory system) through prolonged or repeated exposure.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: IF exposed or concerned: Get medical advice/attention.
-----------------------------------	--

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Use extinguishing media appropriate for surrounding fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

- |                      |   |  |
|----------------------|---|--|
| Protective equipment | : | Wear recommended personal protective equipment.  |
| Emergency procedures | : | Evacuate the danger area. If outdoors, move to an area upwind of the danger area. If possible without taking personal risks, Remove ignition sources, ventilate area. Avoid breathing gas, vapors, mist, and spray. Avoid contact with skin and eyes. Prevent other non-emergency personnel from entering the danger area. |

##### For emergency responders

- |                           |   |   |
|---------------------------|---|---|
| Protective equipment      | : | Wear the recommended personal protective equipment.                                     |
| Emergency procedures      | : | Evacuate personnel to a safe area. Ventilate spillage area. Stop leak if safe to do so. |
| Environmental precautions | : | Do not let the product reach soil, drains, sewers, or surface and ground water.         |

#### 6.2. Methods and materials for containment and cleaning up

- |                         |   |  |
|-------------------------|---|--|
| For containment         | : | Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  |
| Methods for cleaning up | : | Take up in non-combustible inert absorbent and place into container for disposal. Decontaminate surfaces and equipment with water and detergent. Contaminated absorbent material may pose the same hazard as the spilled product. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations. |

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

- |                               |   |  |
|-------------------------------|---|--|
| Precautions for safe handling | : | Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid breathing mist, spray, vapors, gas. Take precautionary measures against static discharge. |
| Hygiene measures              | : | Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace.   |

#### 7.2. Conditions for safe storage, including incompatibilities

- |                       |   |   |
|-----------------------|---|---|
| Storage conditions    | : | Keep away from heat, sparks, and flame. Protect from sunlight. Store in a well-ventilated place. Keep cool. |
| Incompatible products | : | Alkalis. Peroxides. Strong acids. Strong oxidizers.   |
| Storage temperature   | : | ≤ 50 °C / 122 °F  |

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

##### Iron oxide (1309-37-1)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Iron oxide (Fe <sub>2</sub> O <sub>3</sub> )
------------	--

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Iron oxide (1309-37-1)	
ACGIH® TLV® TWA	5 mg/m³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulmonary siderosis. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Iron oxide fume
OSHA PEL TWA	10 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Titanium dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH® TLV® TWA	0.2 mg/m³ (Nanoscale particles. R - Respirable particulate matter) 2.5 mg/m³ (Finescale particles. R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
NIOSH REL 10h TWA	2.4 mg/m³ (fine) 0.3 mg/m³ (ultrafine)
Remark (NIOSH)	Ca = Potential occupational carcinogens (ultrafine particles)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Aluminum (7429-90-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Aluminum, metal and insoluble compounds
ACGIH® TLV® TWA	1 mg/m³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Aluminum Metal (as Al)
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### Aluminum (7429-90-5)

#### USA - NIOSH - Occupational Exposure Limits

Local name	Aluminum Metal (as Al)
NIOSH REL 10h TWA	10 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

#### Hand protection:

Handling product in bulk: Wear nitrile or other impervious gloves if skin contact is possible. When the material is dissolved or suspended in an organic solvent, wear gloves that provide protection against the solvent.

#### Eye protection:

Chemical goggles or safety glasses. Wear safety glasses which protect from splashes

#### Skin and body protection:

Body protection should be chosen depending on activity and possible exposure. Handling product in bulk: Wear protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Use NIOSH approved respirator if ventilation is inadequate. SCBA for emergency responders. Must be used in accordance with an OSHA complaint respiratory protection program.

#### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Various colors
Odor	: Acrylic-like
Odor threshold	: No data available
pH	: 6 – 7
Melting point	: No data available
Freezing point	: No data available

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Boiling point	: No data available
Flash point	: > 100 °C / 212 °F
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1 – 1.2 g/cm <sup>3</sup>
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Incompatible materials.

### 10.5. Incompatible materials

Alkalis. Peroxides. Strong acids. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon dioxide. Carbon monoxide. Nitrogen oxides.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

#### Acrylates Copolymer

LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 Inhalation - Rat (Dust/Mist)	5 mg/l/4h

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Hydroxypropyl methacrylate</b>	
LD50 oral rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
<b>[ethoxy(phenyl)phosphoryl]-(2,4,6-trimethylphenyl)methanone</b>	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight
<b>Eosin</b>	
LD50 oral rat	> 2000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight
<b>Iron oxide</b>	
LD50 oral	> 5000 mg/kg body weight
<b>Titanium dioxide</b>	
LD50 oral rat	> 5000 mg/kg body weight
<b>Aluminum</b>	
LD50 oral rat	> 15900 mg/kg body weight
LC50 Inhalation - Rat	> 0.888 mg/l air
Skin corrosion/irritation	: Not classified pH: 6 – 7
<b>Acrylates Copolymer</b>	
Additional information	Not irritating to rabbits on cutaneous application
<b>Eosin</b>	
pH	6.55 Temp.: 29 °C Concentration: 1 other:
Serious eye damage/irritation	: Causes serious eye irritation. pH: 6 – 7
<b>Acrylates Copolymer</b>	
Additional information	Not irritating to rabbits on ocular application
<b>Eosin</b>	
pH	6.55 Temp.: 29 °C Concentration: 1 other:
Respiratory or skin sensitization	: May cause an allergic skin reaction.
<b>Acrylates Copolymer</b>	
Additional information	No sensitizing reaction was observed for guinea pigs
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
<b>Iron oxide</b>	
IARC group	3 - Not classifiable



# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Titanium dioxide	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

Eosin	
NOAEL (animal/female, F0/P)	1500 mg/kg body weight (rat)
NOAEL (animal/female, F1)	1500 mg/kg body weight (rat)

Aluminum	
NOAEL (animal/male, F0/P)	1000 mg/kg body weight

STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs (respiratory system) through prolonged or repeated exposure.

Hydroxypropyl methacrylate	
LOAEC (inhalation, rat, gas, 90 days)	350 ppm
NOAEL (oral, rat, 90 days)	300 mg/kg body weight
NOAEC (inhalation, rat, gas, 90 days)	100 ppm

Eosin	
NOAEL (oral, rat, 90 days)	1500 mg/kg body weight (rat)

Iron oxide	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.2102 mg/l air
NOAEL (oral, rat, 90 days)	> 1000 mg/kg body weight
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.03 mg/l air
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure.

Aluminum	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.05 mg/l air
NOAEL (subchronic, oral, animal/male, 90 days)	1034 mg/kg body weight
NOAEL (subchronic, oral, animal/female, 90 days)	1087 mg/kg body weight

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Harmful if inhaled.

Symptoms/effects after skin contact : May cause irritation to skin. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Stinging, redness, itching, tears, blurred vision, swelling.

Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

Chronic symptoms : Suspected of causing cancer. May cause damage to organs (respiratory system) through prolonged or repeated exposure.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hydroxypropyl methacrylate	
EC50 - Crustacea [1]	> 143 mg/l
EC50 72h - Algae [1]	> 97.2 mg/l
NOEC (chronic)	45.2 mg/l
[ethoxy(phenyl)phosphoryl]-(2,4,6-trimethylphenyl)methanone	
LC50 - Fish [1]	1.89 mg/l
EC50 - Crustacea [1]	2.26 mg/l
EC50 72h - Algae [1]	1.01 mg/l
EC50 72h - Algae [2]	0.239 mg/l
Eosin	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
EC50 72h - Algae [1]	51.3 mg/l
Iron oxide	
EC50 - Crustacea [1]	> 100 mg/l
EC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 72h - Algae [1]	> 20 mg/l
Titanium dioxide	
EC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
LOEC (chronic)	5 mg/l
Aluminum	
EC50 72h - Algae [1]	1.05 mg/l
EC50 72h - Algae [2]	0.2 mg/l

### 12.2. Persistence and degradability

AcryGel	
Persistence and degradability	Not established.
Acrylates Copolymer	
Persistence and degradability	Not rapidly degradable
Hydroxypropyl methacrylate	
Persistence and degradability	Not rapidly degradable
[ethoxy(phenyl)phosphoryl]-(2,4,6-trimethylphenyl)methanone	
Persistence and degradability	Not rapidly degradable
Eosin	
Persistence and degradability	Not rapidly degradable

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Iron oxide	
Persistence and degradability	Not rapidly degradable
Titanium dioxide	
Persistence and degradability	Not rapidly degradable
Aluminum	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

AcryGel	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

## SECTION 13 Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Refer to all applicable national, international and local regulations or provisions.
Additional information	: Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.

## SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. Proper Shipping Name		
Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated
14.4. Packing group		
Not regulated	Not regulated	Not regulated
14.5. Environmental hazards		
	Not regulated	
No supplementary information available		

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

#### DOT

Not regulated

#### IMDG

Not regulated

#### IATA

Not regulated

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

[ethoxy(phenyl)phosphoryl]-(2,4,6-trimethylphenyl)methanone	CAS-No. 84434-11-7	1 – 5%
Silica	CAS-No. 112945-52-5	5 – 10%
Eosin	CAS-No. 17372-87-1	≤ 3%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum	CAS-No. 7429-90-5	≤ 3%
----------	-------------------	------

### 15.2. International regulations

#### CANADA

##### Acrylates Copolymer (25212-88-8)

Listed on the Canadian DSL (Domestic Substances List)

##### Hydroxypropyl methacrylate (27813-02-1)

Listed on the Canadian DSL (Domestic Substances List)

##### [ethoxy(phenyl)phosphoryl]-(2,4,6-trimethylphenyl)methanone (84434-11-7)

Listed on the Canadian DSL (Domestic Substances List)

##### Iron oxide (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List)

##### Titanium dioxide

Listed on the Canadian DSL (Domestic Substances List)

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Aluminum (7429-90-5)</b>
Listed on the Canadian DSL (Domestic Substances List)

**EU-Regulations**

No additional information available

**National regulations**

<b>Acrylates Copolymer (25212-88-8)</b>
Listed on INSQ (Mexican National Inventory of Chemical Substances)


<b>Hydroxypropyl methacrylate (27813-02-1)</b>
Listed on INSQ (Mexican National Inventory of Chemical Substances)

<b>Iron oxide (1309-37-1)</b>
Listed on INSQ (Mexican National Inventory of Chemical Substances)

<b>Titanium dioxide</b>
Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

<b>Aluminum (7429-90-5)</b>
Listed on INSQ (Mexican National Inventory of Chemical Substances)

**15.3. State regulations**

 **WARNING:**

This product can expose you to Titanium dioxide (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
Iron oxide(1309-37-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Aluminum(7429-90-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

**SECTION 16 Other information**

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)  
Issue date : 7/30/2025

<b>Full text of hazard classes and H-statements</b>	
H228	Flammable solid

# AcryGel

## Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H261	In contact with water releases flammable gas
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.