

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 12/20/2024 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Trade name : Nail Prep Dehydrator

1.2. Other means of identification

No additional information available.

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Nail glue for artificial nails

1.4. Supplier's details

V Beauty Pure 2257 Vista Parkway Ste 23

West Palm Beach, Florida 33411

T 888-390-4259

regulatory@vbeautypure.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)

CCN 854185

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2

H225

Highly flammable liquid and vapor.

Serious eye damage/eye irritation, Category 2A

H319

Causes serious eye irritation.

Specific target organ toxicity – Single exposure, Category 3, Narcosis

H336

May cause drowsiness or dizziness.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Dange

Hazard statements (GHS US)

: Highly flammable liquid and vapor Causes serious eye irritation

May cause drowsiness or dizziness

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No

smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof equipment.

Avoid breathing fume, mist, spray, vapours.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Wash hands, forearms and face thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

In case of fire: Use Dry chemical, CO2, alcohol-resistant foam or waterspray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available.

2.4. Hazards not otherwise classified

No additional information available.

2.5. Unknown acute toxicity

No additional information available.

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Propan-2-ol	CAS-No.: 67-63-0	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Ethyl acetate	CAS-No.: 141-78-6	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Isobutyl acetate	CAS-No.: 110-19-0	15 – 35	Flam. Liq. 2, H225 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general

: First aider: Pay attention to self-protection. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth. Call a poison center/doctor/physician if you feel unwell.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by

warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that

vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Most Important Symptoms/Effects : Causes serious eye irritation. Vapors may cause drowsiness and dizziness.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical, CO2, dry sand, or alcohol-resistant foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : Vapors are heavier than air and may travel considerable distance to an ignition source and flash

back to source of vapors. Heat may build pressure, rupturing closed containers, spreading fire

and increasing risk of burns and injuries.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of

explosion. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers. Use extinguishing media appropriate for

surrounding fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Avoid all personal contact including breathing in gas, vapors, mist, and spray.

Avoid contact with eyes, skin and clothing. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters

sewers or public waters.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

12/20/2024 (Issue date) US - en 3/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Avoid

breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes. If possible without taking personal risks, remove ignition sources, ventilate area. No open flames, no sparks, and no

smoking. Prevent other non-emergency personnel from entering the danger area.

For emergency responders

Protective equipment : Wear the recommended personal protective equipment. Do not attempt to take action without

suitable protective equipment. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Stop leak if safe to do so.

Environmental precautions : Do not let the product reach soil, drains, sewers, or surface and ground water.

6.2. Methods and materials for containment and cleaning up

For containment : Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Absorb spilled material with sand or earth.

Stop leak, if possible without risk.

Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated

absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Notify authorities if product enters sewers or public waters. Dispose of collected material as soon as possible in accordance

with applicable local/regional/national/international regulations.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Wear personal protective equipment. Avoid

contact with skin and eyes. Avoid breathing fume, gas, mist, spray, vapors. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures

against static discharge. Flammable vapors may accumulate in the container.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

Additional hazards when processed : Proper grounding procedures to avoid static electricity should be followed.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store in a cool, dry and well-ventilated area away from incompatible substances. Protect from

sunlight. Keep container closed when not in use.

Incompatible products : Alkali metals. Strong oxidizers.

Heat-ignition : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Propan-2-ol (67-63-0)

USA - ACGIH - Occupational Exposure Limits

Local name 2-Propanol

12/20/2024 (Issue date) US - en 4/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propan-2-ol (67-63-0)	
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	2-Propanol
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL TWA	980 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Ethyl acetate (141-78-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH OEL TWA	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl acetate
OSHA PEL TWA	1400 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Isobutyl Acetate (110-19-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Isobutyl acetate
ACGIH OEL TWA	50 ppm
ACGIH OEL STEL	150 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Isobutyl acetate
OSHA PEL TWA	700 mg/m³
	1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isobutyl Acetate (110-19-0)	
	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity

of any potential exposure.

Environmental exposure controls : Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Materials for protective clothing:

Wear fire/flame resistant/retardant clothing.

Hand protection:

Handling product in bulk: Wear protective gloves

Eye protection:

Handling product in bulk: Chemical goggles or safety glasses

Skin and body protection:

Handling product in bulk: Long sleeved protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Self-contained breathing apparatus

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

: Liquid Physical state : Clear. Appearance Color Colorless Odor : Characteristic Odor threshold : No data available : No data available На : No data available Melting point Freezing point : No data available

Boiling point : $\geq 77 - \leq 78 \, ^{\circ}\text{C} / \geq 170.6 - \leq 172.4 \, ^{\circ}\text{F}$

Flash point : ≥ 1 °C / ≥-33.8 °F Flammability (solid, gas) : Not applicable.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure : \leq 76 hPa / \leq 57 mm Hg Relative vapor density at 20°C : No data available Relative density : No data available

Density : 0.8489 g/cm³ @ 20 °C / 68 °F (7.0841 lbs/gal) Solubility : Not miscible in water or difficult to mix.

Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : No data available

Explosion limits : Lower explosion limit: ≥ 2 vol %

Upper explosion limit: ≤ 12 vol %

Explosive properties : Explosive vapor/air mixtures may be formed.

Particle characteristics : No data available

Propan-2-ol

Particle characteristics No data available

Ethyl acetate

Particle characteristics No data available

Isobutyl Acetate

Particle characteristics No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 100 %

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Incompatible materials.

10.5. Incompatible materials

Alkali metals. Strong oxidizers.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon dioxide. Carbon monoxide.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11 Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Propan-2-ol		
LD50 oral rat	5840 mg/kg body weight	
Ethyl acetate		
LD50 oral	4934 mg/kg body weight	
LD50 dermal rabbit	> 20000 mg/kg body weight	
LC50 Inhalation - Rat	4000 mg/l	
Isobutyl Acetate		
LD50 oral rat	13413 mg/kg	
LD50 oral	13400 mg/kg	
LD50 dermal rabbit	> 17400 mg/kg	
LD50 dermal	17400 mg/kg	
LC50 Inhalation - Rat	> 23.4 mg/l air	
LC50 Inhalation - Rat (Dust/Mist)	21.3 mg/l/4h	

Skin corrosion/irritation : Not classified

Ethyl acetate

LC50 Inhalation - Rat (Vapours)

Skin corrosion/irritation, rabbit Negative, Mildly irritating

Serious eye damage/irritation : Causes serious eye irritation.

30 mg/l

Ethyl acetate

Serious eye damage/irritation, rabbit Severely irritating to the eyes

Respiratory or skin sensitization : Not classified

Ethyl acetate

Guinea pig maximization test Not sensitive

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Propan-2-ol

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

Propan-2-ol

STOT-single exposure May cause drowsiness or dizziness.

12/20/2024 (Issue date) US - en 8/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethyl acetate	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Ethyl acetate	
LOAEL (oral,rat,90 days)	3600 mg/kg body weight
NOAEL (oral,rat,90 days)	900 mg/kg body weight
Isobutyl Acetate	
NOAEL (oral,rat,90 days)	316 mg/kg body weight
Aspiration hazard	: Not classified
Nail Prep Dehydrator	
Viscosity, kinematic	No data available
Propan-2-ol	
Viscosity, kinematic	No data available
Ethyl acetate	
Viscosity, kinematic	No data available
Isobutyl Acetate	
Viscosity, kinematic	0.803 mm²/s
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Most Important Symptoms/Effects	: Causes serious eye irritation. Vapors may cause drowsiness and dizziness.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

Hazardous to the aquatic environment, long-term

(chronic)

: Harmful to aquatic life with long lasting effects

Propan-2-ol		
LC50 - Fish [1]	10000 mg/l	
LC50 - Fish [2]	9640 mg/l	
Ethyl acetate		
LC50 - Fish [1]	230 mg/l	
NOEC (chronic)	2.4 mg/l	
Isobutyl Acetate		
LC50 - Fish [1]	17 mg/l	
EC50 - Crustacea [1]	26.8 mg/l	

12/20/2024 (Issue date) US - en 9/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isobutyl Acetate	
EC50 72h - Algae [1]	397 mg/l
EC50 72h - Algae [2]	246 mg/l
ErC50 algae	397 mg/l
LOEC (chronic)	47.6 mg/l
NOEC (chronic)	23.2 mg/l
NOEC chronic algae	23 mg/l

12.2. Persistence and degradability

Nail Prep Dehydrator		
Persistence and degradability	Not rapidly degradable	
Propan-2-ol		
Persistence and degradability	Not rapidly degradable	
Ethyl acetate		
Persistence and degradability	% biodegradation .	
Isobutyl Acetate		
Persistence and degradability	Not rapidly degradable	

12.3. Bioaccumulative potential

Ethyl acetate	
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. U.S. - RCRA (Resource Conservation Recovery

Act) - D Waste- Characteristic Waste Codes. D001: IGNITABLE WASTE.

Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.

Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

12/20/2024 (Issue date) US - en 10/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	IMDG	IATA
14.1. UN number		
UN1987	1987	1987
14.2. Proper Shipping Name		
Alcohols, n.o.s. (Contains Isopropyl Alcohol, Ethyl Acetate and Isobutyl Acetate)	ALCOHOLS, N.O.S. (Contains Isopropyl Alcohol, Ethyl Acetate and Isobutyl Acetate)	Alcohols, n.o.s. (Contains Isopropyl Alcohol, Ethyl Acetate and Isobutyl Acetate)
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
	Marine pollutant: No	
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No.(DOT) : UN1987 DOT Packaging Exceptions (49 CFR 173.xxx) : 4b:150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242 DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

IMDG

Special provision (IMDG) : 274 Limited quantities (IMDG) : 1L Excepted quantities (IMDG) : E2 : P001 Packing instructions (IMDG) : IBC02 IBC packing instructions (IMDG) Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP1, TP8, TP28

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS EmS-No. (Spillage)

Stowage category (IMDG) : B

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353

12/20/2024 (Issue date) US - en 11/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Propan-2-ol CAS-No. 67-63-0 25 – 50%

Ethyl acetate (141-78-6)

CERCLA RQ 5000 lb

Isobutyl Acetate (110-19-0)

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

Propan-2-ol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl acetate (141-78-6)

Listed on the Canadian DSL (Domestic Substances List)

Isobutyl Acetate (110-19-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available.

National regulations

Propan-2-ol (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Ethyl acetate (141-78-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Isobutyl Acetate (110-19-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date : 12/20/2024

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.