



Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 12/20/2024 Revision date: 7/30/2025 Supersedes: 12/20/2024 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Builder Gel

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Nail Care
Restrictions on use : All other uses not recommended above

1.4. Supplier's details

V Beauty Pure
2257 Vista Parkway
Ste 23
West Palm Beach, Florida 33411
T 888-390-4259
regulatory@vbeautypure.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 854185
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411	Toxic to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Precautionary statements (GHS US)	H319 - Causes serious eye irritation H335 - May cause respiratory irritation H351 - Suspected of causing cancer. H360 - May damage fertility or the unborn child H411 - Toxic to aquatic life with long lasting effects
	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist, vapors, spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If exposed or concerned: Get medical advice/attention. Collect spillage. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Bis-Hydroxyethyl Methacrylate Poly (Neopentyl Glycol Adipate)/IPDI Copolymer	CAS-No.: 82339-16-0	20 – 60	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Trimethylopropane Trimethacrylate	CAS-No.: 3290-92-4	5 – 20	Aquatic Chronic 2, H411
Tripropyleneglycol diacrylate	CAS-No.: 42978-66-5	5 – 20	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Name	Product identifier	%	GHS US classification
Silica	CAS-No.: 60676-86-0	1 – 8	Not classified
Hydroxycyclohexyl Phenyl Ketone	CAS-No.: 947-19-3	0.1 – 5	Aquatic Chronic 3, H412
Trimethylbenzoyl Diphenylphosphine Oxide	CAS-No.: 75980-60-8	≤ 0.1	Skin Sens. 1B, H317 Repr. 1B, H360 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Titanium dioxide	CAS-No.: 13463-67-7	≤ 0.1	Carc. 2, H351

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation. Prolonged and frequent exposure through inhalation may cause cancer.
Symptoms/effects after skin contact	: May cause irritation to skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.
Most Important Symptoms/Effects	: May cause an allergic skin reaction.
Chronic symptoms	: Suspected of causing cancer. May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: IF exposed or concerned: Get medical advice/attention.
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides.

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|---|
| Firefighting instructions | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Use extinguishing media appropriate for surrounding fire. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : Evacuate area. Avoid all personal contact including breathing in the mist, vapors, spray. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. |
|------------------|---|

For non-emergency personnel

- | | |
|----------------------|--|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. If possible without taking personal risks, Remove ignition sources, ventilate area. Avoid breathing gas, vapors, mist, and spray. Avoid contact with skin and eyes. Prevent other non-emergency personnel from entering the danger area. |

For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Wear the recommended personal protective equipment. |
| Emergency procedures | : Evacuate personnel to a safe area. Ventilate spillage area. Stop leak if safe to do so. |

- | | |
|---------------------------|---|
| Environmental precautions | : Do not let the product reach soil, drains, sewers, or surface and ground water. |
|---------------------------|---|

6.2. Methods and materials for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
| Methods for cleaning up | : Take up in non-combustible inert absorbent and place into container for disposal. Decontaminate surfaces and equipment with water and detergent. Contaminated absorbent material may pose the same hazard as the spilt product. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations. |

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid breathing mist, spray, vapors, gas. Take precautionary measures against static discharge. |
| Hygiene measures | : Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. |

7.2. Conditions for safe storage, including incompatibilities

- | | |
|--------------------|---|
| Storage conditions | : Keep away from heat, sparks, and flame. Protect from sunlight. Store in a well-ventilated place. Keep cool. |
|--------------------|---|

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Incompatible products : Alkalis. Peroxides. Strong acids. Strong oxidizers.
Storage temperature : ≤ 50 °C / 122 °F

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Silica (60676-86-0)

USA - OSHA - Occupational Exposure Limits

Local name	Silica, fused, respirable dust
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formula: (80 mg/m ³ / (%SiO ₂)) for mg/m ³ . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

Titanium dioxide (13463-67-7)

USA - ACGIH - Occupational Exposure Limits

Local name	Titanium dioxide
ACGIH® TLV® TWA	0.2 mg/m ³ (Nanoscale particles. R - Respirable particulate matter) 2.5 mg/m ³ (Finescale particles. R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

USA - OSHA - Occupational Exposure Limits

Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

USA - NIOSH - Occupational Exposure Limits

Local name	Titanium dioxide (Total dust)
NIOSH REL 10h TWA	2.4 mg/m ³ (fine) 0.3 mg/m ³ (ultrafine)
Remark (NIOSH)	Ca = Potential occupational carcinogens (ultrafine particles)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Environmental exposure controls : Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Hand protection:

Handling product in bulk: Wear nitrile or other impervious gloves if skin contact is possible. When the material is dissolved or suspended in an organic solvent, wear gloves that provide protection against the solvent.

Eye protection:

Chemical goggles or safety glasses. Wear safety glasses which protect from splashes

Skin and body protection:

Body protection should be chosen depending on activity and possible exposure. Handling product in bulk: Wear protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed and a NIOSH/MSHA or European Standard EN 149 approved respirator must be used if any of the following situations occur: workplace conditions warrant respirator use, or exposure limits are exceeded or if irritation or other symptoms are experienced

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear or Pigmented.
Color	: According to product specification
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 1500000 cP
Explosion limits	: No data available
Particle characteristics	: No data available

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials.

10.5. Incompatible materials

Alkalis. Peroxides. Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon dioxide. Carbon monoxide. Nitrogen oxides.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Tripropyleneglycol diacrylate

LD50 oral rat	6200 mg/kg
LD50 oral	6800 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	2500 mg/kg

Hydroxycyclohexyl Phenyl Ketone

LD50 oral rat	> 2500 mg/kg body weight
LD50 dermal rat	> 5000 mg/kg body weight
LC50 Inhalation - Rat	> 1 mg/l air

Trimethylbenzoyl Diphenylphosphine Oxide

LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Titanium dioxide	
LD50 oral rat	> 5000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Hydroxycyclohexyl Phenyl Ketone	
pH	5.7
Trimethylbenzoyl Diphenylphosphine Oxide	
Additional information	Not irritating to rabbits on cutaneous application
Serious eye damage/irritation	: Causes serious eye irritation.
Hydroxycyclohexyl Phenyl Ketone	
pH	5.7
Trimethylbenzoyl Diphenylphosphine Oxide	
Additional information	Not irritating to rabbits on ocular application
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Trimethylbenzoyl Diphenylphosphine Oxide	
Local Lymph Node Assay	Skin sensitizer
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Silica	
IARC group	3 - Not classifiable
Titanium dioxide	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: May damage fertility or the unborn child.
Trimethylopropane Trimethacrylate	
NOAEL (animal/female, F0/P)	≥ 1000 mg/kg body weight
STOT-single exposure	: May cause respiratory irritation.
Tripropyleneglycol diacrylate	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Trimethylopropane Trimethacrylate	
LOAEL (oral,rat,90 days)	1000 mg/kg body weight
LOAEL (dermal,rat/rabbit,90 days)	300 mg/kg body weight
NOAEL (oral,rat,90 days)	300 mg/kg body weight
NOAEL (dermal,rat/rabbit,90 days)	300 mg/kg body weight
Tripropyleneglycol diacrylate	
LOAEL (dermal,rat/rabbit,90 days)	20 mg/kg body weight

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hydroxycyclohexyl Phenyl Ketone	
NOAEL (oral,rat,90 days)	300 mg/kg body weight
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation. Prolonged and frequent exposure through inhalation may cause cancer.
Symptoms/effects after skin contact	: May cause irritation to skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.
Most Important Symptoms/Effects	: May cause an allergic skin reaction.
Chronic symptoms	: Suspected of causing cancer. May damage fertility or the unborn child.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects

Trimethylopropane Trimethacrylate	
LC50 - Fish [1]	2 mg/l
EC50 - Crustacea [1]	> 9.22 mg/l

Tripropyleneglycol diacrylate	
LC50 - Fish [1]	4.5 mg/l
EC50 - Crustacea [1]	88.7 mg/l
EC50 72h - Algae [1]	> 28 mg/l

Hydroxycyclohexyl Phenyl Ketone	
LC50 - Fish [1]	58.426 mg/l
EC50 - Crustacea [1]	53.9 mg/l
EC50 72h - Algae [1]	14.4 mg/l
EC50 72h - Algae [2]	4.68 mg/l
EC50 96h - Algae [1]	41.382 mg/l

Trimethylbenzoyl Diphenylphosphine Oxide	
LC50 - Fish [1]	1.4 mg/l
EC50 - Crustacea [1]	3.53 mg/l
EC50 72h - Algae [1]	> 2.01 mg/l

Titanium dioxide	
EC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
LOEC (chronic)	5 mg/l

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.2. Persistence and degradability

Builder Gel

Persistence and degradability	Not established.
-------------------------------	------------------

Bis-Hydroxyethyl Methacrylate Poly (Neopentyl Glycol Adipate)/IPDI Copolymer

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Trimethylopropane Trimethacrylate

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Tripropyleneglycol diacrylate

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Silica

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Hydroxycyclohexyl Phenyl Ketone

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Trimethylbenzoyl Diphenylphosphine Oxide

Persistence and degradability	% biodegradation Not readily biodegradable.
-------------------------------	---

Titanium dioxide

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

Builder Gel

Bioaccumulative potential	Not established.
---------------------------	------------------

Tripropyleneglycol diacrylate

Partition coefficient n-octanol/water (Log Pow)	2.77
---	------

Hydroxycyclohexyl Phenyl Ketone

Partition coefficient n-octanol/water (Log Pow)	2.44
---	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
-------	------------------

Fluorinated greenhouse gases	: No
------------------------------	------

SECTION 13 Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

Sewage disposal recommendations	: Disposal must be done according to official regulations.
---------------------------------	--

Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Refer to all applicable national, international and local regulations or provisions.
--	---

Additional information	: Do not re-use empty containers.
------------------------	-----------------------------------

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN3082	3082	3082
14.2. Proper Shipping Name		
Environmentally hazardous substances, liquid, n.o.s. (Trimethylopropane Trimethacrylate and Tripropyleneglycol diacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Trimethylopropane Trimethacrylate and Tripropyleneglycol diacrylate)	Environmentally hazardous substance, liquid, n.o.s. (Trimethylopropane Trimethacrylate and Tripropyleneglycol diacrylate)
14.3. Transport hazard class(es)		
9	9	9
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
	Dangerous for the environment: Yes Marine pollutant: Yes	
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
UN-No. (DOT) : UN3082
DOT Packaging Exceptions (49 CFR 173.xxx) : 155
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No Limit
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG
Special provision (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Stowage category (IMDG) : A

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
ERG code (IATA) : 9L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Bis-HEA Poly(1,4-butanediol)-9/ IPDI Copolymer	CAS-No. No Data	20 – 60%
--	-----------------	----------

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Bis-Hydroxyethyl Methacrylate Poly (Neopentyl Glycol Adipate)/IPDI Copolymer (82339-16-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Trimethylopropane Trimethacrylate (3290-92-4)

Listed on the Canadian DSL (Domestic Substances List)

Tripropyleneglycol diacrylate (42978-66-5)

Listed on the Canadian DSL (Domestic Substances List)

Silica (60676-86-0)

Listed on the Canadian DSL (Domestic Substances List)

Hydroxycyclohexyl Phenyl Ketone (947-19-3)

Listed on the Canadian DSL (Domestic Substances List)

Trimethylbenzoyl Diphenylphosphine Oxide (75980-60-8)

Listed on the Canadian DSL (Domestic Substances List)

Titanium dioxide

Listed on the Canadian DSL (Domestic Substances List)

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

EU-Regulations

No additional information available

National regulations

Tripropyleneglycol diacrylate (42978-66-5)
Listed on INSQ (Mexican National Inventory of Chemical Substances)


Silica (60676-86-0)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hydroxycyclohexyl Phenyl Ketone (947-19-3)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Trimethylbenzoyl Diphenylphosphine Oxide (75980-60-8)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Titanium dioxide
Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

**WARNING:**

This product can expose you to Titanium dioxide (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Silica(60676-86-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
Titanium dioxide(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 7/30/2025
Issue date : 12/20/2024

Full text of hazard classes and H-statements	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H351	Suspected of causing cancer.

Builder Gel

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H360	May damage fertility or the unborn child
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Indication of changes:		
Section	Changed item	Comments
2	Precautionary statements (GHS US)	Modified
2	Signal word (GHS US)	Modified
2	Hazard pictograms (GHS US)	Modified
2	Hazard statements (GHS US)	Modified
2.1	GHS-US classification	Modified
4	Chronic symptoms	Modified

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.