SAFETY DATA SHEET

ARBOSIL® XL1099S

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : ARBOSIL® XL1099S

Product description : Sealants

Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Sealants

Uses advised against	Reason
For professional users only.	-

1.3 Details of the supplier of the safety data sheet

CARLISLE®Adshead Ratcliffe & Co. Ltd
Unit 1, Park Lane Business Park, Park Lane , Kirkby-in-Ashfield, Nottingham, NG17 9GU, United Kingdom
T +44 (0)1623 627285

e-mail address of person responsible for this SDS : SDSQueries@carlisleccm.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : National Poisons Information Service (NPIS)
Tel: 0344 892 0111 (for healthcare professionals only)
Website: http://www.npis.org/
Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111. In Northern Ireland contact your local GP.

Supplier

Telephone number : +44 (0)1773 826661
(Office hours: 8.30 - 17.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Eye Irrit. 2, H319

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



SECTION 2: Hazards identification

Signal word : Warning

Hazard statements : H319 - Causes serious eye irritation.

Precautionary statements

Prevention : P264 - Wash thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Curing process releases 2-pentanone oxime. 2-Pentanone oxime is classified as harmful if swallowed, causes serious eye irritation, may cause damage to blood/ spleen through prolonged/repeated exposure and is harmful to aquatic life with long lasting effects.
Curing process may release a small amount of methanol which is irritating to mucous membranes and has skin drying and narcotic effects.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Silane, dichlorodimethyl-, reaction products with silica	REACH #: 01-2119379499-16 EC: 271-893-4 CAS: 68611-44-9	≤5	Not classified.	[2]
2-Pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	REACH #: 01-2120004323-76 EC: 484-460-1	≤5	Acute Tox. 4, H302 Eye Irrit. 2, H319	[1]
Polydimethylsiloxane with aminoalkyl groups	CAS: 67923-07-3	<3	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	REACH #: 01-2119456810-40	≤3	Asp. Tox. 1, H304 EUH066	[1]
dioctyltin dilaurate	UK (GB) REACH #: UK-01-4760535389-6 EC: 222-883-3 CAS: 3648-18-8 Index: 050-031-00-9	<0.3	Repr. 1B, H360D STOT RE 1, H372 (immune system)	[1] [2]
toluene	EC: 203-625-9	≤0.1	Flam. Liq. 2, H225	[1] [2]

SECTION 3: Composition/information on ingredients

	CAS: 108-88-3 Index: 601-021-00-3		Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 (central nervous system (CNS)) (inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412 **See Section 16 for the full text of the H statements declared above.**	

Type

[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Curing process releases 2-pentanone oxime. 2-Pentanone oxime is classified as harmful if swallowed, causes serious eye irritation and may cause damage to blood/ spleen through prolonged/repeated exposure.
Curing process may release a small amount of methanol which is irritating to mucous membranes and has skin drying and narcotic effects.

Specific treatments : Antidote for methanol poisoning is ethanol.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : No specific fire or explosion hazard.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

Large spill : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Silane, dichlorodimethyl-, reaction products with silica	**EH40/2005 WELs (United Kingdom (UK), 1/2020)** TWA 8 hours: 2.4 mg/m³. Form: Respirable dust. TWA 8 hours: 6 mg/m³. Form: inhalable dust.
dioctyltin dilaurate	**EH40/2005 WELs (United Kingdom (UK), 1/2020) [tin compounds, organic, except cyhexatin (ISO)]** Absorbed through skin. STEL 15 minutes: 0.2 mg/m³ (as Sn). TWA 8 hours: 0.1 mg/m³ (as Sn).
toluene	**EH40/2005 WELs (United Kingdom (UK)) [Toluene]** Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 191 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 384 mg/m³.

Biological exposure indices

SECTION 8: Exposure controls/personal protection

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	**DNEL - Workers - Long term - Inhalation** 0.229 mg/m³ Effects: Systemic **DNEL - Workers - Long term - Dermal** 0.065 mg/kg bw/day Effects: Systemic
dioctyltin dilaurate	**DNEL - General population - Long term - Oral** 0.0005 mg/kg bw/day Effects: Systemic **DNEL - General population - Long term - Inhalation** 0.0009 mg/m³ Effects: Systemic **DNEL - Workers - Long term - Inhalation** 0.0035 mg/m³ Effects: Systemic
toluene	**DNEL - General population - Long term - Oral** 8.13 mg/kg bw/day Effects: Systemic **DNEL - General population - Long term - Inhalation** 56.5 mg/m³ Effects: Local **DNEL - General population - Long term - Inhalation** 56.5 mg/m³ Effects: Systemic **DNEL - Workers - Long term - Inhalation** 192 mg/m³ Effects: Local **DNEL - Workers - Long term - Inhalation** 192 mg/m³ Effects: Systemic **DNEL - General population - Long term - Dermal** 226 mg/kg bw/day Effects: Systemic **DNEL - General population - Short term - Inhalation** 226 mg/m³ Effects: Local **DNEL - General population - Short term - Inhalation** 226 mg/m³

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - Workers - Long term - Dermal
384 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Short term - Inhalation
384 mg/m³
Effects: Local

DNEL - Workers - Short term - Inhalation
384 mg/m³
Effects: Systemic

PNECs

Product/ingredient name	Result
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	**Fresh water** 0.1 mg/l **Marine water** 0.01 mg/l **Sewage Treatment Plant** 2.15 mg/l **Fresh water sediment** 0.569 mg/kg **Marine water sediment** 0.057 mg/kg **Soil** 0.044 mg/kg
toluene	**Fresh water** 0.68 mg/l **Fresh water** 0.68 mg/l **Marine water** 0.68 mg/l **Sewage Treatment Plant** 13.61 mg/l **Fresh water sediment** 16.39 mg/kg **Marine water sediment** 16.39 mg/kg **Soil** 2.89 mg/kg

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

SECTION 8: Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use appropriate respiratory protection if there is a risk of exceeding any exposure limits. Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid. [Paste.]

Color : Various

Odor : Slight

Odor threshold : Not available.

Melting point/freezing point : Not available.

Initial boiling point and boiling range : Not available.

Flammability (solid, gas) : Not available.

Upper/lower flammability or explosive limits : Not applicable.

Flash point : Not applicable.

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

pH : Not applicable.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): Not available.

SECTION 9: Physical and chemical properties

Solubility in water	:	Insoluble
Miscible with water	:	No.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapor pressure	:	Not available.
Evaporation rate	:	Not available.
Relative density	:	1.28
Vapor density	:	Not applicable.
Explosive properties	:	Not available.
Oxidizing properties	:	Not available.
Particle characteristics		
Median particle size	:	Not available.

9.2 Other information

Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid excessive heat for prolonged periods of time.

10.5 Incompatible materials : Oxidizing agents

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
Silane, dichlorodimethyl-, reaction products with silica	**Rat - Oral - LD50** >5000 mg/kg **Rat - Inhalation - LC50 Vapor** 450 mg/m³ [4 hours] Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Dyspnea Lung, Thorax, or Respiration - Other changes
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	**Rat - Female - Oral - LD50** 1234 mg/kg OECD [Acute Oral Toxicity: Up-and-Down Procedure] **Rat - Male, Female - Dermal - LD50** >1782 mg/kg
dioctyltin dilaurate	**Rat - Oral - LD50** 6450 mg/kg
toluene	**Rat - Oral - LD50**

SECTION 11: Toxicological information

636 mg/kg

Rat - Inhalation - LC50 Vapor
49 g/m³ [4 hours]

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
ARBOSIL® XL1099S	29899.6	N/A	N/A	N/A	N/A
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne) trioxime]	1234	N/A	N/A	N/A	N/A
dioctyltin dilaurate	6450	N/A	N/A	N/A	N/A
toluene	N/A	N/A	N/A	49	N/A

Skin corrosion/irritation

Product/ingredient name	Result
toluene	**Pig - Skin - Mild irritant** Duration of treatment/exposure: 24 hours Amount/concentration applied: 250 uL **Rabbit - Skin - Mild irritant** Amount/concentration applied: 435 mg **Rabbit - Skin - Moderate irritant** Duration of treatment/exposure: 24 hours Amount/concentration applied: 20 mg **Rabbit - Skin - Moderate irritant** Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product/ingredient name	Result
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	**Rabbit - Eyes - Irritant**
toluene	**Rabbit - Eyes - Mild irritant** Duration of treatment/exposure: 0.5 minutes Amount/concentration applied: 100 mg **Rabbit - Eyes - Mild irritant** Amount/concentration applied: 870 ug **Rabbit - Eyes - Severe irritant** Duration of treatment/exposure: 24 hours Amount/concentration applied: 2 mg **Rabbit - Eyes - Severe irritant** Amount/concentration applied: 0.1 Ml

Conclusion/Summary [Product] : Eye Irrit. 2

Respiratory corrosion/irritation

Not available.

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Respiratory

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
toluene	STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
dioctyltin dilaurate	STOT RE 1, H372 (immune system)
toluene	STOT RE 2, H373 (central nervous system (CNS)) (inhalation)

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

SECTION 11: Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Causes serious eye irritation.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

General : Curing process releases 2-pentanone oxime. 2-Pentanone oxime is classified as harmful if swallowed, causes serious eye irritation and may cause damage to blood/spleen through prolonged/repeated exposure.
Curing process may release a small amount of methanol which is irritating to mucous membranes and has skin drying and narcotic effects.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
toluene	**Acute - LC50 - Fresh water** Fish - Coho salmon,silver salmon - *Oncorhynchus kisutch* - Fry Weight: 1 g 5500 µg/l [96 hours] Effect: Mortality **Acute - EC50 - Fresh water** Daphnia - Water flea - *Daphnia magna* - Juvenile (Fledgling, Hatchling, Weanling) 6000 µg/l [48 hours] Effect: Intoxication **Acute - EC50 - Fresh water** Algae - Green algae - *Raphidocelis subcapitata* 12.5 mg/l [72 hours] Effect: Growth **Chronic - NOEC - Fresh water** Daphnia - Water flea - *Daphnia magna*

SECTION 12: Ecological information

Age: ≤24 hours
1 mg/l [21 days]
Effect: Mortality

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met. Curing process releases 2-pentanone oxime. 2-Pentanone oxime is classified as harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	-	-	Not readily
toluene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
dioctyltin dilaurate	-	<100	Low
toluene	2.73	90	Low

12.4 Mobility in soil

Soil/Water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Silane, dichlorodimethyl-, reaction products with silica	No	N/A	N/A	No	N/A	N/A	N/A
2-pentanone, 2,2',2''-[O,O',O''-(methylsilylidyne)trioxime]	No	N/A	N/A	No	N/A	N/A	N/A
Polydimethylsiloxane with aminoalkyl groups	No	N/A	N/A	No	N/A	N/A	N/A
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	No	N/A	N/A	No	N/A	N/A	N/A
dioctyltin dilaurate	No	N/A	No	Yes	No	N/A	No
toluene	No	N/A	No	Yes	No	N/A	No

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Waste catalogue

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

SECTION 15: Regulatory information

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Part	Ingredient name	Status
Part 1	dioctyltin compounds	Listed

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
dioctyltin dilaurate toluene	<0.3 ≤0.1	20 48

Labeling : Not applicable.

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Canada : Not determined.

Chile : Not determined.

China : Not determined.

Colombia : Not determined.

Eurasian Economic Union : **Russian Federation inventory**: Not determined.

Japan : **Japan inventory (CSCL)**: Not determined.
Japan inventory (ISHL): Not determined.

New Zealand : Not determined.

Philippines : Not determined.

SECTION 15: Regulatory information

Republic of Korea : Not determined.

Taiwan : Not determined.

Thailand : Not determined.

Turkey : Not determined.

United States : Not determined.

Viet Nam : Not determined.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Eye Irrit. 2, H319	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 12 August 2026

SECTION 16: Other information

Date of issue/ Date of revision : 12 August 2026

Date of previous issue : No previous validation

Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.