

Material Confirmation

Your Contact:
Evelyn Allert-Ektilah
evelyn.allert-ektilah@akro-plastic.com

Phone: +49 2636 9742 - 137
Fax: +49 2636 9742-42137

Date: 12.01.2024
Page: 1 of 1

STANDARDS/RECOMMENDATIONS/DIRECTIVES

FMVSS 302 Federal Motor Vehicle Safety Standard 302
CMVSS 302 Flammability of Interior Materials
TL 1010 Interior Materials, burning rate
ISO 3795 Interior Materials, burning rate
GB 8410 Flammability of Automotive Interior Materials

CONFIRMATION

We confirm that

AKROMID®, AKROLOY®, AKROTEK® and AKROLEN®

grades fulfill the above mentioned standards. The burning rate is ≤ 100 mm/min @ 1 mm wall thickness.

Kind Regards
AKRO-PLASTIC GmbH

i. A. 

Evelyn Allert-Ektilah
R&D Project Engineer

The information is based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests. The declaration is not be construed as guaranteeing specific properties of the product or their suitability for a particular application. This declaration replaces all previous ones to this subject. The document is valid two years.

AKRO-PLASTIC GmbH
Member of the Feddersen Group

Industriegebiet Brohltal Ost
Im Stiefelfeld 1
56651 Niederzissen

P.O.B. 67
56649 Niederzissen

Phone: +49 2636 9742-0
Fax: +49 2636 9742-31
info@akro-plastic.com
www.akro-plastic.com

Managing Directors:
Dr. Oliver Neuß
Dirk Steinbrück
Marc Tenne

Chairman of the Supervisory Board:
Dr. Matthias von Rönn
Commercial Register Koblenz HRB 12227
VAT no. DE811117257