CHECKLIST FOR CONSTRUCTION DRAWINGS OF TOURIST STANDARD TENTED ACCOMODATION



CONTENTS

MANDATORY FUNCTION	OPTIONAL FUNCTION	
1.) BUILDING LAYOUT AND FUNCTION ZONING 1	6.) SEMINAR / MEETING ROOM	6
2.) LOBBY AREA 2	7.) SWIMMING POOL	7
3.) RESTAURANT AREA	8.) HOT STONE BATHING	8
4.) GUESTROOMS AREA	9.) FITNESS ROOM	1
5.) STAFF AND SERVICE AREA 4	10.) EXTERNAL SHOP	1
	11.) ENTERTAINMENT ROOMS	1

This document is the necessary function requirements of tourist standard tented accommodation drawings for TCB technical clearance

1. BUILDING LAYOUT AND FUNCTION ZONING

No.	Requirement function	Description	✓
1.1	Parking area	-If there is no parking lot in the layout drawings, the parking lots area must be provided in the site or closed to the site when the hotel is opened.	
		-Separate parking for staff	
1.2	Internal access road to the	One lane road	
	parking area	- Minimum clear width = 3.0 m	
		Two lanes road	
		- Minimum clear width = 5.0 m	
1.3	Guest main entrance door	-Prominent and easily accessible from the parking lot	
1.4	Staff main entrance door	-Separated and hidden away from the guest entrance.	
1.5	Internal function zoning	-Guests function rooms must be separated from staff and service functions rooms.	
		-Private function area must be separated from public function area.	

No.	Requirement function	Description	✓
2.1	Reception	-Counter or desk area must be provided.	
		-Minimum clear height = 3m	
2.2	Seats area	-Spacious reception hall with several seats and service.	
		-Windows and natural ventilation must be adequate.	
2.3	Public restrooms	-Easily accessible from the reception.	
	(semi-permanent/tent)	-Male & female separation.	
		-Male restroom minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet	
		-Female restroom minimum sanitary wares = 1 wash basin, 1 flush toilet	
		-Natural or mechanical ventilation must be provided.	
2.4	Main walkway for guests	-Minimum clear width = 1.5 m	
	(Covered/Uncovered)	-Materials	
		-If covered, should be natural with locally found materials	
2.5	Platform	-Minimum elevation = 0.5 m	
	(Can be Concrete)		
2.6	Steps	-Minimum landing distance = 1.5 m	
		-Minimum clear width = 1.5 m	
		-Minimum tread width = 0.28 m	
		-Maximum riser height = 0.19 m	

2. RESTAURANT AREA

No.	Requirement function	Description	✓
3.1	Dining area	-Easily accessible from lobby area or public walkway.	
		-Minimum seating capacity: 50% of the total number of beds	
		-Windows and natural ventilation must be adequate.	
		-Minimum clear width of 1.2m between tables.	
3.2	Kitchen	-Back entrance and walkway for kitchen staff and service must be provided	
	(semi-permanent/tent)	separately from guest area.	
		-Size should not be less than 0.5sqm per bed offered (minimum 9sqm).	
		-Must be able to serve the dining area through pantry area.	
		-Natural or mechanic ventilation must be provided.	
3.3	Pantry room	-Natural or mechanic ventilation must be provided.	
	(semi-permanent/tent)		
3.4	Dry storage room	-Must be a separated room which can be entered from the kitchen or service	
	(semi-permanent/tent)	walkway.	
		-Natural or mechanic ventilation must be provided.	
3.5	Pastry/Bakery	-Must be a separated room which can be entered from the kitchen or service	
	(semi-permanent/tent)	walkway.	
3.5	Cold storage room	-Must be a separated room which can be entered from the kitchen or service	
	(semi-permanent/tent)	walkway.	

3.6 Restaurant restroom (semi-permanent/tent)

(If the restaurant position is connected with the lobby restrooms, the lobby restrooms can be shared with the restaurant by adding more sanitary wares)

Specific restrooms for the restaurant.

- Male & female separation
- Must be easily accessible from the dining area
- Male restroom minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet
- Female restroom minimum sanitary wares =1 wash basin, 1 flush toilet
- Natural or mechanical ventilation must be provided.

Addition minimum sanitary wares for the shared lobby restrooms.

- Male restroom = 1 flush toilet, 1 urinal, added partitions and doors for flush toilets.
- Female restroom = 1 flush toilet, added partitions and doors for flush toilets.

3. GUESTROOMS AREA

No.	Requirement function	Description	✓
4.1	Front Walkway	-Minimum clear width = 1.5 m	
4.2	Bedroom	-Bedrooms entrance must be directly connected to the front walkway.	
		Single bedroom type	
		- Minimum floor area = 16.0 sq.m	
		Double bedroom type	
		- Minimum floor area = 20.0 sq.m	
		-Minimum clear height = 2.7m	
		-Windows and natural ventilation must be adequate.	
4.3	Bathroom	-Bathroom entrance must be in the bedroom.	
	(semi-permanent/tent)	Single bedroom type	
		- Minimum floor area = 5.0 sq.m	
		Double bedroom type	
		- Minimum floor area = 6.0 sq.m	
		-Minimum sanitary wares = 1 Washbasin, 1 flush toilet, 1 shower	
		-Natural or mechanical ventilation must be adequate.	

4. STAFF AND SERVICE AREA

No.	Requirement function	Description	✓
5.1	Laundry room	-Must be able to enter from service walkway.	
		-Natural or mechanical ventilation must be provided.	
5.2	Linen room	-Must be able to enter from service walkway.	
	(semi-permanent/tent)	-Must be easily accessible to the laundry room.	
		-Secondary linen room should be provided depending on the distance &	
		number of tents.	
		-Natural or mechanical ventilation must be provided.	
5.3	Staff office	-Must be able to enter from service walkway.	
		-Natural or mechanical ventilation must be provided.	
5.4	Staff cafeteria	-Must be able to enter from service walkway.	
		-Natural or mechanical ventilation must be provided.	
		-Sink, cooking space and storage cabinet area must be provided if the staff	
		cafeteria position is not connected to the kitchen.	
5.5	Staff changing rooms	-Must be able to enter from staff walkway or staff cafeteria.	
	with lockers	-Male & female separation.	

5.6	Staff restrooms	-Must be able to enter from staff walkway or staff cafeteria	
	with showers	or staff changing rooms.	
		-Must be connected with the staff changing rooms.	
		-Male & female separation.	
		-Male restroom minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet	
		, 1 shower	
		-Female restroom minimum sanitary wares = 1 wash basin, 1 flush toilet	
		, 1 shower	
		-Natural or mechanical ventilation must be provided.	

5. SEMINAR ROOM / MEETING ROOM (OPTIONAL FUNCTION)* **Description Requirement function** No. Reception in front of -Counter or desk area must be provided. 6.1 seminar or meeting room 6.2 Waiting area -Must be separated from the lobby area. in front of seminar or -Natural or mechanical ventilation must be provided. meeting room **Restrooms for** 6.3 -Must be able to enter from the waiting area. -Male & female separation. seminar or meeting room (semi-permanent/tent) -Male restroom minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet -Female restroom minimum sanitary wares = 1 wash basin, 1 flush toilet -Natural or mechanical ventilation must be provided. (If the waiting area of Addition minimum sanitary wares for the shared lobby restrooms. seminar room is connected -Male restroom = 1 urinal, added partition and door for flush toilet.

-Female restroom = 1 flush toilet, added partition and door for flush toilet.

-Natural or mechanical ventilation must be provided.

with the lobby restrooms ,the lobby restrooms can be shared by adding more

sanitary wares)

Seats area

6.4

^{*} Optional function: Not mandatory but if any hotel provides this function, the design must follow the requirement

6. SWIMMING POOL (OPTIONAL RECREATION FUNCTION)**

No.	Requirement function	Description	✓
7.1	Reception	-Counter or desk area must be provided.	
	for the swimming pool		
7.2	Waiting area	-Natural or mechanical ventilation must be provided.	
	for the swimming pool		
7.3	Changing rooms	-Must be able to enter from the waiting area.	
	with lockers	-Male & female separation.	
	for the swimming pool	-Minimum changing units in each gender = 2 units	
		-Natural or mechanical ventilation must be provided.	
7.4	Restrooms	-Must be able to enter from the waiting area or the changing rooms.	
	with showers	-Male & female separation.	
	for the swimming pool	-Male restroom minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet,	
	(semi-permanent/tent)	1 shower room	
		-Female restroom minimum sanitary wares = 1 wash basin, 1 flush toilet,	
		1 shower room	
		-Natural or mechanical ventilation must be provided.	
7.5	Storage room	-Storage room for swimming pool must be provided.	

^{**} Optional recreation function: Not mandatory but if any hotel provides this function, the design must follow the requirement

7. HOT STONE BATHING (OPTIONAL RECREATION FUNCTION)**

No.	Requirement function	Description	✓
8.1	Reception	-Counter or desk area must be provided.	
	for hot stone bathing	(If the hot stone bathing service is connected with the reception of another	
	service	optional recreation function , the reception can be shared)	
8.2	Waiting area	-Natural or mechanical ventilation must be provided.	
	for the hot stone bathing	(If the hot stone bathing service is connected with the waiting area of another	
	service	optional recreation function , the waiting area can be shared)	
8.3	Changing rooms	-Must be able to enter from the waiting area.	
	with lockers	-Natural or mechanical ventilation must be provided.	
	for the hot stone bathing		
	service	8.3.1) Changing room for public hot stone bathing service	
		-Male & female separation.	
		-Minimum changing units in each gender = 2 units	
		(If the hot stone bathing service is connected with the changing rooms of	
		another optional recreation function , the changing rooms can be shared by	
		adding more changing units)***	
		8.3.2) Changing room for private hot stone bathing service	
		-Minimum changing unit = 1 unit	

^{**} Optional recreation function: Not mandatory but if any hotel provides this function, the design must follow the requirement

- 1.) Changing room for maximum 2 optional functions: +1 changing unit in each gender room
- 2.) Changing room for more than 2 optional functions: +2 changing units in each gender room

 $^{^{***}}$ Addition changing units for the shared changing rooms.

No.	Requirement function	Description	√
8.4	Restrooms with showers	-Natural or mechanical ventilation must be provided.	
	for the hot stone bathing	8.4.1) Restrooms for public hot stone bathing service	
	service (semi-permanent/tent)	-Must be able to enter from the waiting area or the changing rooms.-Male & female separation.	
		-Male: minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet, 1 shower room	
		-Female: minimum sanitary wares = 1 wash basin,1 flush toilet,1 shower room (If the hot stone bathing service is connected with the restrooms of another optional recreation function, the restrooms can be shared by adding more sanitary wares)***	
		8.4.2) Restrooms for private hot stone bathing service	
		-Minimum sanitary wares = 1 wash basin, 1 urinal and 1 flush toilet in a room, 1 shower room	
8.5	Storage room	-Storage room for hot stone bathing service must be provided.	
8.6	Service back entrance	-Back entrance for staff to service the hot stone bath must be provided.	

**** Addition sanitary wares for the shared restrooms.

- 1.) Restrooms for maximum 2 optional functions : +1 wash basin, +1 urinal(male restroom), +1 flush toilet, +added partitions and doors for flush toilets.
- 2.) Restrooms for more than 2 optional functions: +1 wash basins, +2 urinals(male restroom), +2 flush toilets, +added partitions and for flush toilets.

8. FITNESS ROOM (OPTIONAL RECREATION FUNCTION)** **Requirement function Description** No. -Counter or desk area must be provided. 9.1 Reception for the fitness room (If the fitness room is connected with the reception of another optional recreation function, the reception can be shared) Waiting area -Natural or mechanical ventilation must be provided. 9.2 for the fitness room (If the fitness room is connected with the waiting area of another optional recreation function, the waiting area can be shared) -Must be able to enter from the waiting area. 9.3 **Changing rooms** with lockers -Natural or mechanical ventilation must be provided. for the fitness room -Male & female separation. -Minimum changing units in each gender = 2 units (If the fitness room is connected with the changing rooms of another optional recreation function, the changing rooms can be shared by adding more changing units)***

*** Addition changing units for the shared changing rooms.

- 1.) Changing room for maximum 2 optional functions: +1 changing unit in each gender room
- 2.) Changing room for more than 2 optional functions: +2 changing units in each gender room

^{**} Optional recreation function: Not mandatory but if any hotel provides this function, the design must follow the requirement

No.	Requirement function	Description	✓
9.4	Restrooms with showers for the fitness room (semi-permanent/tent)	-Natural or mechanical ventilation must be provided. -Must be able to enter from the waiting area or the changing rooms. -Male & female separation. -Male: minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet	
9.5	Storage room	-Storage room for fitness room must be provided.	

- 1.) Restrooms for maximum 2 optional functions : +1 wash basin, +1 urinal(male restroom), +1 flush toilet, +added partitions and doors for flush toilets.
- 2.) Restrooms for more than 2 optional functions: +2 wash basins, +2 urinals(male restroom), +2 flush toilets, +added partitions and doors for flush toilets.

^{**} Optional recreation function: Not mandatory but if any hotel provides this function, the design must follow the requirement

**** Addition sanitary wares for the shared restrooms.

9.	9. EXTERNAL SHOP (OPTIONAL FUNCTION)*			
No.	Requirement function	Description	✓	
10.1	Entrance	-Must be located in public areaMust be separated from hotel guests & staff entrances.		

^{*} **Optional function**: Not mandatory but if any hotel provide this function, the design must follow the requirement.

10.ENTERTAINMENT ROOMS (OPTIONAL FUNCTION)*			
No.	Requirement function	Description	✓
11.1	Entrance	-Must be located in public areaMust be separated from hotel guests & staff entrances.	
11.2	Specific reception	-Counter or desk area must be provided.	
11.3	Entertainment rooms	-Must be sound-proofNatural or mechanical ventilation must be provided.	
11.4	Specific restrooms	-Male & female separation. -Male restroom minimum sanitary wares = 1 wash basin, 1 urinal, 1 flush toilet -Female restroom minimum sanitary wares = 1 wash basin, 1 flush toilet -Natural or mechanical ventilation must be provided.	
11.5	Pantry area	-Counter for food/drink preparation and sink must be provided.	

^{*} **Optional function**: Not mandatory but if any hotel provide this function, the design must follow the requirement.