




## CAMCAT® Highspeed

The CAMCAT® Highspeed, a variant of the CAMCAT® Standard is an advanced, fully remote controlled cable camera system designed to run between two fixed points up to 1000m apart at speeds of up to 130 km/h.

The CAMCAT® Highspeed camera buggy can accept a range of payloads. You can use open platform stabilized mounts fitted with different cameras up to 35mm as well as stabilized mounts with integrated camera and lens.

Examples of open platform stabilized mounts:  
 Libra Head, Stab-C, Mini-C, Flight Head

Examples of stabilized mounts with integrated camera and lens:  
 GSS, Apex etc.



Max. Speed  
 130 km/h  
 36 m/s



Max. Acceleration  
 5,5 m/s<sup>2</sup>  
 6,6 sec. 111m to top speed



Length  
 1000 m  
 3280 ft



Dimension Base Station  
 l/h/w: 5m/4,5 m/2,6 m  
 weight: 1600 kg ( 3500 lbs)

**Certified from the German Health and Safety Group (TÜV) including DGUV V 17/18**

\*More information available on request.

**CAMCAT®**

WWW.CAMCAT-SYSTEMS.COM

Josef Perger Straße 4A  
 3031 Rekawinkel  
 Tel.: +43 660 6677505  
 Fax: +43 1 4853682  
 office@camcat-systems.com