




CAMCAT® colibri

The CAMCAT® colibri was developed to offer our customers a lightweight and compact wire camera system. It finds its place in the CAMCAT® family where the proven systems of the CAMCAT® are too large and the requirements are not that extreme (wind, weather, acceleration or track length).

In an intensively process with our clients we defined the parameters for the CAMCAT® colibri I. In the end our developers were able to optimize the system with respect to safety, quality and efficiency.

The result is a small cable camera (min 50 cm track width) that needs just very little tension forces, because of the low weight.

In combination with the Flight Head-MINI, (compact, fully stabilizing camera head) which was optimized by the manufacturer, the CAMCAT® colibri is not only the perfect tool for live broadcast. In combination with a modern digital „movie camera“ you can also use the CAMCAT® colibri for feature film and commercials as an economically alternative to the proven CAMCAT® System.



Max. Speed
54km/h
15 m/s



Max. Acceleration
3 m/s²
0 to 50km/h in 4,6 sec



Length
350 m
1148 ft

Certified from the German Health and Safety Group (TÜV) including DGUV V 17/18

*More information available on request.

CAMCAT®

WWW.CAMCAT-SYSTEMS.COM

Josef Perger Straße 4A
3031 Rekawinkel
Tel.: +43 660 6677505
Fax: +43 1 4853682
office@camcat-systems.com