

**1KOM
MA5°**

1KOMMA5° BACKUP BOX

- Full Home Backup
- Automatically switch to Off-Grid state
- 3 Phase Backup-Box



BACKUP BOX

63MAX. INPUT CURRENT
(PER PHASE)**Plug & Play**

EASY INSTALLATION

AllrounderCOMPATIBLE WITH
1K5[®] BATTERY & INVERTER**IP65**

PROTECTION CLASS

MODEL**1K5-BACKUP-V1****UTILITY SUPPLY**

Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50 / 60 Hz
Max. Input Current (Per Phase)[A]	63

INVERTER GRID

Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50 / 60
Max. Input Current (Per Phase)[A]	25

GENERAL DATA

Cooling Concept	Natural
Installation	Wall-mounted
Operating Temperature Range (°C)	-25 ~ +60 (derating at 45)
Dimensions (W×H×D)[mm]	550×420×138.5
Dimensions of packing (W×H×D)(mm)	660×530×245
Net Weight [kg]	16
Gross Weight [kg]	19.3
Ingress Protection	IP65

INVERTER EPS

Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50 / 60
Max. Input Current (Per Phase)[A]	25

LOAD

Rated Voltage [VAC]	220/380, 230/400, 3L/N/PE
Rated Frequency [Hz]	50 / 60
Max. Output Current (Per Phase)[A]	63

COMMUNICATION INTERFACE

RS-485 (Meter)