

TCB

GRANT OF EQUIPMENT
AUTHORIZATION

TCB

Certification
Issued Under the Authority of the
Federal Communications Commission
By:

UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538

Date of Grant: 06/23/2023

Application Dated: 06/23/2023

Axon Enterprise, Inc
17800 N. 85th Street
Scottsdale, AZ 85255

Attention: Elisabet Dominguez , Product Compliance
Engineer

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's Rules
and Regulations listed below.

FCC IDENTIFIER: X4GAB065
Name of Grantee: Axon Enterprise, Inc
Equipment Class: PCS Licensed Transmitter
Notes: Module
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	829.0 - 844.0	0.3148	0.01 PM	8M95G7D
	22H	829.0 - 844.0	0.2642	0.01 PM	8M94W7D
	22H	825.5 - 847.5	0.2673	0.01 PM	2M69W7D
	22H	831.5 - 841.5	0.3076	0.01 PM	13M5G7D
	22H	831.5 - 841.5	0.26	0.01 PM	13M5W7D
	22H	829.0 - 844.0	0.3119	0.01 PM	8M96G7D
	24E	1860.0 - 1900.0	0.2904	0.01 PM	17M9G7D
	24E	1860.0 - 1900.0	0.2404	0.01 PM	17M9W7D
	24E	1855.0 - 1905.0	0.2477	0.01 PM	8M93W7D
	24E	1860.0 - 1905.0	0.2667	0.01 PM	17M9G7D
	24E	1860.0 - 1905.0	0.2208	0.01 PM	17M9W7D
	24E	1855.0 - 1910.0	0.2679	0.01 PM	8M94G7D
	24E	1851.5 - 1913.5	0.2265	0.01 PM	2M69W7D
	27	1720.0 - 1745.0	0.2844	0.01 PM	17M9G7D
	27	1720.0 - 1745.0	0.2438	0.01 PM	17M9W7D
	27	1711.5 - 1753.5	0.2958	0.01 PM	2M70G7D
	27	1712.5 - 1752.5	0.25	0.01 PM	4M48W7D
	27	2510.0 - 2560.0	0.2716	0.01 PM	17M9G7D
	27	2510.0 - 2560.0	0.2286	0.01 PM	17M9W7D
	27	2507.5 - 2562.5	0.2735	0.01 PM	13M5G7D
	27	704.0 - 711.0	0.3062	0.01 PM	8M94G7D
	27	704.0 - 711.0	0.26	0.01 PM	8M94W7D
	27	782.0 - 782.0	0.3027	0.01 PM	8M92G7D
	27	782.0 - 782.0	0.2588	0.01 PM	8M93W7D
	27	779.5 - 784.5	0.3055	0.01 PM	4M47G7D

27	2310.0 - 2310.0	0.1977	0.01 PM	9M97G7D
27	2310.0 - 2310.0	0.1629	0.01 PM	8M97W7D
27	2307.5 - 2312.5	0.169	0.01 PM	4M52W7D
27	1720.0 - 1770.0	0.2704	0.01 PM	18M0G7D
27	1720.0 - 1770.0	0.2317	0.01 PM	17M9W7D
90	793.0 - 793.0	0.2904	0.01 PM	8M93G7D
90	793.0 - 793.0	0.2415	0.01 PM	8M93W7D
90	790.5 - 795.5	0.2917	0.01 PM	4M47W7D
90	790.5 - 795.5	0.2472	0.01 PM	4M48W7D
90	819.0 - 819.0	0.2178	0.01 PM	8M93G7D
90	819.0 - 819.0	0.1837	0.01 PM	8M92W7D
90	814.7 - 823.3	0.2183	0.01 PM	1M09G7D
90	815.5 - 823.5	0.1849	0.01 PM	2M69W7D

C2PC to add portable host with collocated transmitters approved under FCC ID X4GS01506. Output power is reduced when installed in the host as documented in the filing. The highest reported SAR values for body-worn, extremity (10g) and simultaneous transmission (1g and 10g) exposure conditions are 1.161 W/kg, 3.41 W/kg (10g) and 1.354 W/kg and 3.546 W/kg (10g) respectively

Output power listed for LTE Band 2/4/5/7/12/13/14/25/26/30/66 are conducted average power. It supports LTE (QPSK, 16QAM, 64QAM) LTE B2, B4, B5, B7, B12, B13, B14, B25, B26, B30, B66 Channel Bandwidth (1.4/3/5/10 MHz) for LTE B5, B12 Channel Bandwidth (1.4/3/5/10/15 MHz) for LTE B26 Channel Bandwidth (1.4/3/5/10/15/20 MHz) for LTE B2, B4, B25, B66 Channel Bandwidth (5/10 MHz) for LTE B13, B14, B30 Channel Bandwidth (5/10/15/20 MHz) for LTE B7

This device contains functions that are not operational in U.S. Territories; this filing is only applicable for U.S. operations.

Modular Approval for mobile RF Exposure conditions, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. Approval is limited to OEM installation only. OEM integrators must be provided with antenna installation instructions. OEM integrators and end users must be provided with transmitter operating conditions for satisfying RF exposure compliance. This grant is valid only when the device is sold to OEM integrators and the OEM integrators are instructed to ensure that the end user has no manual instructions to remove or install the device. Only the antenna(s) listed in this filing can be used with this device. Use of additional antenna(s) are subject to the requirements of 15.204(c)(4).

Max. Antenna Gain are LTE B2/4/25/66 are 1.38 dBi, B5/12/13/14/26 are -0.01 dBi, B7 is -5.90 dBi, and B30 is -5.70 dBi.