

Service Bulletin

no. 21, 2019-03-26

Seals on the Deckma OMD-24, 15 ppm bilge alarm

System applicability: Marinfloc Oily Water Separators and Marinfloc WhiteBoxes supplied with the Deckma OMD-24 oil content monitor

Background

Deckma fasten sticker seals on their OMD-24 oil content monitor computer units, on the oil content monitor cells and on the magnetic valve attached to the oil content monitor. This service bulletin highlights those seals and is a reminder of never removing/breaking them. The seals serve as a proof that the equipment has never been tampered with.

1. Oil content monitor computer unit

The OMD-24 EV bilge alarm is sealed according to picture no. 1. Do not break the yellow seal.

2. Oil content monitor cell

One seal sticker in combination with a metal clip on the measuring cell (label works as seal), see picture no. 2. Do not remove the sticker.

3. The magnetic valve

One seal sticker and two sealed screws on top of the valve, see picture no. 3. Do not remove the seals. You are not allowed to open up the valve for cleaning purposes, you are only allowed to replace the valve with a new one. The two sealed screws should never be opened. Some valves distributed are missing the sticker (PN 00212381/00314402) on the bottom of the valve but the screws are sealed with the red paint.



Picture 1.
Oil content monitor - computer unit



Picture 2.
Oil content monitor - cell



Picture 3. Magnetic valve

Source: Deckma official letter: Seals on the OMD-24, 15 ppm Bilge Alarm

Page 1 (1)

Marinfloc Service Bulletin no. 21, ver. 1.0