




NSPB Series

The ultimate solution for demanding level control. Multi-function level switches in standard lengths, delivering outstanding performance.

- Impact resistant terminal box, IP67
- Universal mounting, G1" & flange
- Standard lengths and functions*



HM 2511



Sensors with REED technology without power consumption, manufactured with the highest quality in our ISO-certified factory in Roslagen, Sweden.

General description:

NSPB. The float level switches are available with up to five functions in the same unit. It can also be combined with a built-in temperature sensor or overtemperature protection. Suitable for most kinds of liquids.

Construction:


Terminal box with waterproof screw lid, protection class IP67. Terminals with spring-loaded connection for mounting your own cable. G1" threaded connection and flange provide two options for mounting. Ø12mm probe in SUS-316, floats in NBR.





* See our range of NSBP standard switches on our website. Other models on request. Variants with (e.g. other switch point length) can be added, m.o.q. 10 pcs.

O: NO, open at low level, closes rising
S: NC, closed at low level, opens rising
V: NO/NC, change-over

T: Overtemperature protection. NC, opens rising at 70°C ±5
T1: Built-in temperature sensor Pt100
T3: Built-in temperature sensor Pt1000
T8: Built-in temperature sensor, 0-10V -20...100°C



= Switch closed
 = Switch open



Section A-A

TEMPERATURE SENSOR
Analog output 0-10V

Measuring range: -20°C....+100°C
(0V at -20°C, 10V at +100°C)

Supply voltage	10-30VDC
Output	0-10V

FEATURES

Float liquid level sensor with REED-technology to activate pumps or valves via relays or PLC. Suitable for most kinds of liquids.

MATERIALS

Probe : SUS-316
Float : NBR, S.G. 0,42
Terminal box : Polyamid 6
Gasket : Nitrile
Temp. media : -20...+100°C
Temp. ambient : -20...+70°C

CONTACT SYMBOLS

O = means NO low, NC going upwards

PROTECTION DEGREE

Terminal box : IP67
Probe : IP68

ELECTRICAL MAX DATA (LEVEL)

Contact rating *	70 VA
Voltage	3-48 VAC/DC
Current	1,5 A

* = resistive load