

HEMOMATIK

Sweden

Liquid level switch

Art.nr.

HMC-V

V=..... mm

Drawing nr.

HMC-V

Rev.

2

Approved

P.L. 930603

Scale

1:2

Date

921019

Sign.

MEM

Rev. date

921117





Note! Read this instruction before installation and use

yellow / green
black
gray (common)
brown



Rights to the design and drawing belongs to HEMOMATIK Sweden, copyright ©



FEATURES

Float liquid level sensor with REED-technology to activate pumps or valves via relays or PCs. Recommended for oil and petroleum fluids.

MATERIALS

Stem : Brass
Float : Buna-N (nitrofuel), S.G. 0,3
Fitting : POM C
Cable : 2m / PVC 4x 0.5mm²
Temp. media : -20...+100°C
Temp. ambient : -20...+70°C
For use 0-5000m above MSL

CONTACT SYMBOLS

V = change over

PROTECTION DEGREE

Outside tank : IP65
Inside tank : IP68

ELECTRICAL DATA

Contact rating *	60 VA
max voltage	3-230 V AC/DC DC to 60Hz
max current	1 A

* = resistive load

WARNING! If no protective earth is connected to the sensor then only voltages of maximum 48V AC or DC may be connected

■ = Switch closed

□ = Switch open

This manual is available in pdf format, please contact Hemomatik AB