



HSC3/8 Series

The ultimate solution for demanding level control. Multi-function level switches in custom lengths, delivering outstanding flexibility.

- Withstands pressure up to 25 bar
- Full INOX, all parts in stainless steel, SUS-316
- Selectable switch point lengths and contact functions*



HM 2511

Sensors with REED technology without power consumption, manufactured with the highest quality in our ISO-certified factory in Roslagen, Sweden.

General description:

HSC3/8. The float level switches are available with up to three functions in the same unit. It can also be combined with an overtemperature protection. Suitable for most kinds of liquids.

Construction:

Two meters oil resistance polyurethane cable, other cable length on request. Adjustable G3/8" compression fitting, when the nut is tightened, the coupling is fixed and pressure tight to the probe. Ø57mm float with extra high buoyancy.

Options:

Art No: M-G3/8-V4A (Nut G3/8", SUS-316). Ordered as a separate part.

* We manufacture the sensor in desired lengths. Specify switch points length (mm) and contact function when ordering.

O : NO, open at low level, closes rising

S : NC, closed at low level, opens rising

V : NO/NC, change-over

T : Overtemperature protection. NC, opens rising at 70°C ±5

Options, special on request:

Overtemperature protection with other switching temperature and smaller hysteresis.

Built-in temperature sensor Pt100 or Pt1000.