AQUALISA

S3 SINGLE OUTLET SMART SHOWER

S3C.H.P

S3MB.H.P

S3BB.H.P

S3GG.H.P


WITH WI-FI CONNECTED TECHNOLOGY AND
HD MULTI-FUNCTION DISPLAY, ADJUSTABLE HANDSET

GRAVITY


Chrome / Matt Black / Brushed Brass / Gunmetal Grey

DIMENSIONAL DRAWINGS


S3 Controller




1.5m Hose




120mm Adjustable Handset




Rail Kit



Wall Outlet



Pumped Single Outlet SmartValve™ - Gravity



The company reserves the right to alter, change or modify the product or product specifications without prior warning.
Please refer to the installation guides for technical information.

Issue 01 February 2025

AQUALISA

S3 SINGLE OUTLET SMART SHOWER

S3C.H.P

S3MB.H.P

S3BB.H.P

S3GG.H.P

WITH WI-FI CONNECTED TECHNOLOGY AND HD MULTI-FUNCTION DISPLAY, ADJUSTABLE HANDSET

GRAVITY

Chrome / Matt Black / Brushed Brass / Gunmetal Grey

TECHNICAL SPECIFICATIONS

Minimum pressure requirements	For optimal performance the Aqualisa SmartValve™ should be sited 1m below the base level of the cold water system (Gravity)
Maximum pressure requirements	1 Bar (Gravity)
Aqualisa SmartValve™ inlet fitting connections	15mm push fit fittings, valve inlet centres 47.5mm, inlet supply positions – hot right, cold left
Aqualisa SmartValve™ outlet fitting connection	15mm push fit
Permissible Aqualisa SmartValve™ siting location	Airing cupboard, under bath, loft
Supply temperature	Cold inlet temperature 1°C (minimum) Cold inlet temperature 15°C (maximum) Hot inlet temperature 65°C (maximum)
Water system	Gravity
Features	Fully customisable advanced high definition digital display
	Temperature and flow control dial with lighting indication, divert between outlets including pre-set temperature and flow
	Glass faceplate and metal dials including edge and mood backlighting, adjustable via app
	Auto 'wake up' and digital display to let you when know your chosen temperature has been reached
	Wifi, Mobile App, Google Home & Amazon Alexa enabled to allow you to control your shower remotely including profile selection and personalised user interface
	120mm 3 spray adjustable head with push button spray selector
	Optional multi-function wired remote control
Guarantee period	5-year guarantee - shower unit
	2-year guarantee - shower head and kit
Approvals	CE Marking
	UKCA
	BEAB

The company reserves the right to alter, change or modify the product or product specifications without prior warning.
Please refer to the installation guides for technical information.

Issue 01 February 2025