

BASECRETE

FLEXIBLE WATERPROOFING BOND COAT

FLEXIBLE CEMENTITIOUS WATERPROOFING & BOND COAT SYSTEM

Simple to mix and even easier to apply, one kit consists of a 5-gallon bucket of our resin and 3-50lb bags of compound.

BASECRETE is a waterproofing bond coat /underlayment/micro-topping for use in all applications where a solid and durable waterproof barrier is required. **BASECRETE** will adhere to most surfaces, is resistant to most chemicals and corrosive agents, and can withstand a high degree of movement while maintaining its integrity. **BASECRETE** protects structures and all water containment vessels from corrosives penetrating the substrate.

WHY USE BASECRETE:

- **Dual-Purpose Solution:**

Acts as BOTH the waterproofing and bond coat membrane. Apply 1 coat for bond coat and 2 coats to create a solid and durable waterproof bond coat.

- **Superior Protection:**

Stops water, chlorides, and other acidic elements and resists most chemicals, sunlight, salt, and other corrosives. It's completely resistant to the chemicals used in pool maintenance and high traffic substrates, and is suitable for freeze thaw climates.

- **Versatile Adhesion:**

Adheres to most surfaces including,

but not limited to, acrylics, cement, stone, metals, glass, ceramic, porcelain, ICF, XPS, EPS, wood, etc.

- **Structural Repair:**

Can be used to repair cracking and spalling. Repair structures that have already suffered deterioration as a result of water infiltration, spalling, and/or the effects of corrosive agents.

- **Environmentally Friendly:**

Eco-Friendly with low VOC's and is safe for drinking water contact.

- **Effortless Application:**

Simple to apply with a roller, trowel, squeegee, or sprayer. Apply with no priming or bond coat needed.



Optimal Coverage:

Coverage is approximate for one coat. Slump can be adjusted to accommodate specific job requirements by adjusting the liquid or the compound.

A. Trowel:

1 gallon & 1 × 50 lb bag =
80–100 sq ft @ 1/16" or 40–50 sq ft @ 1/8"

B. Roller:

5 gallons & 3 × 50 lb bags =
450–500 sq ft @ 1/16" or 225–250 sq ft @ 1/8"

C. Squeegee:

5 gallons & 3 × 50 lb bags =
450–500 sq ft @ 1/16" or 225–250 sq ft @ 1/8"

D. Spray:

5 gallons & 3 × 50 lb bags =
400–500 sq ft @ 1/16" or 225–250 sq ft @ 1/8"

NOTHING BEATS  BASECRETE

8255 Consumer Ct, Sarasota, FL, USA 34240 | basecreteusa.com | info@basecreteusa.com | (941) 312-5142

BASECRETE

FLEXIBLE WATERPROOFING BOND COAT




EXPANDED APPLICABILITY

Whether it's high-rise buildings or the depths of swimming pools, **BASECRETE** products provide a waterproof barrier that resists cracking, corrosive chemicals, and protects any cement structure. With the fastest application and cure times in the concrete industry, it's the ultimate waterproofing solution for any concrete surface.

Elevate Your Projects to the Extreme with BASECRETE


We invite architects, engineers, and construction professionals to discover how **BASECRETE** can transform their projects, offering durable, efficient, and sustainable solutions. Together, we can build the future of waterproofing.

MIX IT • APPLY IT • DONE!




Combine

Pour Basecrete Liquid into a clean pail & add the dry Basecrete Cement Compound.



Blend

Blend with an electric paddle mixer until mixture is uniform. **Let FALSE SET for 4 minutes.**



Apply

Blend for 1 minute and use within 30 minutes. Add more liquid if needed.



Certified to
NSF/ANSI 61

MIAMI-DADE COUNTY
APPROVED



SCAN ME

FOR ESPAÑOL, FRANÇAIS, AND MORE!

NOTHING BEATS  BASECRETE

8255 Consumer Ct, Sarasota, FL, USA 34240 | basecreteusa.com | info@basecreteusa.com | (941) 312-5142