

BOOMER COMPACT TRACTORS

BOOMER25 | BOOMER25C | BOOMER35 | BOOMER50



YOUR JOBS – NOW MADE EASIER

The new Boomer™ compact tractors are the ultimate power tools for small horticulture and agriculture applications, homeowners, rural lifestylers, landscapers, golf courses, municipalities and hobby farmers. Responsive, efficient and comfortable, they're built to make your jobs easier. Available in four models, with power output from 23 to 47 hp, Boomer tractors give you big-tractor reliability wrapped in a compact, maneuverable package. They're loaded with features that keep you comfortable while saving you time and money.

THE POWER YOU NEED

Quiet, fuel-efficient three and four-cylinder engines give you the power you need for mowing, digging, cultivating, and much, much more. You get fast implement response and steering thanks to the high-capacity, dual-pump hydraulic system.

OPERATING EASE

The word “easy” defines Boomer tractors. Controls come easily to hand, the seat and steering wheel adjust to match every operator, and the large, uncluttered operating platform gives you plenty of legroom to stretch out. Controls are color-coded and clearly marked so you are confident of your every move.

SIMPLE SERVICE

Boomer tractors are easy to maintain. Checkpoints are easy to reach and the flip-up bonnet gives you complete access to the engine, battery, radiator and air filters.

SYNCHRONISED COMFORT

The Boomer 35 features a 12x12 synchronised shuttle shift (SSS) transmission as standard, while the Boomer 50 model has a 16x16 SSS transmission. Both transmissions are made for smooth shifting. Because shuttle shifts are synchronised, there's no need to come to a complete stop before shuttling from forward to reverse, and the convenient shuttle lever located to the left of the steering wheel makes it easy.

HYDROSTATIC CONVENIENCE

The Boomer 25 and 25C are equipped with a 2-range hydrostatic transmission with two separate forward and reverse pedals, while a 3-range hydrostatic transmission is available on the Boomer 35 to Boomer 50 models. All Boomer tractors with hydrostatic transmissions make shuttling and choosing the right speed very easy. In addition, all hydrostatic transmissions run smoothly and quietly.



READY FOR ANY JOB

Whether you need to mow the lawn, top a paddock, dig a drain, cultivate the garden, clean a stable yard or install a fence, Boomer tractors are for you. These tractors make it easy to change implements so you can move quickly from job to job. All Models offer Independent, Electro hydraulic 540-rpm rear PTO and Category 1 three point hitch.

Boomer 25 and 25C models offer:

- Independent Electro Hydraulic Mid Mount PTO as standard equipment.
- One rear hydraulic remote available as optional equipment.
- Mid mount valve and joystick available as optional equipment.
- Loader, mower, Backhoe combo on the Boomer 25C.

Boomer 35 and 50 models offer:

- One rear hydraulic remote standard, second rear remote valve
- available as option.
- Mid Mount valve and joystick standard.
- Mid Mount PTO available as optional equipment.
- Cab option on Boomer 50.

PROVEN MANOEUVRABILITY AND TRACTION

Your Boomer tractor is designed to get you in and out of tight spots. It manoeuvres easily around and, thanks to generous ground clearance, over obstacles. Four-wheel drive gives you the traction you need to get through rough patches. When the going gets tough, simply step on the differential lock foot pedal and both rear wheels lock together for added traction to get through mud or rough, slippery ground..

THE BEST VISIBILITY

The sloped bonnet of Boomer tractors not only looks great, it makes your job easier with phenomenal forward visibility. Your view is enhanced with a lighting package that's the best in the business, illuminating your work area to both front and side to make you more productive and safe when operating in the early



Boomer Models		BOOMER 25	BOOMER 25C	BOOMER 35	BOOMER 50
Engine					
Rated power (hp/kW)		27 / 20.1	24.7/18.4	38 / 28.3	46.4 / 34.6
Rated Speed (rpm)		2700	3000	2700	2600
Type		3-cylinder diesel	share '3-cylinder diesel'	4-cylinder diesel	
Displacement (L)		1.3	1.27	1.8	2.5
Air cleaner		Replaceable dry element			
Fuel tank (L)		25	25	33	36
Alternator (amps)		50	40	50	50
Transmission					
Type - Mechanical gearbox		-		I	I
Gears		-		12 x 12	16 x 16
Shuttle type		-		Syncho	Syncho
Gear speed (kph), R4 Industrial -		-		1.2 - 23.8	1.0 - 24.4
Type - Hydrostatic		I	I	I	I
Ranges		2	2	3	3
Shuttle Twin pedal		I	I	I	I
HST Speed range (kph), R4 Industrial		0 - 15.2	0-13.3	0 - 24.8	0 - 22.7
Cruise Control on hydrostatic transmission		I	I	I	I
Rear diff. lock engagement		Mechanical / foot			
Brake type		Mechanical / Wet, multi disc			
Hydraulics					
Implement hydraulic flow (lpm)		22.9	17.1	30.1	29
Steering hydraulic flow / HST (lpm)		9.5	8	16.2	15.6 / 20.8
Rear Remote valve Std/Opt		O	O	1/2	1/2
Mid mount valve/ joystick		O	O	O	O
3-point lift capacity @ ball ends (kg)		650	450	820	1250
3-point linkage category		1	1	1	
Steering type		Hydrostatic			
PTO					
Rear PTO		I	I	I	I
Mid PTO		I	I	O	O
PTO speed (rear) (rpm)		540			
PTO speed (mid) (rpm)		2000	2500	2000	2000
PTO type		Independent Electro - hydraulically engaged			
Dimensions (W/R3 Tyres)					
Wheelbase (cm)		150	143	167	176
Overall length (cm)		263.2	258	301	307
Height to top of ROPS frame (cm)		217.3	236	232	245
Weight (kg)		772	650	1451	1725
Tyre choice		Agricultural, Turf or Industrial	Turf or Industrial	Agricultural, Turf or Industrial	Agricultural, Turf or Industrial
Tractor class		2	1	3	4

I Standard O Optional – Not available (a) Gear speed range (b) HST speed range



SCAN TO LEARN MORE

The data indicated in this folder are approximate. The models described here can be modified without the manufacturer's notice. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please get in touch with our Dealer Network for any further information. Published by CNH Industrial. Printed for New Zealand - 11/22 - NZ/1004