

The COSMO BULLY™ UL Series Rotary Hoe suits compact and subcompact tractors rated between 15 and 40 horsepower. It is designed for virgin soil preparation in garden plots, hobby farms, vineyards and narrow crop rows. This implement is well-suited to operators working in confined areas where precision and manoeuvrability are important.

A gear-driven transmission powers the rotor at 245rpm, delivering consistent torque to the blades. The rotor features a forward-action layout with six C-curved blades per flange, mounted in a staggered pattern to support continuous soil engagement and even refinement. This configuration helps reduce horsepower demand while maintaining effective soil turnover. A friction clutch helps manage load during heavier ground conditions.

The rear deflector is chain-supported and self-levelling, helping to leave a smooth finish after each pass.

Side transmission

Gear-drive transmission for increased power transfer to the blades and ground. Includes an oil-level sight glass.

Front parking stand facilitates connection to tractor.

Skids

Four positive-locking positions with individual bolt holes.

3-Point linkage

Category 1, quick-hitch compatible, double clevis mount.

Powder-coated finish.

CE-compliant guarding.

Blades

C-curved blades excel in cutting, turning, and refining softer or looser soil types. Their smoother cutting action requires less horsepower to produce a finer finish.

Code	TBUL36	TBUL48	TBUL60
Size reference	0.91m 3'0" 36"	1.2m 4'0" 48"	1.5m 5'0" 60"
Tractor range (hp)	15 - 40 12.5 - 33 @ PTO	20 - 40 17 - 33 @ PTO	30 - 40 25 - 33 @ PTO
Gearbox	40hp, 540rpm, single speed		
PTO shaft/clutch	Series 4 with 150mm (6") friction clutch		
Rotor	speed 245rpm shaft Ø375mm		
No. of rotor flanges	4	6	7
No. of blades p/flange	6		
Total no. of blades	24	36	42
Overall width (mm)	1035	1340	1645
Working width (mm)	915	1220	1525
Working depth (mm)	165		
Weight (kg)	153	180	200
Price			