

Swift Roller Mower

Winged, Trailed

Offering the same qualities found in the three-point linkage models, the Swift trailed winged roller mower is designed to meet – and exceed – the requirements to maintain vast areas of grass for contractors, turf farms and local authorities.

Unlike other machines on the market, these wide area mowers are fitted with brakes and an LED lighting kit as standard to ensure safe transport between sites.

High-performance Strenx™ 700 MC structural steel makes these roller mowers strong. Combined with hot-dip galvanisation to EN ISO 1461:2009 specifications, these roller mowers outlive most of its competitors and retain their values.



Take a 360° virtual tour



“



Phil's Story

The blades chop the clippings and spreading them evenly - they don't take long to disappear with no windrows. There are no belts - just a heavy-duty driveline. For a big machine, it is far more manoeuvrable than I expected. It also consumes very little power - and is very economical with fuel.”

Phil Cole, Contract Ground-keeper, Cirencester Polo

FEATURES

- Simple height adjustment from 10-130mm for versatile and year round mowing
 - The gearbox driveline eliminates the problems associated with belt-driven mowers.
 - Walterscheid wide-angle PTO shafts
 - Oil filled sealed internal roller bearings for total protection against moisture, soil and debris.
 - LED road lighting kit and fully braked for safe and legal road work
 - 3-year MAJOR warranty
- Option for Racecourses**
- Standard roller fitted to the rear and a modified roller to the front
 - Castor wheels (1 per wing) to the front for superior cutting in a variety of grass heights



Option of a castor wheel per wing for racecourse applications.



Two in one blade system, rigid and swinging.



10-130mm height adjustment for year round mowing.

MODEL	MJ71-400T	MJ71-540T	MJ71-600T	MJ71-730T
Overall Width	4.16m (13' 8")	5.54m (18' 2")	6.21m (20' 5")	7.42m (24' 5")
Working Width	4.00m (13' 1")	5.40m (17' 9")	6.00m (20')	7.30m (24')
Transport Width	2.40m (8')	2.40m (8')	2.60m (8' 6")	2.60m (8' 6")
Power (HP)	60-110 HP	70-120 HP	90-130 HP	105 - 150 HP
PTO rpm	540	540	1000	1000
Cutting Height	10-130mm	10-130mm	10-130mm	10-130mm
Rotors	6	8	9	11
Blades	12	16	18	22
Weight	1665kg	1830kg	2025kg	2270kg
Blade tip speed	75 m/s	75 m/s	70 m/s	70 m/s
Mowing Rates (Acres/hr at 7mph)	11.4	14.9	16.8	20.4