



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure DWPQ



Selected product

- Article no.: 6202368002 + 1046969
- EAN code: 7630029443750 + 7630029428979
- Type: DWPQ12g
- Product category: Range hood
- Telescopic casing: Standard
- Standard width: 120 cm
- Front design: Black glass
- Installation method: Wall hood
- Recirculation air filter: Long-life activated charcoal filter



Details DW PQ12

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: DWPQ12g
- Product category: Range hood
- Telescopic casing: Standard
- Standard width: 120 cm
- Front design: Black glass
- Installation method: Wall hood
- Recirculation air filter: Long-life activated charcoal filter

Dimensions

- Device height exhaust air: 460 mm
- Device height exhaust air maximum: 660 mm
- Device height recirculation air: 570 mm
- Device height recirculation air maximum: 770 mm
- Front height: 55 mm
- Appliance width: 1198 mm
- Appliance depth: 550 mm
- Max. appliance depth: 550 mm
- Empty weight: 29 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Consumption when off: 0 W
- Energy efficiency rating: A+
- Annual energy consumption: 29.7 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 36.3
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 3 x 2 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.14 kW
- Fuse protection (1): 10 A
- Plug type: SII32
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- SilentPlus
- Activated charcoal filter saturation indicator
- Telescopic casing: Standard
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Fleece grease filter: 4
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: included

Functions

- ComfortFix
- Grease filter cleaning indicator
- Recirculation air
- Activated charcoal filter saturation indicator
- SilentPlus
- Cleaning lock
- Intensive setting
- Automatic after-running time

**Additional data**

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 33
- Illumination on cooking surface: 196 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 880 m³/h
- Extracted air output, max. setting: 670 m³/h
- Extracted air output, min. setting: 247 m³/h
- Recirculation air output, intensive setting: 570 m³/h
- Recirculation air output, max. setting: 389 m³/h
- Recirculation air output, min. setting: 210 m³/h
- Extracted air noise output, intensive setting: 70 dB(A)
- Extracted air noise level, max. setting: 63 dB(A)
- Extracted air noise output, min. setting: 50 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 1
- Motor output: 130 W
- Feature level: 5