



Dishwasher

DFI747U/1

Energy efficiency class: A

Style

Series 8

Noise level (max) dB(A): 38

Number of place settings: 14 pcs

Number of baskets: 3

Size: XL, 820 mm

Turbo Combi Drying™ ensures dry dishes with fan assisted evacuation of moisture in combination with Auto Door Opening

Installation: Fully integrated



Construction and performance

- 8 Steel™ - Vital parts of the dishwasher made in stainless steel: Yes
- No need to rinse the dishes thanks to Super Cleaning System™: Yes
- Automatic water-softener for better washing performance: Yes
- Number of spray arms: 3 pcs
- Number of spray zones: 9
- Cleaning systems: Cutlery Spray™ - Extra dishwashing power for the cutlery basket, No need to rinse the dishes thanks to Super Cleaning System™, Aqua Level™ Sensor, Sensi Clean™ Sensor - measures dirtiness level, Stainless steel spray arms, Adjustable power zones that can be set for cleaning Pots & Pans or Bottles & Vases. Can also be turned off., The water pressure is adapted depending on program, type of dishes and dirtiness level.

Use and flexibility

- Number of place settings: 14 pcs
- Number of baskets: 3
- Top tray: Easy height adjustment, With telescopic rails, Handle, Removable, Guide rails with ball bearings
- Upper basket type: Exclusive - Basket wiring in steel, all pin rows foldable, divisible/foldable wine shelves, Light Lock™ for fastening lightweight items
- Upper basket system: Easy height adjustable with lever
- Upper basket: Dividable pin rows, Wine glass fixings in TPE, Sliding tines for easy adaptation to stone ware etc., Perfect ergonomics with easy sliding telescopic rails, Light Lock™ for fastening lightweight items, China Guard - Protects fragile load from the rotating spray arm, Extra wide knife stand, Two foldable glass supports, Divisible/foldable wine shelves to left, Foldable wine shelves to right, Handle with ASKO logo, Small distance between the basket threads - makes loading easy and prevents small items to fall through
- Middle basket: Without middle basket
- Lower basket type: Exclusive
- Lower basket: Small distance between the basket threads - makes loading easy and prevents small items to fall through., Handle with ASKO logo, Foldable/divisible rear pin row, Foldable/divisible front pin row, Vase/bottle holder for cleaning vases/baby bottles, Cutlery basket, Sliding tines for easy adaptation to stone ware etc.
- Automatic dosing system: Yes, integrated
- Interior light: Yes, 2 LED lights

Interaction and control

- Wifi: Yes
- Type of display: Graphic TFT display
- Status Light™ - Visual indication of dishwashing progress: Yes, floor projection
- Remaining time indication: Yes
- Wash end indication: Displayed with sound and light
- Available languages in control unit: Ukrainian, Swedish, Serbian, Slovenian, Slovak, Russian, Portuguese, Polish, Norwegian, Dutch, Latvian, Lithuanian, Japanese, Italian, Croatian, French, Finnish, Estonian, Spanish, English, German, Danish, Czech

Functions, programs and modes

- Programs: Anti odour, Self cleaning, Quick Pro wash, Crystal glass, Lower half, Upper half, Universal programme, Rinse and hold programme, Plastic wash, Time program, Hygiene wash, ECO wash, Auto wash, Intensive program
- Main wash temperature (°C): 45/50/55/60/65/70
- Delayed start: Possible to delay up to 24 hours
- Options and modes: Enable/disable automatic door opening, Super Rinse™ - Two extra rinses, Time set, Green mode - Less energy and water is used. The program time is extended, Speed mode - The program time is shortened. More energy is used., Night mode - Lower noise level. The program time is extended., Intensive mode - The dishwasher uses more heat and water. The program time is extended, ExtraHygiene with UV Technology, Sensor controlled door opening - Optimizes the drying process according to the room temperature, Push to open - Handle-free door opening, Light sabbath mode

Design and integration

- From the front adjustable door spring: Yes
- From front adjustable rear foot: Yes
- Installation: Steam protection strip, Integrated anti-siphon - Prevents spontaneous in- and outlet of water and simplifies elevated installation, Velcro strips for easy mounting and adjustment of the separate custom door
- Sliding door: No
- Possible to install elevated: Yes
- Custom door size: Custom door size 680-760
- Min. niche width: 600 mm
- Min. niche height: 820 mm
- Depth (incl. wall spacing): 555 mm
- Max Height adjustment: 53 mm
- Adjustable kick plate: No

Safety and maintenance

- Aqua Safe™: Sealing points outside container, Extra durable stainless steel container, Waterproof bottom plate, Detection of water leakage on the bottom plate, Aqua Detect™ - Instant recognition of any leakage in the motor compartment, Aqua Level™ Sensor - Ensures an optimized water level, Stand-by water protection - Leakage detection when machine is off, Maximum time for water intake, Light and sound alarm, Anti Block™ - Self cleaning drain pump
- Aqua Safe™ system: Yes
- Child safety: Kid Safe™ - Lockable controls
- Indication of low level of rinse-aid: Notification in display
- Salt refill indicator: Notification in display

Technical data

- Water connection: Hot&cold water
- Adapter for water connection: 1/2
- Max. temperature of inflow water: 70 °C
- Noise level (max) dB(A): 38
- Reference programme: 1
- Energy label program time: 275 min
- Energy consumption per cycle for the Eco program 40-60 °C: 0.54 kWh
- Water consumption per cycle for the Eco program: 9.4 l
- Consumption in standby mode: 0.49 W
- Energy efficiency class: A
- Plug type: Euro
- Connected load: 1900 W
- Voltage (V): 220-240 V
- Number of phases: 1
- Fuse: 10 A
- Frequency: 50 Hz
- Required inlet water pressure MPa: 0,3-1
- Net weight: 43 kg
- Noise class: A
- Energy Efficiency Index (EEI): 31.8
- Cleaning performance: 1.121
- Drying performance: 1.061


- Start delay (W): 3.99
- Networked standby: 1.99 W
- Energy consumption per 100 cycles: 54 kWh

Dimensions

- Width: 596 mm
- Height: 819 mm
- Depth: 554 mm
- Maximum product height: 872 mm
- Length of electrical cord: 1730 mm
- Depth with door open: 1191 mm
- Length inlet hose: 175 cm
- Length outlet hose: 200 cm

Logistic information

- Packaging width: 640 mm
- Packaging height: 890 mm
- Packaging depth: 680 mm
- Gross weight: 46.3 kg
- Product code: 746108
- EAN code: 3838782989940



Fully integrated dishwasher XL Floor projection

