

ROQSTAR Unmanaged Ethernet Switch

8 Ports / M12

Product number 006-130-100



Features & Applications

- 10/100 Mbit/s
- Plug & Play
- For simple networks
- Additional network nodes



Technical Specifications

Connectors

M12 d-coded Ethernet ports	8 x 10/100 Mbps
M12 a-coded male	1 x power supply

MTBF

25°C	1 273 723 hrs
60°C	476 965 hrs

Physical

Enclosure	Aluminium, die-cast
Protection class	IP54
Installation	Wall mount/any orientation
Dimensions (W x D x H)	175 x 52 x 121 mm
Weight	550 g

Power

Power consumption	max. 5.0W
Operating voltage	16 - 60VDC
Power supply input	V1, V2 dual, polarity protected

Environment

Ambient temperature operating	-40°C ... +70°C
Ambient temperature storage	-40°C ... +85°C
Ambient humidity	10% ... 90% non condensing
Shock and Vibration	IEC 61373

Approvals

E-Mark EMC	EN50121-3-2, UN ECE R10
Environment	EN50155
E-Mark fire protection	EN45545, UN ECE R118
IBIS-IP	Compliant
ITxPT	Laboratory test compliant

LED display

Power LEDs	V1, V2
Ethernet port LEDs	Link/activity

Drawings

