

Insulated Panels
CEME Division

ems Thermowand EC

Product Data Sheet




Product Overview

ems Thermowand EC panel is visibly screwed and has an IPN insulation core as well as a special joint geometry but is supplied from the factory without sealing tape. It is suitable for efficient wall solutions and enables quick and easy installation.

Application

ems Thermowand EC Coldstore Panel is ideal for use in temperature-controlled and hygienically safe environments such as food processing, cold storage and fresh food logistics, clean rooms, biotechnology and the pharmaceutical industry.

Panel Cross Section



Technical Parameters

The ems Thermowand EC Coldstore Panel has been tested and approved to comply with EN 14509:2013.

Module width/Cover width [mm]	Core Thickness [mm]	Mass	Thermal Transmittance (U-value) acc. EN 14509:2013 [W/m ² ·K]	Thermal Transmittance (U-value) acc. EN ISO 6946:2017 [W/m ² ·K]	GWP for modules A1-A3	GWP for modules A-C
1,150/1,150	80	12.38 kg/m ²	0.27	0.27	33.8 kg CO ₂ -eq./m ²	45.3 kg CO ₂ -eq./m ²
	100	13.14 kg/m ²	0.22	0.21	35.7 kg CO ₂ -eq./m ²	48.9 kg CO ₂ -eq./m ²
	120	13.9 kg/m ²	0.18	0.18	37.9 kg CO ₂ -eq./m ²	52.8 kg CO ₂ -eq./m ²
	150	15.04 kg/m ²	0.15	0.14	41.3 kg CO ₂ -eq./m ²	60.7 kg CO ₂ -eq./m ²
	170	15.8 kg/m ²	0.13	0.13	43.3 kg CO ₂ -eq./m ²	64.6 kg CO ₂ -eq./m ²
	200	16.94 kg/m ²	0.11	0.11	45.2 kg CO ₂ -eq./m ²	67.8 kg CO ₂ -eq./m ²

The technical data is valid for a face thickness of Ext / Int. 0.60 / 0.50 mm.

Dimensions

Length

Shorter lengths (non-standard) [mm]	270-1799
Standard lengths [mm]	1800-14500
Longer lengths (non-standard) [mm]	14500-18000

Additional costs and transport restrictions may apply for non-standard trucks (> 13,50 m).

Width

The standard module width is 1,150 mm and cover width 1,150 mm.

14509:2013, attachment D.

Length tolerance	L≤3m, -	5 mm
Length tolerance	L≤3m, +	5 mm
Length tolerance	L>3m, -	10 mm
Length tolerance	L>3m, +	10 mm
Cover width tolerance	-	2 mm
Cover width tolerance	+	2 mm
Thickness tolerance	-	2 mm
Thickness tolerance	+	2 mm
Thickness tolerance	D>100mm, -	2 %
Thickness tolerance	D>100mm, +	2 %
Deviation from squareness		0.006 x w
Deviation from straightness (on length)		1mm/m, maximum 5 mm/m

Product Tolerances

Product tolerances are measured according to the standard EN

Materials

Insulation Core

Polyisocyanurate (IPN 3) insulation core with a Thermal

Conductivity (λ_p) of 0.022 W/m-K according to EN 14509:2013.

External facing

The standard thicknesses of the coil coated steel sheet are 0.60 mm. On request also 0.50 mm steel sheet thicknesses available. Standard coating: Polyester (25 μ m) – PES. Optional: Foodsafe (150 μ m) – for applications with increased hygienic requirements. The special FS3000 and FS4000 coating is also available as an option for use in food processing and exclusively for interior applications.

Internal facing

The standard thicknesses of the coil coated steel sheet are 0.50 mm. On request also 0.40 mm or 0.60 mm steel sheet thicknesses available. Standard coating: Thin film coating (15 μ m). Optional: Polyester (25 μ m) – PES or Foodsafe (150 μ m) – for applications with increased hygienic requirements. The special FS3000 and FS4000 coating is also available as an option for use in food processing.

Seals

The ems Thermowand EC panel is supplied from the factory without sealing tape. Any sealing of the tongue and groove areas that may be required for a specific project is carried out on site.

Profilings

The available profilings can be found in the corresponding profiling table further back in the document.

Colours

The colours available can be found in the 'Colours and Coatings' brochure.

Fire Performance

The ems Thermowand EC panel has been tested and approved to comply with EN 14509:2013. Product technical specifications relating to fire classification are available from Kingspan Technical Support. For FM Approved product specifications please contact ems Technical Support.

Module width/ Cover width [mm] / [mm]	Core Thickness [mm]	Reaction to Fire
1,150/1,150	80	B-s1, d0
	100	B-s1, d0
	120	B-s1, d0
	150	B-s1, d0
	170	B-s1, d0
	200	B-s1, d0

Mechanical Resistance

For load / span tables, please refer to the 'Span table' on our website or contact our Technical Support.

Environmental Performance

Our production facilities generate renewable energy onsite

which contributes to that sites energy mix. Kingspan Insulated Panels source steel with 15-25% recycled content. Kingspan Insulated Panels directly contribute to BREEAM® and LEED® credits.

Production Standard

Kingspan Insulated Panels apply to the European Standard EN 14509:2013 self-supporting double skin metal faced insulating panels.

Quality

ems Insulated Panels are manufactured to rigorous quality control standards, complying with ISO 9001:2015 Quality management systems standards, ensuring long term reliability and durability. The panels are also manufactured under Environmental management system certification EN ISO 14001:2015 and Occupational health and safety certification EN ISO 45001:2018. The ems Thermowand EC panel is CE marked to EN 14509:2013.

Packing

Standard Packing - Road Transportation

ems Thermowand EC panel is stacked weather side to internal side. The top, bottom, sides and ends are protected with foam and polystyrol packing and the entire palette is wrapped with protection film. The number of panels in a pack depends on panel thickness and length. Quantities are reduced for exceptionally long panels.

Core Thickness [mm]	80	100	120	150	170	200
Number of Panels	13	11	9	7	6	5

Delivery

All deliveries are by road transport to a project site unless otherwise indicated. Unloading is the responsibility of the customer. Please refer to our 'Handling & Assembly' brochure.

Sea Freight

Full timber crate packs are available at extra cost for projects requiring sea freight delivery. Alternatively steel containers can be used. Special loading charges apply.

Site Storage & Installation

For site storage and installation instructions please refer to our 'Handling & Assembly' brochure and the 'Guideline for the planning and implementation of roof, wall & ceiling constructions made from proled metal panels' of the IFBS.

Guarantee

Guarantees are individually assessed for each project, depending in particular on the aggressiveness of the environment and the type of surface treatment chosen.

Profiles

Profile	External	Internal
B - Box		
E - Eurobox		
F - Flat		
M - Micro		
Q - Minibox		
W - Wave		
D - Deep		

Contact Details

ems®

Kingspan GmbH

Am Schornacker 2 | 46485 Wesel | Germany

T: +49 281 95 25 0-0

F: +49 281 95 25 0-50

E: info@kingspan.de

www.kingspan.de



[Click here](#) for the most up to date version of this document.

The information provided in this datasheet is accurate as of its date of publication and represents our commitment to quality and transparency. However, Kingspan Insulated Panels reserve the right to modify product specifications without prior notice to reflect advancements or improvements. For applications not explicitly covered within this datasheet, consultation with our Technical Advisory Service is strongly advised to ensure the product meets your specific requirements. Customer are responsible for verifying the product's suitability for their particular needs and for ensuring compliance with all applicable laws and regulations. We reserve the right to update this datasheet, and any other informational materials, at our discretion and without notice. For the latest information, please visit: www.ems-bau.com
QuadCore®, Hoesch® and ems® are all Registered trademarks of Kingspan Group plc in United Kingdom, Ireland, and other Countries. All rights reserved.

