


Reface™ AST® L Renovation Wall Panel

Product Data Sheet





Product Overview

The Reface™ panel is installed directly on top of an existing wall structure. It significantly reduces the time required for renovations because you do not need to remove old walls to start with. Additionally, the use of the property can continue practically uninterrupted during panel installation. The internal steel facing is "breathable", or open to diffusion, allowing for a substantially faster installation process to speed up any renovation.



Panel Cross Section



Technical Parameters

Module width / Cover width [mm]	Nominal Thickness [mm]	Mass [kg/m²]	Thermal Transmittance (U-value) acc. EN 14509:2013 [W/m²·K]	R [m²K/W] Thermal Resistance as per EN 14509:2013 with effect of joint [m²K/W]	Airborne Sound Insulation $R_w(C;C_v)$	Weighted Sound Absorption Coefficient $[\alpha_w]$	GWP for modules A1-A3 [kg CO2-eq./m²]	GWP for modules A-C [kg CO2-eq./m²]
1,200 / 1,196	80	15.31	0.45	2.09	NPD	NPD	28.1	33.7
	100	16.71	0.37	2.61	NPD	NPD	28.4	30.0
	120	18.11	0.30	3.14	NPD	NPD	29	30.7
	150	20.21	0.24	3.93	NPD	NPD	29.9	31.6
	175	21.96	0.21	4.59	NPD	NPD	30.5	32.3
	200	23.71	0.18	5.24	NPD	NPD	31.4	33.2
	240	26.51	0.15	6.30	NPD	NPD	32.3	34.2
	300	30.71	0.12	7.87	NPD	NPD	34.1	36.1

The technical data is valid for a face thickness of Ext / Int. 0.60 / 0.50 mm

Fire Performance

Product technical specifications relating to fire classification are available from Paroc Panel System Technical Support.

Module width / Cover width [mm]	Nominal Thickness [mm]	Reaction to Fire	Fire Resistance - External Wall - Horizontal	Fire Resistance - External Wall - Vertical
1,200 / 1,196	80	A2-s1, d0	NPD	NPD
	100	A2-s1, d0	NPD	NPD
	120	A2-s1, d0	NPD	NPD
	150	A2-s1, d0	NPD	NPD
	175	A2-s1, d0	NPD	NPD
	200	A2-s1, d0	NPD	NPD
	240	A2-s1, d0	NPD	NPD
	300	A2-s1, d0	NPD	NPD

¹ See details in the relevant classification reports and/or in technical documentation available on request.

³ Class is not defined in standard EN 13501-2 for this application, but the product meets its criteria.

Dimensions

Length

Shorter lengths (non-standard) [mm]	200-1499
Standard lengths [mm]	1500-9000
Longer lengths (non-standard) [mm]	9001-12100

Additional costs and transport restrictions may apply for non-standard lengths.

Width

Module width is 1,200 mm and cover width 1,196 mm.

Product Tolerances

Product tolerances are measured according to the standard EN 14509:2013

Length tolerance	L ≤ 3m, -	5 mm
Length tolerance	L ≤ 3m, +	5 mm
Length tolerance	L > 3m, -	10 mm
Length tolerance	L > 3m, +	10 mm
Cover width tolerance	-	2 mm
Cover width tolerance	+	2 mm
Thickness tolerance	-	2 mm
Thickness tolerance	+	2 mm
Thickness tolerance	D > 100mm, -	2 %
Thickness tolerance	D > 100mm, +	2 %
Deviation from squareness		0.006 x w
Deviation from straightness (on length)		1mm/m, maximum 5 mm/m

Materials

Insulation Core

Paroc stone wool insulation core with a Thermal Conductivity (λ) of 0.038 W/m·K according to EN 14509:2013.

External facing

The standard thicknesses of the coil coated steel sheet are 0.5 mm and 0.6 mm.

Standard coating: Spectrum®, PVDF, Polyester SP25.

Internal facing

The standard thicknesses of the coil coated steel sheet are 0.6 mm and 0.7 mm.

Standard coating: Polyester SP25.

Seals

Factory applied side joint seals. All side joints have a factory applied seal fitted into the groove to automatically seal the joint between panels.

Panels intended for external walls are usually delivered with an on the production line installed sealant in internal and external grooves.

Panels for high or vertically installed facades always have to be provided with sealant in both grooves of the joint.

Profiles

For available profiles, see the supplementary overview available further down.

Colours

For available colours, please refer to the "Colour Indications" brochure.

Mechanical Resistance

For load / span tables, please refer to the "Technical Guide" brochure or contact Paroc Panel System Technical Support.

Environmental Performance

Paroc Panel System's facilities located in Parainen generate renewable energy onsite which contributes to that sites energy mix.

Paroc Panel System procure steel that is made from 15-25% recycled content.

Paroc Panel Systems products directly contribute to BREEAM® and LEED® credits.

Production Standard

Paroc Panel System applies to the European Standard EN 14509:2013 Self-supporting double skin metal faced insulating panels.

Quality

Paroc Panel System products are manufactured from the highest quality materials, using state of the art production equipment to rigorous quality control standards, complying with ISO 9001:2015 Quality management systems standards.

The panels are also being manufactured under Environmental management system certification EN ISO 14001:2015, Energy management system certification EN ISO 50001:2018, Safety certification EN ISO 45001:2018 and Compliance management system certification ISO 37301:2021.

Packing

Standard Packing - Road Transportation

Reface™ AST® L Renovation Wall Panel is stacked weather side to internal side.

The top, bottom, sides and ends are protected with foam and timber packing and the entire palette is wrapped with protection film.

The number of panels in a pack depends on panel thickness and length.

Quantities are reduced for exceptionally long panels.

Nominal Thickness [mm]	80	100	120	150	175	200	240	300
Number of Panels	15	12	10	8	7	6	5	4

Delivery

All deliveries, unless indicated otherwise, are by road transport to a project site. Off-loading is the responsibility of the client.

Sea Freight

Fully timber crated packs are available on projects requiring delivery by sea freight shipping, at additional costs. Alternatively, steel containers can be used. Special loading charges apply.








Site Storage & Installation

Site storage and installation instructions are available from Paroc Panel System Technical Support.

Warranty

Paroc Panel System's warranty are individually assessed for each project, especially depending on the aggressiveness of the environment and the type of surface treatment chosen.

Profiles

Profile	External	Internal
1 - Line 600		
5 - Line 200		
7 - Line 150		
F - Smooth		
M - Micro profiled		

Contact Details



Paroc Panel System
Sysilahden teollisuusalue 2
Parainen, Fi-21600



[Click here](#) for the most up to date version of this document.

The information provided in this datasheet is accurate as of its date of publication and represents our commitment to quality and transparency. However, Paroc Panel System reserve the right to modify product specifications without prior notice to reflect advancements or improvements.

For applications not explicitly covered within this datasheet, consultation with our Technical Advisory Service is strongly advised to ensure the product meets your specific requirements.

Users are responsible for verifying the product's suitability for their particular needs and for ensuring compliance with all applicable laws and regulations.

For the most up to date and comprehensive product details, always refer to the latest version of this datasheet by scanning the QR code above.

We reserve the right to update this datasheet, and any other informational materials, at our discretion and without notice.

For the latest information, please visit: www.parocpanels.com