

Insulated Panels
Central Asia and Türkiye

Quadcore™ KS110CTF CamLock ColdStore Panel Product Data Sheet



POWERED BY
QuadCore
TECHNOLOGY



Kingspan

Application

The QuadCore™ KS110CTF CamLock ColdStore Panel features a factory-integrated locking system produced through an automated continuous line process. This technology allows locking kit spacings to be adjusted based on specific project requirements, ensuring optimal quality and joint airtightness. Designed with a QuadCore™ insulation core for high energy efficiency, the system is suitable for internal-external walls and ceiling applications in temperature-controlled environments.

Each application should be verified against individual project requirements.

Panel Cross Section



Technical Parameters

Thermal Transmittance (U-Value), calculated by using Finite Element Analysis in accordance with EN 14509: 2013 taking into account the profile geometry of the panel and the thermal influence of the longitudinal joint.

The technical data is valid for a face thickness of Ext / Int. 0.50 / 0.50 mm

Panels with galvanized steel or stainless steel facers have undergone extensive testing, and FM Approvals certification encompasses core thicknesses of 40 to 200 mm (valid for a minimum facer gauge of Ext / Int: 0.47 / 0.47 mm).

FM 4880: Attaining a Class 1 fire rating for building panels or interior finish materials.

FM 4881: Certifying Class 1 exterior wall systems.

FM 4882: Confirming Class 1 interior wall panels suitable for environments sensitive to smoke (such as pharmaceutical manufacturing & storage areas, food preparation & storage areas, or similar spaces).

Fire Performance

The Quadcore™ KS110CTF Camlock ColdStore Panel has been tested and approved to comply with EN 14509:2013.

The reaction-to-fire classification according to EN 13501-1:2018 is presented in the below data table.

Classification reports available on request.

Dimensions

Length

Additional costs and transport restrictions may apply for non-standard lengths.

Width

Standard cover width: 1,100 mm.

Standard module width: 1,100 mm.

Product Tolerances

All product tolerances are in compliance with EN 14509:2013.

Materials

Insulation Core

QuadCore™ Technology insulation core with a thermal conductivity (λ) of 0.020 W/m·K according to EN 14509:2013.

External facing

The standard thickness range of the coil coated steel sheet:

B - Box (IzoCold): 0.45–0.70 mm

Standard coating: Polyester. PVDF and Plastisol.

Internal facing

The standard thickness range of the coil coated steel sheet:

B - Box : 0.45–0.70 mm

Standard coating: Polyester. PVDF and Plastisol.

Seals

Site applied joint sealants are the responsibility of the installer.

Profiles

Available profiles are shown in the Profiles section.

Colours

External colours are available in a wide variety of metallic, matte, and solid finishes. For guidance on selecting the most suitable colours for your project, please contact Kingspan Technical Support.

Mechanical Resistance

For load / span tables, please contact Kingspan.

Environmental Performance

We ensure that our products are free from CFC, HCFC, HFC, and Halogenated Fire Retardants.

Kingspan Insulated Panels are manufactured in facilities certified to the ISO 14001 Environmental management system (EMS) standard.

Production Standard

Kingspan Insulated Panels complies with the requirements of EN 14509:2013 Self-supporting double skin metal faced insulating panels.

Quality

Kingspan insulated panels are manufactured in compliance with the ISO 9001:2015 quality management system standard. The manufacturing process is also certified to ISO 14001:2015 for environmental management and ISO 45001:2018 for

occupational health and safety management.

Packing

Standard Packing - Road Transportation

Quadcore™ KS110CTF Camlock ColdStore Panels are stacked with the external surface facing inward. The top, bottom, side, and end faces of each package are protected with cardboard or polystyrene protectors, and the entire pallet is wrapped with protective stretch film. The number of panels in a pack depends on panel thickness and length. Quantities are reduced for exceptionally long panels.

Protective film on the panels should be removed within a maximum of two months of the production date.

Delivery

All deliveries, unless indicated otherwise, are by road transport to a project site. Off-loading is the responsibility of the recipient.

Sea Freight

Full timber crated packs are available at additional cost for projects requiring sea freight delivery. Alternatively, steel containers can be used. Special loading charges apply.

Site Storage & Installation

The responsibility for unloading the goods lies with the recipient. The goods must not be dropped or thrown from the vehicle and should not be stacked on uneven surfaces.

During unloading, care must be taken to protect the goods from damage and to ensure the safety of personnel on site.

Manual unloading is not recommended. Appropriate lifting equipment, such as a forklift truck or crane fitted with a spreader beam, should be used to prevent excessive pressure on the product, which may result in delamination, joint damage, or surface irregularities.

Please contact Kingspan to obtain guidelines for the safe transportation, unloading and on-site handling of products supplied by Kingspan.

Warranty

Kingspan warranties are assessed individually for each project, depending on the environmental conditions and the selected surface treatment.

Profiles

Profile	External	Internal
B - Box		

Contact Details

Çırağan Cad. No: 97 | Ortaköy 34347 Beşiktaş
İstanbul | Türkiye
T: +90 212 236 60 32
E: enquiry.catl@kingspan.com
www.kingspan.com.tr



For the most up-to-date version of this document please scan or click here.

The information provided in this datasheet is accurate as of its date of publication and represents our commitment to quality and transparency. However, Kingspan Insulated Panels reserve the right to modify product specifications without prior notice to reflect advancements or improvements.

For applications not explicitly covered within this datasheet, consultation with our Technical Department is strongly advised to ensure the product meets your specific requirements.

Users are responsible for verifying the product's suitability for their particular needs and for ensuring compliance with all applicable laws and regulations.

For the most up to date and comprehensive product details, always refer to the latest version of this datasheet by scanning the QR code above.

We reserve the right to update this datasheet, and any other informational materials, at our discretion and without notice.

For the latest information, please visit: www.kingspan.com.tr

