EAP BEAM TROLLEY

Variable anchor devices

Description

The anchor point allows for the secure attachment of energy absorbers with lanyards, fall arrest devices, restraint systems, or work positioning systems. Furthermore, the EAP BEAM TROLLEY is also approved as a mobile anchor point for rope access and positioning techniques. In this case, the user attaches two rope access systems to two separate EAP BEAM TROLLEY units.

Assembly is simple and safe:
The trolley is opened via the folding lock and placed onto the support flange. The roller jaws are then pressed together using the rack until they fit snugly against the support. The locking pin is then inserted into the corresponding hole. Finally, the personal fall protection system can be attached.

The EAP BEAM TROLLEY impresses with its high mobility, ease of use and reliable safety when working at height or using rope access.

Specifications

- Ausführung: Zahnstange und Klemmbacken aus Aluminium.
  Drehbarer EAP aus beschichtetem Legierungsstahl.
  Verstelleinrichtungen aus Edelstahl.
  Rollen mit Kugellager.
- Zertifiziert nach: EN 795:2012 Typ B
- Nennlast: Max: 140 kg



Explanations

Item No.	Designation	Flange width	Flange thickness	Weight
7331929	EAP BEAM TROLLEY	63.5 to 305 mm	Max. 38 mm	3,00 kg

Teufelberger Seil Ges.m.b.H. | Böhmerwaldstraße 20, 4600 Wels, Austria | T +43 (0) 7242 615-0 | E wirerope@teufelberger.com
www.teufelberger.com