HWB

Fall arrest device with swivel suspension

Description

Our fall arrest devices are self-locking devices with an automatic tensioning and retraction mechanism for the lanyard. They consist of an aluminum or plastic housing with a swivel attachment at the top. The retractable lanyards are available as webbing (polyester/Dyneema®) or wire rope. An aluminum attack carabiner is permanently attached to the end of the lanyard. Additional carabiners are available upon request!
Fall absorption is achieved via the internal mechanism (brake). This integrated fall arrest system allows for an extremely short fall distance and reduces the impact force to a minimum (well below 6 kN)! Our fall arrest devices can be used vertically overhead, at working level, as well as horizontally. The lanyard is edge-tested (radius > 0.5 mm)! It is also equipped with a fall indicator! Our fall arrest devices offer the highest possible level of safety for the user!

Specifications

- Ausführung des HWBs: Aluminiumgehäuse / Textilband / Alu-Attack-Karabiner / Drehwirbel
- Zertifiziert nach: EN 360, CNB 11.060 2008 sharp edge type A
- Temperatureinsatzbereich: - 40°C bis + 50°C
- Max. Verwendungsdauer: 10 Jahre
- Nennlast: Max: 136 kg



Explanations

Item No.	Designation	Material	Weight	Dimensions
7333911	HWB 1,8 Band	Aluminium	0,7 kg	237 x 78 x 60 mm
7333912	HWB 2 Bands	Aluminium	0,8 kg	240 x 84 x 61 mm
7333913	HWB 2,8 Band	Aluminium	0,8 kg	240 x 84 x 61 mm
7333968	HWB 3,5 Band	Aluminium	1,1 kg	270 x 88 x 64 mm
7333992	HWB 2,8 Band	Aluminium	0,8 kg	240 x 84 x 61 mm
7333939	HWB 3,5 Band	Aluminium	0,8 kg	270 x 88 x 64 mm

Teufelberger Seil Ges.m.b.H. | Böhmerwaldstraße 20, 4600 Wels, Austria | T +43 (0) 7242 615-0 | E wirerope@teufelberger.com
www.teufelberger.com