30 kN / 35 kN webbing sling

Fastener

Description

The webbing slings with a breaking strength of 30 kN and 35 kN are primarily designed for secure attachment to load-bearing structures. They are also ideal for positioning at various anchor points or as a fall arrest system. The 30 kN sling is made of robust tubular webbing, while the 35 kN sling is made of durable flat webbing. Both versions are available in various lengths and configurations, ensuring maximum safety and flexibility for professional use.

Specifications

- Version: The 30 kN webbing sling is made from a high-quality, flexible tubular webbing made of polyamide. The 35 kN webbing sling is made from a high-quality, robust tubular webbing made of Dyneema.
- Certified according to: EN 354(depending on the length), EN 795 B
- Maximum usage time: 10 years



Execution

Item No.	Designation	Long	Color	Weight
7330130	30 kN webbing sling	0,4 m	red	60 g
7330131	30 kN webbing sling	0,6 m	red	90 g
7330132	30 kN webbing sling	0,8 m	red	120 g
7330133	30 kN webbing sling	1,0 m	red	150 g
7330134	30 kN webbing sling	1,2 m	black	180 g
7330135	30 kN webbing sling	1,5 m	black	210 g
7330136	30 kN webbing sling	2,0 m	black	300 g
7330104	35 kN webbing sling	0,6 m	black	85 g
7330105	35 kN webbing sling	0,8 m	black	100 g
7330106	35 kN webbing sling	1,0 m	black	130 g
7330107	35 kN webbing sling	1,2 m	black	160 g
7330108	35 kN webbing sling	1,5 m	black	190 g
7330109	35 kN webbing sling	2,0 m	black	250 g
7330137	35 kN webbing sling	3,0 m	black	370 g
7330138	35 kN webbing sling	4,0 m	black	490 g
7330139	35 kN webbing sling	5,0 m	black	610 g

*From 2 m in length only approved according to EN 795 B

Teufelberger Seil Ges.m.b.H. | Böhmerwaldstraße 20, 4600 Wels, Austria | T +43 (0) 7242 615-0 | E wirerope@teufelberger.com
www.teufelberger.com