



EU DECLARATION OF CONFORMITY



Copreci S.Coop.
Araba Ibilbidea, 3
E-20550 Aretxabaleta-GIPUZKOA (Spain)
Tlfn: + 34 943034499

Declare under our sole responsibility that the product:

| Model | PIN AENOR | Description |
|----------------|--------------|---|
| T15 T15 EID | 99CT952 | Manually operated valve with a flame supervision device for gas burning appliances |

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106:2022 Manually operated taps for gas burning appliances
- EN 125:2022 Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2019 Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate, on 2021/10/13.

This certificate is valid from 22/08/2023

Iñigo Peñagarikano
Copreci, S. Coop.
Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

| INSTRUCTIONS | |
|---------------------------------|--|
| MODEL | T15 – T15 EID |
| GROUP | 1 |
| PURPOSE | Heaters |
| CHARACTERISTICS | Number of ways: 1 Maximum pressure: 2000 mbar Reference flow: 0.450 m ³ /h air with 1 mbar. pressure drop Nominal diameter: 6 T ^a max.: 80 °C T ^a min.: 0 °C |
| NUMBER OF MECHANICAL CYCLES | 10000 cycles |
| MOUNTING POSITION | multiposition |
| CONNECTIONS | Depending on the manufacturer's requirements. |
| TORQUE OF FITTING OUTLET (max) | 8 Nm (bicone) 15 Nm (flared pipe) |
| TORQUE OF FITTING INLET (max) | 8 Nm (bicone) 15 Nm (flared pipe) |
| PUSHING FORCE (max) | 30 N |
| TURNING TORQUE OF SPINDLE (max) | 0.4 Nm |
| PULL IN CURRENT | Different options: <ul style="list-style-type: none"> • 240 ÷ 110 mA • 200 ÷ 80 mA • 180 ÷ 60 mA |
| OPENING TIME | 2 seg (thermocouple optimal position) |
| CLOSING TIME | < 60 seg |
| PRESSURES RANGE | 8 - 2000 mbar |
| GASES OF USE | 2nd y 3th families |

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use
- Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the “Designed lifetime for safe operation”