

**EU DECLARATION OF CONFORMITY**

***Copreci S.Coop.
Araba Ibilbidea, 3
E-20550 Aretxabaleta-GIPUZKOA (Spain)
Tlfn: + 34 943034499***

Declare under our sole responsibility that the product:

Model	PIN AENOR	Description
SOV MODEL D (DUAL) SOV MODEL S (SINGLE)	99DP1037	Mechanically operated shut off valve for gas burning appliances

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EU/2016/426 A III B (09.03.2016)
- EN 1106:2022
- EN 13611:2022
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate, on 2021/10/13.

This certificate is valid from 2024.02.15

Unai Gerenabarrena
Copreci, S. Coop.
Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical instructions for the installer.

INSTRUCTIONS SOV	
MODEL	<i>SOV Model D and model S</i>
GROUP	1
PURPOSE	<i>Free Standing Cookers</i>
CHARACTERISTICS	<i>Number of ways: 2 or 1 Outlets</i> <i>Maximum pressure: 100 mbar</i> <i>Reference flow: 2,4 m³/h fully open, with air at 20 mbar and 1 mbar pressure drop</i> <i>Nominal diameter: 15</i> <i>T^a max.: 150 °C</i> <i>T^a min.: 0 °C</i>
NUMBER OF MECHANICAL CYCLES	<i>10.000 cycles</i>
MOUNTING POSITION	<i>Appliance Inlet</i>
RANGE OF PRESSURES IN MB	<i>8- 100 mbar</i>
CONNECTIONS	<i>Inlet: Joint, Male G1/2</i> <i>Outlet: Joint Female G1/2 and Biconic</i>
GAS TYPE	<i>1st, 2nd y 3th families</i>
TORQUE OF FITTING OUTLET (max)	<i>35 Nm (Taps Outlet)</i> <i>12 Nm (Oven Outlet)</i>
TORQUE OF FITTING INLET (max)	<i>55 Nm</i>
TORQUE OF 8 LATERAL HOLES (max)	<i>1,4 Nm</i>
TURNING OF 2 UPPER HOLES (max)	<i>1.2Nm</i>

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use
- An inlet strainer must be fitted to prevent the ingress of foreign material (hole dimension not exceeding 1,5mm and prevent the passage of 1 mm diameter pin gauge)
- Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the "Designed lifetime for safe operation"

