

**EU DECLARATION OF CONFORMITY**

Copreci S.Coop.
Araba Ibilbidea, 3
E-20550 Aretxabaleta-GIPUZKOA (Spain)
Tlfn: + 34 943034499

Declare under our sole responsibility that the product:

Model	PIN AENOR	Description
CAM 23900-076	99DL1031	Gaseous Manually operated tap for gas burning appliances

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EU/2016/426 A III B (09.03.2016)
- EN 1106:2022
- EN 13611:2019
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002173 certificate, on 25/04/2019.

This certificate is valid from 22/08/2023

Iñigo Peñagarikano
Copreci, S. Coop.
Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

INSTRUCTIONS	
MODEL	CAM 23900-076
GROUP	TYPE 2
DESTINATION COUNTRIES	EU,NAR,AU
CHARACTERISTICS	Num. of outlets; 2 Nominal diameter: < 10 Reference flow: 0,4 m ³ /h air (1mbar pressure drop) Max. operating pressure: 65 mbar / 1/2 PSI T ^a Max.: 150 °C / 300°F T ^a Min.: 0 °C / 32°F Pushing force: 30 N Turning torque: 0.20 N
SWITCH CHARACTERISTICS	16A 125/250VAC; 1/2HP 125VAC; 3/4HP 250VAC (UL-cUL-CSA) 16 (4) A 125/250VAC (VDE CQC). TERMINALS: MAIL 6,35x0.8 mm
BYPASS ORIFICE	0,20 to 1,10mm orifice diameter.
MOUNTING POSITION	Multi position
GAS TYPE	1 ^a , 2 ^a y 3 ^a families
OUTLET TIGHTENING TORQUE	Union nut; 9-12Nm (7/16-24 UNS-2A) 5-7Nm (M8x1)
INLET TIGHTENING TORQUE	Screw; 1-1.5 Nm
EXPECTED OPERATING CYCLES	40,000 cycle

2. Instruction manual for use and maintenance intended for the user.

- *Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.*
- *Do not pour liquids in the component.*
- *The appliance can only be switched on in the user's presence.*
- *The component must not be manipulated or repaired in any way*
- *In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.*
- *The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance*
- *The installer must check the suitability of the component functions for the intended use*
- *Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the "Designed lifetime for safe operation"*