



EU DECLARATION OF CONFORMITY



Copreci S. Coop.
Araba Ibilbidea, 3
E-20550 Aretxabaleta-GIPUZKOA (Spain)
Tlfn: + 34 943034499

Declare under our sole responsibility that the product:

Model	PIN AENOR	Description
CPMM 17700	99CT949	Manually operated multifunctional valve with a flame supervision device for gas burning appliances

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106:2022 Manually operated taps for gas burning appliances
- EN 126: 2025: Multifunctional controls for gas burning appliances
- EN 125:2022 Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2019: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate first issued on 24/05/2018 and valid until 24/05/2027.

This certificate is valid from 27/02/2026

Iñigo Peñagarikano
 Copreci, S. Coop.
 Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

INSTRUCTIONS	
MODEL	CPMM 17700
GROUP	1
PURPOSE	heaters
CHARACTERISTICS	Number of ways: 3 Maximum pressure: 50 mbar Reference flow: 0.450 m ³ /h air with 1 mbar. pressure drop Nominal diameter: 6 T ^a max.: 105 °C T ^a min.: 0°C
NUMBER OF MECHANICAL CYCLES	10000 cycles
MOUNTING POSITION	multiposition
CONNECTIONS	Depending on the client requirements.
TORQUE OF FITTING OUTLET (max)	8 Nm (bicone) 15 Nm (flared pipe)
TORQUE OF FITTING INLET (max)	8 Nm (bicone) 15 Nm (flared pipe)
PUSHING FORCE (max)	30 N
TURNING TORQUE OF SPINDLE (max)	0.4 Nm
PULL IN CURRENT	200 ÷ 80 mA
OPENING TIME	2 seg (thermocouple optimal position)
CLOSING TIME	< 60 seg
PRESSURES RANGE	8 - 50 mbar
GASES OF USE	1st, 2nd y 3th families

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use
- Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the “Designed lifetime for safe operation”.