



## EU DECLARATION OF CONFORMITY



**Copreci S.Coop.**  
**Araba Ibilbidea, 3**  
**E-20550 Aretxabaleta-GIPUZKOA (Spain)**  
**Tfn: + 34 943034499**

Declare under our sole responsibility that the product:

| Model     | PIN<br>AENOR | Description  |
|-----------|--------------|--|
| LOG 22700 | 99CT958      | Manually operated multifunctional valve with a flame supervision device for gas burning appliances |

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106:2022 Manually operated taps for gas burning appliances
- EN 126: 2012: Multifunctional controls for gas burning appliances
- EN 125: 2022 Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2019: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002173 certificate, on 2021/10/13.

This certificate is valid from 22/08/2023

Iñigo Peñagarikano  
Copreci, S. Coop.  
Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

| INSTRUCTIONS                    |  |
|---------------------------------|--|
| MODEL                           | LOG 22700  |
| GROUP                           | 1  |
| PURPOSE                         | heaters  |
| CHARACTERISTICS                 | Number of ways: 3<br>Maximum pressure: 50 mbar<br>Reference flow: 1.5 m <sup>3</sup> /h air with 1 mbar.<br>pressure drop<br>Nominal diameter: <10<br>T <sup>a</sup> max.: 150 °C<br>T <sup>a</sup> min.: 0 °C |
| NUMBER OF MECHANICAL CYCLES     | 10000 cycles   |
| MOUNTING POSITION               | Multi positional   |
| CONNECTIONS                     | Depending on the oven manufacturer's requirements.   |
| TORQUE OF FITTING OUTLET (max)  | 8 Nm (bicone)<br>15 Nm (flared pipe)   |
| TORQUE OF FITTING INLET (max)   | 8 Nm (bicone)<br>15 Nm (flared pipe)   |
| PUSHING FORCE (max)             | 30 N   |
| TURNING TORQUE OF SPINDLE (max) | 0.4 Nm   |
| PULL IN CURRENT                 | 200 ÷ 80 mA  |
| OPENING TIME                    | 2 seg (thermocouple optimal position)  |
| CLOSING TIME                    | < 60 seg   |
| PRESSURES RANGE                 | 8 - 100 mbar   |
| GASES OF USE                    | 1st, 2nd y 3th families  |

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use
- Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the “Designed lifetime for safe operation”