



## EU DECLARATION OF CONFORMITY



**Copreci S. Coop.**  
**Araba Ibilbidea, 3**  
**E-20550 Aretxabaleta-GIPUZKOA (Spain)**  
**Tlfn: + 34 943034499**

Declare under our sole responsibility that the product:

| Model                               | PIN<br>AENOR | Description                                                                                        |
|-------------------------------------|--------------|----------------------------------------------------------------------------------------------------|
| CAL 22200<br>CAL 22210<br>CAL 22220 | 99CT953      | Manually operated multifunctional valve with a flame supervision device for gas burning appliances |

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106:2022 Manually operated taps for gas burning appliances
- EN 126: 2025: Multifunctional controls for gas burning appliances
- EN 125:2022 Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2019 Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate first issued on 24/05/2018 and valid until 24/05/2027.

This certificate is valid from 27/02/2026

Iñigo Peñagarikano  
 Copreci, S. Coop.  
 Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

| INSTRUCTIONS                    |                                                                                                                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MODEL                           | CAL 22200, CAL 22220                                                                                                                                                                                          |
| GROUP                           | 1                                                                                                                                                                                                             |
| PURPOSE                         | Built in                                                                                                                                                                                                      |
| CHARACTERISTICS                 | Number of ways: 1<br>Maximum pressure: 100 mbar<br>Reference flow: 0.2 m <sup>3</sup> /h air with 1 mbar.<br>pressure drop<br>Nominal diameter: 6<br>T <sup>a</sup> max.: 150 °C<br>T <sup>a</sup> min.: 0 °C |
| NUMBER OF MECHANICAL CYCLES     | 40000 cycles                                                                                                                                                                                                  |
| MOUNTING POSITION               | multiposition                                                                                                                                                                                                 |
| CONNECTIONS                     | Depending of the manufacturer's requirements                                                                                                                                                                  |
| TORQUE OF FITTING OUTLET (max)  | 8 Nm (bicone)<br>15 Nm (flared pipe)                                                                                                                                                                          |
| TORQUE OF FITTING INLET (max)   | 3 Nm                                                                                                                                                                                                          |
| PUSHING FORCE (max)             | 30 N                                                                                                                                                                                                          |
| TURNING TORQUE OF SPINDLE (max) | 0.2 Nm                                                                                                                                                                                                        |
| PULL IN CURRENT                 | Different options: <ul style="list-style-type: none"> <li>• 200 ÷ 80 mA</li> <li>• 110 ÷ 20 mA</li> <li>• 90 ÷ 10 mA</li> </ul>                                                                               |
| OPENING TIME                    | 2 seg (thermocouple optimal position)                                                                                                                                                                         |
| CLOSING TIME                    | < 60 seg                                                                                                                                                                                                      |
| PRESSURES RANGE                 | 8 - 100 mbar                                                                                                                                                                                                  |
| GASES OF USE                    | 1st, 2nd y 3th families                                                                                                                                                                                       |

| INSTRUCTIONS                    |                                                                                                                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MODEL                           | CAL 22210                                                                                                                                                                                                     |
| GROUP                           | 1                                                                                                                                                                                                             |
| PURPOSE                         | Built in                                                                                                                                                                                                      |
| CHARACTERISTICS                 | Number of ways: 2<br>Maximum pressure: 100 mbar<br>Reference flow: 0.2 m <sup>3</sup> /h air with 1 mbar.<br>pressure drop<br>Nominal diameter: 6<br>T <sup>a</sup> max.: 150 °C<br>T <sup>a</sup> min.: 0 °C |
| NUMBER OF MECHANICAL CYCLES     | 40000 cycles                                                                                                                                                                                                  |
| MOUNTING POSITION               | multiposition                                                                                                                                                                                                 |
| CONNECTIONS                     | Depending of the manufacturer's requirements                                                                                                                                                                  |
| TORQUE OF FITTING OUTLET (max)  | 8 Nm (bicone)<br>15 Nm (flared pipe)                                                                                                                                                                          |
| TORQUE OF FITTING INLET (max)   | 3 Nm                                                                                                                                                                                                          |
| PUSHING FORCE (max)             | 30 N                                                                                                                                                                                                          |
| TURNING TORQUE OF SPINDLE (max) | 0.2 Nm                                                                                                                                                                                                        |
| PULL IN CURRENT                 | Different options: <ul style="list-style-type: none"> <li>• 200 ÷ 80 mA</li> <li>• 110 ÷ 20 mA</li> <li>• 90 ÷ 10 mA</li> </ul>                                                                               |
| OPENING TIME                    | 2 seg (thermocouple optimal position)                                                                                                                                                                         |
| CLOSING TIME                    | < 60 seg                                                                                                                                                                                                      |
| PRESSURES RANGE                 | 8 - 100 mbar                                                                                                                                                                                                  |
| GASES OF USE                    | 1st, 2nd y 3th families                                                                                                                                                                                       |

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use
- Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the "Designed lifetime for safe operation"