



EU DECLARATION OF CONFORMITY



Copreci S. Coop.
Araba Ibilbidea, 3
E-20550 Aretxabaleta-GIPUZKOA (Spain)
Tlfn: + 34 943034499

Declare under our sole responsibility that the product:

Model	PIN AENOR	Description
JFM 22600	99DQ1039	Multifunctional motorized control device with thermoelectric flame monitoring device for appliances burning gaseous fuels managed by an electronic system.

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 126: 2025: Multifunctional controls for gas burning appliances
- EN 125:2022 Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2019: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements
- EN 60730-1:2011: Automatic electrical controls
- EN 60730-2-5:2015: Automatic electrical controls for household and similar use. Particular requirements for automatic electrical burner systems.
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate, on 19/06/2026.

This certificate is valid from 19/06/2026

Unai Gerenabarrena
 Copreci, S. Coop.
 Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

INSTRUCTIONS	
MODEL	JFM 22600
GROUP	2
CLASS	C
PURPOSE	BBQ, Gas Cooking, Heating
CHARACTERISTICS	Number of ways: 2 or 1 Outlets Maximum pressure: 100 mbar Reference flow: 1000 l/hr fully open, with air at 1mbar pressure drop Nominal diameter: 10 Range of T ^a : -20°C to 80°C
NUMBER OF MECHANICAL CYCLES	25.000 cycles x 10 = 250.000 Cycle definitions: OFF, push magnet unit, maximum and 10 modulation from max to min
MOUNTING POSITION	Multipositional
CONNECTIONS	Inlet: 3/8" x 18NPT-2B & 5/8" x 18UNF-2B Outlet: 3/8" x 18NPT-2B & 5/8" x 18UNF-2B Pilot: 3/8" x 24UNF-2B *Las roscas son americanas ya que es un requerimiento del cliente, son roscas normalizadas según la norma ASME B1.1-2024 para las roscas UNF (Unified Inch Screw Thread) y ANSI/ASME B1.20.1-2013 (R2018) para las roscas NPT (American National standard pipe Threads (inch))
TORQUE OF FITTING OUTLET / INLET (max)	3/8"NPT: 15-20 Nm 5/8" *18 UNF :12-15 Nm *Las roscas son americanas ya que es un requerimiento del cliente, son roscas normalizadas según la norma ASME B1.1-2024 para las roscas UNF (Unified Inch Screw Thread) y ANSI/ASME B1.20.1-2013 (R2018) para las roscas NPT (American National standard pipe Threads (inch))
MAGNET UNIT CHARACTERISTICS	Hold in ≤ 180 mA Drop out ≥ 30 mA
TORQUE OF FITTING PILOT OUTLET (max)	8 Nm
TORQUE OF 8 LATERAL HOLES (max)	2 - 2,5 Nm
PRESSURES RANGE	8 - 100 mbar
GASES OF USE	1st, 2nd y 3th families
TORQUE TO FITTING THERMOCOUPLE TO RACORD (max)	4 Nm

2. Instruction manual for use and maintenance intended for the user.

Instruction manual for use and maintenance intended for the user.

- *Component does not require any maintenance. Washing the valve with soapy water or other products may involve deterioration.*
- *Do not pour liquids into the component.*
- *The appliance can only be switched on in the user's presence.*
- *The component must not be manipulated or repaired in any way.*
- *In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.*
- *Not necessary transformation of the component to use another gas.*
- *The installer must check the suitability of the component functions for the intended use.*
- *Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the "Designed lifetime for safe operation"*
- *An inlet strainer must be fitted to prevent the ingress of foreign material (hole dimension not exceeding 1,5mm and prevent the passage of 1 mm diameter pin gauge).*