

Terrazzo Large Chip Repair

Please read instructions thoroughly before beginning any repairs. If you have any questions, please reach out to us. Wear appropriate safety equipment (gloves and masks) when performing any repairs.

Contents

- Terrazzo Base Patch Powder
- Pigment for Color Matching
- Instant Cyanoacrylate Glue in both high & low viscosities

Not Included

- Gloves
- Protective Eyewear
- Respirator
- Razor/Knife/Diamond Sandpaper
- 240-600 Grit Sandpaper as needed
- Spray Bottle with Water
- Sealer as needed

Sensitile Systems - Large Chip Repair

Instructions

1. Make sure that the area you are working in is completely dry and free of dust and debris. Clean the inside of the crack/chip and remove all loose items. Mask the area surrounding the chip with removable tape to protect it.
2. Color match and test your patch powder. Use the provided pigment to adjust the color of the base powder to match your installed slabs. Apply only to a small or inconspicuous area while testing the color.
3. Cover the crack/chip with a layer of the thick glue. Add a layer of the color matched powder to the glue. Then add a layer of the thin glue, sealing the powder to the stone.
4. Repeat layering thick glue, powder, and thin glue until the crack/chip has been filled. Use a razor, knife, or diamond sand paper after layers of the thin glue to level the repaired area as needed. Be careful not to scratch the surrounding area.
5. Once the area is built up, polish with 240 grit sandpaper until the area is flat and conforms to the surrounding area.
6. Polish with 600 grit sandpaper to finish and wipe clean. Mist the surface with water intermittently to prevent it from over heating, Heat in this phase can alter the color.
7. For larger areas, sealer may need to be reapplied. Please contact us for sealer instructions and recommendations as they are project specific.

Please contact us with any questions at (313) 872-6314 or by email at production@sensitile.com