



mitas-tyres.com



Tractor Radial Tyres



HC 2000 New VF (Very High Flexion) tyre for high-horsepower tractors

- Lower inflation pressure provides excellent traction efficiency.
- Better ground protection thanks to reduced soil compaction.
- Higher load capacity for higher haulage efficiency.

Available Sizes					
VF 420/85 R 28	151D	VF 380/95 R 38	154B	VF 480/80 R 46	175D
VF 540/65 R 30	155D	VF 480/70 R 38	172D	VF 380/105 R 50	176D*
VF 540/65 R 30	161D	VF 520/85 R 42	174B	VF 480/80 R 50	181D*
VF 600/70 R 30	165D	VF 650/65 R 42	170D	VF 480/95 R 50	170B
VF 380/85 R 34	149D	VF 710/70 R 42	179D	VF 320/105 R 54	169D*
VF 420/85 R 34	154D	VF 380/90 R 46	173D*	VF 380/105 R 54	168B
VF 540/65 R 34	163D	VF 480/80 R 46	164D		

* Tread pattern HC 1000 for sprayers

Tractor Radial Tyres



Super Flexion Tyre (SFT) Maximum load capacity and traction for powerful machines

- Developed specifically for use on high-horsepower tractors.
- Flexible ultra-strong sidewalls allow low inflation pressures for high load-carrying capacities.
- Maximum traction and outstanding productivity.

Available Sizes			
620/75 R 26 166A8	620/75 R 30 163D	650/75 R 38 169D	580/85 R 42 163D
750/65 R 26 166D	710/55 R 30 159D	650/85 R 38 173D	650/75 R 42 165D
540/65 R 28 142D	710/60 R 30 162D	710/70 R 38 166D	680/80 R 42 180D
600/65 R 28 154D	750/55 R 30 162D	710/70 R 38 171D	710/70 R 42 173D
600/70 R 28 157D	650/60 R 34 159D	800/70 R 38 173D	710/75 R 42 175D
600/70 R 28 161D	650/65 R 34 161D	800/70 R 38 178D	900/60 R 42 180D
540/65 R 30 150D	710/60 R 34 164D	900/60 R 38 172D	IF 710/65 R 46 183D
600/70 R 30 152D	650/65 R 38 157D	900/60 R 38 178D	710/65 R 46 174D

Tractor Radial Tyres



Silent Speed Tyre (SST) Noise-reducing radial tyre for fast, comfortable and quiet road use

- Noise reduction of up to 6 dB(A) in the cab maximises concentration and minimises stress.
- Reduced rolling resistance, long tyre life and high damage resistance.
- Highest possible sustained speed capability of up to 70 km/h.

Available Sizes	
600/65 R 38	153D
650/65 R 38	157D
710/70 R 38	171D
650/65 R 42	165D
710/70 R 42	173D
710/75 R 42	175D

Tractor Radial Tyres



AC 65 Powerful wide tyre for all-round applications

- Gentle ground handling in the field and on grassland.
- Comfortable on the road at high speeds up to 65 km/h.
- Very high transportation capability through large volume of air.
- Extremely economical thanks to excellent traction and low-wear tread compound.

Available Sizes		
320/65 R 16	117D	540/65 R 28 142D
420/65 R 20	125D	600/65 R 28 147D
440/65 R 24	128D	540/65 R 30 150D
480/65 R 24	133D	600/65 R 30 149D
540/65 R 24	140D	540/65 R 34 145D
540/65 R 24	146D	600/65 R 34 151D
440/65 R 28	131D	600/65 R 34 157D
480/65 R 28	136D	540/65 R 38 147D
		600/65 R 38 153D
		650/65 R 38 157D
		650/65 R 38 166D
		650/65 R 38 173D
		710/70 R 38 166D
		650/65 R 42 165D

Tractor Radial Tyres



HC 70 The all-round benchmark in the 70 series wide tyre segment

- Higher load capacity than conventional 70 series.
- Gentle handling of the soil thanks to rounded shoulders and lug design.
- Wide tyre shoulders provide comfortable and safe road performance.
- Low operating costs thanks to minimised slip.

Available Sizes		
320/70 R 24	116D	420/70 R 28 133D
360/70 R 24	122D	480/70 R 28 140D
380/70 R 24	125D	420/70 R 30 134D
420/70 R 24	130D	480/70 R 30 141D
480/70 R 24	138D	480/70 R 30 152D
380/70 R 28	127D	480/70 R 34 143D
		480/70 R 34 155D
		520/70 R 34 148D
		480/70 R 38 145D
		520/70 R 38 150D
		580/70 R 38 155D

Tractor Radial Tyres



AC 85 Modern all-round standard tyre for all applications

- Radial tyre with balanced characteristics for a wide range for applications both on the field and on the road.
- Larger ground contact area makes the tyre well suited for handling grassland.
- Long service life thanks to wear-resistant tread compound.

Available Sizes						
280/85 R 20	112A8	320/85 R 28	124A8	460/85 R 30	145A8	380/95 R 38 147D
280/85 R 24	115A8	340/85 R 28	127A8	380/85 R 34	146A8	420/85 R 38 144A8
320/85 R 24	122A8	380/85 R 28	133A8	420/85 R 34	142A8	460/85 R 38 149A8
340/85 R 24	125A8	420/85 R 28	139A8	420/85 R 34	147A8	520/85 R 38 155A8
380/85 R 24	131A8	380/85 R 30	135A8	460/85 R 34	147A8	480/80 R 42 151A8
420/85 R 24	137A8	420/85 R 30	140A8	340/85 R 38	133A8	520/85 R 42 162A8
280/85 R 28	118A8	420/90 R 30	147A8	380/80 R 38	142A8	480/80 R 46 158A8
						380/90 R 50 151A8
						480/80 R 50 159A8
						480/95 R 50 164D



HC 3000

New Very High Flexion (VF) harvester tyre for Cyclic Field Operation (CFO)

- Less inflation pressure provides excellent traction efficiency.
- Higher load capacity for higher haulage efficiency.
- Larger footprint for better ground protection and reduced soil compaction.

Available Sizes	
VF 1000/65 R 32 CFO*	200A8
VF 580/80 R 34 CFO	178B
VF 520/85 R 42 CFO	177B
VF 580/85 R 42 CFO	183B
VF 710/70 R 42 CFO	190B

* Tread pattern HC 3000 R



SFT CHO

More load at lower tyre pressure

- Maximum load capacity for Cyclic Harvesting Operation.
- Minimum inflation pressure during cyclic harvest operation.
- Good driving stability in road application.
- Reduces soil compaction thanks to a large footprint.
- Fulfils all legal requirements (limited vehicle width).

Available Sizes			
680/85 R 32 CHO	178A8*	800/70 R 38 CHO	178D
800/70 R 32 CHO	175A8	800/70 R 38 CHO	181D
900/60 R 32 CHO	176A8	900/60 R 38 CHO	178D
900/70 R 32 CHO	182A8	900/60 R 38 CHO	181D
900/70 R 32 CHO	188A8	680/80 R 42 CHO	180D
1050/50 R 32 CHO	184A8	800/70 R 42 CHO	182D
1250/50 R 32 CHO	194A8	900/60 R 42 CHO	183D
680/80 R 38 CHO	179D		

* Tread pattern AC 70 G



SFT harvester & AC70 H/G/N

Economical tyre for gentle ground handling on harvesters

- Harvester tyre with high load capacity and low inflation pressure.
- Wide and even distribution of ground pressure minimises pressure on the soil resistance.
- Low vibration on the road.
- High mileage performance.

Available Sizes for SFT harvester				Available Sizes for AC70 H/G/N	
1000/50 R 25	178A8	1050/50 R 32	178A8	650/75 R 32	167A8
1000/50 R 25	175D	1250/50 R 32	188A8	650/75 R 32	172A8
620/75 R 26	166D	1250/50 R 32	194A8	680/85 R 32	173A8
800/70 R 32	175A8	900/60 R 38	178D	680/85 R 32	178A8
900/60 R 32	176A8	580/85 R 42	163D	800/65 R 32	167A8
900/60 R 32	181A8	580/85 R 42	168D	800/65 R 32	172A8
900/70 R 32	188A8	680/80 R 42	180D	800/65 R 32	178A8



AGRITERRA 02

New generation of flotation tyres

- Approved for speed up to 65 km/h.
- Low rolling resistance reduces fuel consumption.
- Rounded shoulders allow better respect for grass stand.

Available Sizes			
500/60 R 22.5 IMP	161D	650/65 R 26.5 IMP	174D
560/45 R 22.5 IMP	152D	710/50 R 26.5 IMP	170D
560/60 R 22.5 IMP	165D	800/45 R 26.5 IMP	174D
600/50 R 22.5 IMP	163D	600/60 R 30.5 IMP **	173D
600/50 R 22.5 IMP	167D	680/60 R 30.5 IMP *	176D
710/45 R 22.5 IMP	165D	750/60 R 30.5 IMP *	181D
600/55 R 26.5 IMP	165D	850/50 R 30.5 IMP	182D
650/55 R 26.5 IMP	169D	800/65 R 32 IMP **	185D

* Tread pattern AGRITERRA 03 ** Tread pattern AGRITERRA 04



High Capacity Municipal (HCM)

Universal quiet running tyre for all terrains and applications

- Particularly suitable for municipal and road maintenance tractors and equipment.
- High durability due to steel belted radial construction and unique design of tread pattern in the central part.
- Exceptional traction characteristics due to more edges on the lugs. Different lugs width in shoulder for better traction in deeper terrain.

Available Sizes			
340/80 R 18 IND	138D	540/65 R 30 IND	156D
360/80 R 24 IND	139D	440/80 R 34 IND	155D
400/80 R 24 IND	144D	480/80 R 34 IND	159D
440/80 R 24 IND	149D	480/80 R 38 IND	161D
400/80 R 28 IND	146D	540/80 R 38 IND	167D
440/80 R 28 IND	151D	650/65 R 42 IND	171D



TI-20

Universal radial tyre suitable for agricultural, construction and road work

- Improved tread pattern can be used even on soft ground.
- Excellent durability.

Available Sizes	
340/80 R 18 IND	143A8
460/70 R 24 IND*	159A8
480/80 R 26 IND	160A8
440/80 R 28 IND	156A8

* Tread pattern TI-22



EM-02

Agricultural tread pattern with excellent traction

- Approved for speeds up to 50 km/h or 90 km/h.
- Good self-cleaning properties.
- Better driving comfort due to the steel breaker.

Available Sizes	
335/80 R 18 (12.5 R 18)	139B
335/80 R 18 (12.5 R 18)	132G
440/70 R 24 (17.5L R 24)	147B
445/70 R 24 (17.5L R 24)*	151G

* Tread pattern MPT-22

Dealer's stamp:

Trelleborg Wheel Systems Czech Republic a.s.
Švehlova 1900/3
106 00 Prague 10
Czech Republic

Complete assortment of tyres you can find on www.mitas-tyres.com or in the Mitas technical documentation.