

Super Flexion Tyre SFT (vervolg)

Technische gegevens en draagvermogen (vervolg)

Bandmaat LI/SS index	Velg * (toege- staan)	Sectie- breedte (mm)	Buiten- diameter (mm)	Statische radius belast (mm)	Afrol- omtrek (mm)	Snelheids- radius index	Draagvermogen van de band (kg) bij bandenspanning (bar)										Snelheid (km/u)	
							0,4	0,6	0,8	1,0	1,2	1,4	1,6	2,0	2,4	2,8	3,2	
900/60 R 32 181 A8 (178 B)	DW 27 B DW 30 B	857 890	1 910	850	5 700	925		3 890	4 315	4 250	4 650	5 020	5 450	5 950	6 500	7 025	7 500	50
								4 165	4 615	5 000	5 465	5 900	6 000	6 535	7 100	7 720	8 250	40
								4 320	4 790	5 185	5 670	6 120	6 660	7 255	7 880	8 570	9 160	30
								4 790	5 305	5 745	6 285	6 785	7 380	8 040	8 735	9 495	10 150	20
								5 060	5 610	6 070	6 640	7 170	7 800	8 495	9 230	10 810	11 550	10
900/70 R 32 188 A8 (185 B)	DW 27 B DW 30 B	895 925	2 050	896	6 050	975		4 615	5 120	5 555	5 530	6 060	6 700	7 215	7 750	8 415	9 250	50
								4 940	5 480	5 945	6 080	6 660	7 300	7 925	8 500	9 250	10 000	40
								5 125	5 685	6 165	6 505	7 125	7 810	8 480	9 095	9 895	10 700	30
								5 675	6 300	6 830	7 475	8 195	8 980	9 750	10 455	11 375	12 300	25
								6 000	6 660	7 220	7 905	8 660	9 490	10 305	11 050	12 025	13 000	20
1050/50 R 32 178 A8 (178 B)	36.00 VA	1 015	1 890	855	5 640	875		4 200	4 655	5 045	5 515	5 955	6 500	7 055	7 500			50
								4 495	4 985	5 395	5 900	6 370	6 955	7 550	8 025			40
								4 665	5 170	5 595	6 120	6 610	7 215	7 830	8 325			25
								5 170	5 730	6 200	6 785	7 320	7 995	8 680	9 225			20
								5 465	6 055	6 555	7 170	7 740	8 450	9 175	9 750	11 250		10
1250/50 R 32 188 A8 (185 B)	44" 40"	1 220 1 180	2 020	890	6 000	975		5 020	5 515	5 655	6 265	6 960	7 750	8 500	9 250	10 040	10 900	50
								4 730	5 060	5 905	6 645	7 265	8 000	8 740	9 490	10 240	11 000	40
								5 250	5 815	6 125	6 895	7 640	8 490	9 435	10 370	11 300	12 245	25
								5 815	6 620	6 785	7 640	8 470	9 410	10 455	11 490	12 300	13 570	20
								6 620	7 725	8 695	9 640	10 710	11 900	13 075	14 000	15 445	16 520	10
1250/50 R 32 194 A8 (191 B)	44" 40"	1 220 1 180	2 020	890	6 000	975		4 730	5 060	5 515	6 210	6 885	7 650	8 500	9 340	10 040	11 800	50
								5 250	5 815	5 905	6 645	7 265	8 000	8 740	9 490	10 240	11 800	40
								5 815	6 620	6 785	7 640	8 470	9 410	10 455	11 490	12 300	13 570	25
								6 620	7 725	8 695	9 640	10 710	11 900	13 075	14 000	15 445	16 520	20
																		10
650/60 R 34 159 D (162 A8)	DW 20 B DW 21 B DW 23 B	650 660 680	1 638	740	4 935	775		2 430	2 755	2 795	3 055	3 355	3 650	4 040	4 375			65
								3 105	3 525	2 995	3 365	3 695	4 040	4 455	4 710	5 000		50
								2 550	2 895	3 215	3 515	3 860	4 200	4 645	5 030	5 320		40
							2 660	3 105	3 525	3 915	4 280	4 700	5 110	5 655	6 125	6 565		30
																		10
650/65 R 34 161 D (164 A8)	DW 20 B DW 21 B DW 23 B	664 674 694	1 719	769	5 116	825		3 070	3 375	3 475	3 745	4 040	4 375	4 710	5 000			65
								2 850	3 205	3 320	3 600	3 880	4 200	4 545	4 895	5 230		50
								2 995	3 365	3 475	3 745	4 040	4 375	4 710	5 000			40
							3 150	3 645	4 095	4 500	4 860	5 165	5 425	5 775	6 075	6 940		30
																		10
1610/60 R 34 174 D (167 A8)	DW 23 B	700	1 700	770	5 060	825		3 205	3 375	3 475	3 745	4 040	4 375	4 710	5 000			65
								2 785	3 160	3 310	3 635	3 880	4 185	4 500	5 060			50
							3 050	3 560	4 040	4 490	4 905	5 350	5 775	6 470	7 000	7 500		40
																		30
																		10
650/65 R 38 157 D (160 A8)	W 18 L DW 20 B DW 21 B	645 660 670	1 828	810	5 445	875		3 000	3 230	3 380	3 655	3 905	4 125	4 330				65
								3 150	3 370	3 510	3 835	4 080	4 375	4 645	5 060			50
							3 315	3 835	4 310	4 490	4 905	5 350	5 775	6 470	7 000	7 500		40
																		30
																		10
650/75 R 38 169 D (172 A8)	DW 21 B DW 20 B DW 23 B	667 657 687	1 944	872	5 795	925		3 445	3 920	4 375	4 645	4 880	5 120	5 425	5 800			65
								3 620	4 120	4 590	5 030	5 480	5 900	6 300	6 670			50
							3 760	4 405	5 015	5 585	6 125	6 505	6 825	7 590	8 120	8 700		40
																		30
																		10
650/85 R 38 173 D (176 A8)	DW 23 B DW 20 B DW 21 B	720 688 699	2 070	920	6 130	975		3 855	4 390	4 690	5 140	5 455	5 725	6 375	6 825			65
								4 050	4 610	4 890	5 360	5 690	6 000	6 650	7 100			50
							4 210	4 930	5 610	6 250	6 855	7 275	7 630	8 500	9 100	9 750		40
																		30
																		10
710/70 R 38 166 D (169 A8)	DW 23 B DW 25 B	736 756	1 958	870	5 780	925		3 715	4 055	4 520	4 955	5 280	5 565	5 800				65
							4 055	3 905	4 445	4 950	5 425	5 785	6 095	6 300	6 720			50
								4 750	5 410	6 025	6 605	7 045	7 420	7 950				40
																		30
																		10
710/70 R 38 171 D (174 A8)	DW 23 B DW 25 B	736 756	1 958	870	5 780	925		3 715	4 055	4 520	4 955	5 280	5 565	5 800				65
							4 055	3 905	4 445	4 950	5 425	5 785	6 095	6 300	6 720			50
								4 750	5 410	6 025	6 605	7 045	7 420	7 950				40
																		30
																		10
800/70 R 38 173 D (176 A8)	DW 25 B DW 27 B	765 787	2 052	911	6 090	975		4 480	4 890	5 190	5 690	6 070	6 400	6 720				65
							4 890	4 705	5 360	5 970	6 545	6						

